

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-025-12360

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Harry Leonard(NCT-G)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Chevron USA, Inc.

8. Well No.
41

3. Address of Operator
15 Smith Rd. Midland, Tx 79705

9. Pool name or Wildcat
Dollarhide-Queens

4. Well Location

Unit Letter F : 1650 feet from the north line and 1650 feet from the west line

Section 4 Township 25-S Range 38-E NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Tag 7" CIBP @ 3650 spot 40sx(Queens)Tag @ 3439
2. Displace hole w/MLF 9.5# Brine w/25# Gel P/BBL.
3. Spot 40sx plug fr/1175-1075(T-salt)Tag @ 982
4. Perf 4 holes @ 520 & 450 unable to sqz spot 40sx plug fr/570-400(9 5/8 shoe)Tag @ 372
5. Csg leak fr/40 to 155 circ cmt behind 9 5/8 csg w/75sx (Tag @ 38) fr/surf
6. Fill csg w/cmt fr/38 to surf Install dry hole marker 4-11-03

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE MANAGER/SUNSET DATE 4-11-03

Type or print name Jimmy BAGLEY Telephone No. 915 561-8600
(This space for State use)

APPROVED BY [Signature] ORIGINAL SIGNED BY GARY W. WINK DATE APR 18 2003
Conditions of approval, if any: OC FIELD REPRESENTATIVE II/STAFF MANAGER