

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-37204		5. Indicate Type of Lease STATE ☐ FEE ☒	
		State Oil & Gas Lease No.		7. Lease Name or Unit Agreement Name CSW 17	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG				8. Well No. 001	
1a. Type of Well: OIL WELL ☐ GAS WELL ☒ DRY ☒ OTHER _____				9. Pool name or Wildcat Wildcat S163617J; Morrow (Gas)	
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER					
2. Name of Operator Chesapeake Operating, Inc.					
3. Address of Operator P. O. Box 11050 Midland, TX 79702-8050					
4. Well Location Unit Letter N 475 Feet From The South Line and 2185 Feet From The West Line Section 17 Township 16S Range 36E NMPM Lea County					
10. Date Spudded 06/27/2005		11. Date T.D. Reached 07/29/2005		12. Date Compl. (Ready to Prod.) 3932 GR	
13. Elevations (DF& RKB, RT, GR, etc.) 3932 GR		14. Elev. Casinghead		15. Total Depth 12400	
16. Plug Back T.D. 0		17. If Multiple Compl. How Many Zones? 0		18. Intervals Drilled By Rotary Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name				20. Was Directional Survey Made Yes	
21. Type Electric and Other Logs Run Quad Combo; GR/Neutron				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE		WEIGHT LB./FT.		DEPTH SET	
HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED	
13 3/8"		48#		482'	
8 5/8"		32#		4340'	
17 1/2"		415 sx cmt.		1025 sx cmt	
11"		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
24. LINER RECORD					
SIZE		TOP		BOTTOM	
SACKS CEMENT		SCREEN		TUBING RECORD	
SIZE		DEPTH SET		PACKER SET	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
25. TUBING RECORD					
SIZE		TOP		BOTTOM	
SACKS CEMENT		SCREEN		TUBING RECORD	
SIZE		DEPTH SET		PACKER SET	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
1025 sx cmt		1025 sx cmt		1025 sx cmt	
26. PERFORATION RECORD (interval, size, and number)					
DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
1025 sx cmt		Cmt. plugs attached			
1025 sx cmt		1025 sx cmt			
1025 sx cmt		1025 sx cmt			
1025 sx cmt		1025 sx cmt			
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
DEPTH INTERVAL					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico	
T. Anhy	T. Canyon		T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn 11442		T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka 11795		T. Pictured Cliffs	T. Penn. "D"
T. Yates 3198	T. Miss 12181		T. Cliff House	T. Leadville
T. 7 Rivers 3496	T. Devonian		T. Menefee	T. Madison
T. Queen 4116	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg 4525	T. Montoya		T. Mancos	T. McCracken
T. San Andres 4877	T. Simpson		T. Gallup	T. Ignacio Otzte
T. Glorieta 6351	T. McKee		Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger		T. Dakota	T.
T. Blinebry	T. Gr. Wash		T. Morrison	T.
T. Tubb 7572	T. Delaware Sand		T. Todilto	T.
T. Drinkard 7701	T. Bone Springs		T. Entrada	T.
T. Abo 8291	T. 12400Morro		T. Wingate	T.
T. Wolfcamp 9647	T.		T. Chinle	T.
T. Penn 11034	T.		T. Permian	T.
T. Cisco (Bough C)	T.		T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
 No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	2015	2015	Redbeds				
2015	3198	1183	Anhy/Salt				
3198	4525	1327	Sand/Salt/Anhy/Shale				
4525	4877	352	Dolo/Sand				
4877	6351	1474	Dolo				
6351	7701	1350	Dolo/Sd/Shale				
7701	9647	1946	Dolo/Anhy				
9647	11034	1387	Limestone				
11034	11442	408	Shale				
11442	11795	353	Limestone				
11795	12069	274	Shale & Sand				
12069	12181	112	Limestone & Shale				
12181	12400	219	Limestone/shale/chert				

CSW 17 Well #1
Lea County, New Mexico
Page 2 – Attachment to Form C-105

CEMENT PLUGS:

Plug	#1:	12,400 – 12,300'	25 sx Premium cmt.
	#2:	11,055 – 10,944'	40 sx Premium cmt.
	#3:	9630 – 9530'	30 sx Premium cmt.
	#4:	7615 – 7515'	30 sx Premium cmt.
	#5:	6,395 – 6295'	25 sx Premium cmt.
	#6:	4,390' – 4290'	60 sx Premium Plus cmt.
	#7:	2,050' – 1950'	30 sx Premium Plus cmt.
	#8:	532' – 432'	30 sx Premium Plus cmt.
	#9:	100' – 0'	30 sx Premium Plus cmt.