

Submit to Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French, Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
Revised June 10, 2003

WELL API NO.

30-025-37266

5. Indicate Type Of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____

b. Type of Completion:

NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER _____

7. Lease Name or Unit Agreement Name

South Hobbs (GSA) Unit

2. Name of Operator

Occidental Permian Limited Partnership

8. Well No.

243

3. Address of Operator

P.O. Box 4294, Houston, TX 77210-4294

9. Pool name or Wildcat

Hobbs; Grayburg - San Andres

4. Well Location

SHL: Unit Letter F : 1660 Feet From The North Line and 2106 Feet From The West Line
BHL: F 1840 North 2484 West
Section 4 Township 19-S Range 38-E NMPM Lea County

10. Date Spudded

6/30/05

11. Date T.D. Reached

7/6/05

12. Date Compl. (Ready to Prod.)

8/1/05

13. Elevations (DF & RKB, RT, GR, etc.)

3616' GR

14. Elev. Casinghead

15. Total Depth

4367'

16. Plug Back T.D.

4301'

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

4367'

Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name

4104' - 4262'; Grayburg - San Andres

20. Was Directional Survey Made

Yes

21. Type Electric and Other Logs Run

CN/SGR/CCL; NGR/SL/CCL

22. Was Well Cored

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
16	Conductor	40	26	100 sx.	
8-5/8	24	1508	12-1/4	750	
5-1/2	15.5	4367	7-7/8	950-sx.	

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-7/8	4023'	

26. Perforation record (interval, size, and number)

4104' - 4262', 2 SPF (172 holes)

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED
4104' - 4262' 3864 gal. 15% NEFE HCL

28. PRODUCTION

Date First Production 8/10/05	Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping - ESP, Reda					Well Status (Prod. or Shut-in) Producing	
Date of Test 8/10/05	Hours Tested 24	Choke Size N/A	Prod'n For Test Period	Oil - Bbl. 29	Gas - MCF 75	Water - Bbl. 1644	Gas - Oil Ratio 2586
Flow Tubing Press. N/A	Casing Pressure 35	Calculated 24-Hour Rate	Oil - Bbl. 29	Gas - MCF 75	Water - Bbl. 16440	Oil Gravity - API - (Corr.) 34	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Sold

Test Witnessed By

T. Summers

30. List Attachments

Logs (2 ea.): Deviation Report; Directional Survey

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Mark Stephens
E-mail address Mark Stephens@oxy.com

Printed Name Mark Stephens

Title Reg. Comp. Analyst Date 8/22/05

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northeastern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 3411	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3745	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4034	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp		T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 3937 to 4277
 No. 2, from to

No. 3, from to
 No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet
 No. 2, from to feet
 No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
3411	3745	334	Mixed anhydrite & silt with minor dolomite				
3745	3937	192	Mixed anhydrite, silt, and dolomite				
3937	4034	97	Mixed silt & dolomite with minor anhydrite				
4034	4301	267	Dolomite				