abandoned well. Use Form 3160-3 (APD)	S ON WELI II or to re-en for such prop	LS		RM APPROVED 1 B No. 1004-0137 xpires: March 31, 2007 No.	
SUNDRY NOTICES AND REPORT Do not use this form for proposals to dril abandoned well. Use Form 3160-3 (APD) SUBMIT IN TRIPLICATE- Other instruction	S ON WELI II or to re-en for such prop	LS	5. Lease Serial 1	· · · · · · · · · · · · · · · · · · ·	
SUNDRY NOTICES AND REPORT Do not use this form for proposals to dril abandoned well. Use Form 3160-3 (APD) SUBMIT IN TRIPLICATE- Other instruction	S ON WELI II or to re-en for such prop	LS	NM 0113		
Do not use this form for proposals to dril abandoned well. Use Form 3160-3 (APD) SUBMIT IN TRIPLICATE- Other instruction	ll or to re-en for such prop		1402 01104	5	
SUBMIT IN TRIPLICATE- Other instruction		Do not use this form for proposals to drill or to re-enter an			
	ons on revers	osals.	N/A	<u></u>	
1. 1 ype of well Gas Well Other	SUBMIT IN TRIPLICATE- Other instructions on reverse side. 1. Type of Well			 If Unit or CA/Agreement, Name and/or No N/A 8. Well Name and No. Southeast Lusk 34 Federal #3 	
2. Name of Operator Edge Petroleum Operating Company, Inc.			9. API Well	No.	
	3b. Phone No. (include area code) 713-654-8960		30-025-37358 10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 35, T19S, R32E 330' FNL & 330' FWL				Lusk Delaware	
		11. County or Lea Cour	Parish, State nty, New Mexico		
12. CHECK APPROPRIATE BOX(ES) TO INDI	CATE NATURE	OF NOTICE, F	1	••	
TYPE OF SUBMISSION		OF ACTION			
	eepen	Production (St	art/Resume)	Water Shut-Off	
	acture Treat	Reclamation	Į	Well Integrity	
	ew Construction	Recomplete	L	Other	
Einel Ahan donmant Nation	ug and Abandon ug Back	U Temporarily A			
As per our conversation with Joe Lara with the Bureau of Lan			lge	completed, and the operator ha	
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf	sing Program as fo ol (Stage Collar) a r is to be set inside face.	ollows: above an e the	ge		
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer	sing Program as fo ol (Stage Collar) a r is to be set inside face.	ollows: above an e the	lge		
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf	sing Program as fo ol (Stage Collar) a r is to be set inside face.	ollows: above an e the	lge	37320 25 26 2	
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf	sing Program as fo ol (Stage Collar) a r is to be set inside face.	ollows: above an e the	lge		
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf	sing Program as fo ol (Stage Collar) a r is to be set inside face.	ollows: above an e the	lge		
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf	sing Program as fo ol (Stage Collar) a r is to be set inside face.	ollows: above an e the	lge		
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf We propose the top of cement to be at approximately 2400' f	sing Program as fo ol (Stage Collar) a r is to be set inside face.	ollows: above an e the	lge		
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf We propose the top of cement to be at approximately 2400' f	sing Program as fo ol (Stage Collar) a r is to be set inside face.	ollows: above an e the duction casing.	lge		
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf We propose the top of cement to be at approximately 2400' f 10-3/4" casing at 2950 +/ Cement will be circulated to surf We propose the top of cement to be at approximately 2400' f 10-3/4" casing at 2950 +/ Cement will be circulated to surf we propose the top of cement to be at approximately 2400' f 10-3/4" casing at 2950 +/ Cement will be circulated to surf we propose the top of cement to be at approximately 2400' f 10-3/4" casing at 2950 +/ Cement will be circulated to surf we propose the top of cement to be at approximately 2400' f	sing Program as fo ol (Stage Collar) a r is to be set inside face. for the 4-1/2" prod	ollows: above an e the duction casing. asultant	lge 		
Petroleum would like to propose an Alternate Cement and Cas On the 7-5/8" casing set at 4270', we propose to set a DV To External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf We propose the top of cement to be at approximately 2400' f 14. Ihereby certify that the foregoing is true and correct Name (Printed/Typed) Lindsay Truesdell	sing Program as fo ol (Stage Collar) a r is to be set inside face. for the 4-1/2" prod Title Con L Date	ollows: above an e the duction casing.)8/11/2005	27320,25262	
Petroleum would like to propose an Alternate Cement and Caso On the 7-5/8" casing set at 4270', we propose to set a DV Tot External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf We propose the top of cement to be at approximately 2400' f 14. Ihereby certify that the foregoing is true and correct Name (Printed/Typed) Lindsay Truesdell Signature Approved by /S/ JOE G. Lara	sing Program as fo ol (Stage Collar) a r is to be set inside for the 4-1/2" pro- Title Con Date ERAL OR ST.	ollows: above an e the duction casing.)8/11/2005 USE	AUG 2 5 2	
Petroleum would like to propose an Alternate Cement and Caso On the 7-5/8" casing set at 4270', we propose to set a DV Tot External Casing Packer (ECP). The External Casing Packer 10-3/4" casing at 2950 +/ Cement will be circulated to surf We propose the top of cement to be at approximately 2400' f 14. Ihereby certify that the foregoing is true and correct Name (Printed/Typed) Lindsay Truesdeli Signature Signature THIS SPACE FOR FEDE	sing Program as fo ol (Stage Collar) a r is to be set inside for the 4-1/2" pro- Title Con Date ERAL OR ST. 	ollows: above an e the duction casing. asultant ATE OFFICE Seum Eng)8/11/2005 USE gineer Dat	AUG 2 5 2	

Kz