

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-025-0109600
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No. K-3657
Lease Name or Unit Agreement Name State of NM T
Well No. 1
Pool name or Wildcat Baum Upper Penn

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
Name of Operator Dominion Oklahoma Texas Expl. & Prod. Inc.	
Address of Operator 14000 Quail Springs Parkway Suite 600 Oklahoma City, OK 73134	
Well Location Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line Section 32 Township 13-S Range 33-E NMPM Lea County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 4267	

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.


4-4-03 Set CIBP @ 7350' on wireline Approved by Bill Prichard with OCD. Circulate well with plugging mud. Spot 25 sks of cement on top of CIBP

4-7-03 Attempt to cut & pull 4 1/2" casing from 4063'. Unable to pull off slips. Squeezed 40 sks of cement 4063' Tagged @ 3850'

4-8-03 Perf @ 1700' Squeezed 40 sks of cement under a packer Tagged TOC @ 1574'. Perf @ 357' Squeezed 50 sks of cement into perfs leaving 4 1/2 casing full to surface (TOC behind 4 1/2 203')

Cut off wellhead and anchors 3'BGL installed dry hole marker. Clean location

Approved as to plugging of the Well Bore.  
Liability under bond is retained until  
surface restoration is completed.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

DATE

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY

OC FIELD REPRESENTATIVE II/STAFF MANAGER

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAY 01 2003