N.M. Oil Cons. Division 1525 N. French Dr.

A Wended 1004-0135

	LAND MANAGEMEN I	31, 1993
SUNDRY NOTICES	AND REPORTS ON WELLS	5. Lease Designation and Serial No. NM-14791
Do not use this form for proposals to dr	ill or to deepen or reentry to a different reservoir. FOR PERMIT-" for such proposals	6. If Indian, Allottee or Tribe Name
SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
Type of Well		1
Oil Gas Well X Other		8. Well Name and No.
2. Name of Operator		New Mexico A Federal #4
STRATA PRODUCTION COMPANY 3. Address and Telephone No. P. O. Box 1030		9. API Well No.
3. Address and Telephone No. P. O. BOX 1030 Roswell, New Mexico 88202-1030 505-622-1127 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1980' FNL & 660' FEL Section 4-21S-32E		30-025-30988 10. Field and Pool, or Exploratory Area
		Hat Mesa Delaware
		11. County or Parish, State
		Lea County, New Mexico
CHECK APPROPRIATE BOX	X(s) TO INDICATE NATURE OF NOTICE	, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
X Notice of Intent	X Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
**	OTHER	Dispose Water (Note: Report results of multiple completion on Well
Strata Production Company promanner.	SHOE PLUG oposes to plug and abandon the New Mex Styles of 180 F	the state of the s
1. Set CIBP at 6700'. Place	35' of cement on top. Circulate hole with	(4562-212) 1516
 Set CIBP at 6700'. Place Set first plug at 3200' - 33 	35' of cement on top. Circulate hole with	(4) 62 -7112) + FL
 Set CIBP at 6700'. Place Set first plug at 3200' - 33 Set second plug at 1320' Set surface plug with 10 st 	35' of cement on top. Circulate hole with 2.5 300' with 20 sacks Class "C" cement. - 1420' with 20 sacks Class "C" cement. sacks Class "C" cement. Spot 9.5# per ga	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug.
nanner. 1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 s 5. Cut off wellhead, clean lo	35' of cement on top. Circulate hole with 25 sacks Class "C" cement. 25' - 1420' with 20' sacks Class "C" cement.	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED APPROVED MAY 5 2003
nanner. 1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 s 5. Cut off wellhead, clean lo	35' of cement on top. Circulate hole with 2.5 sacks Class "C" cement. - 1420' with 20 sacks Class "C" cement. sacks Class "C" cement. Spot 9.5# per gate cation and reclaim surface.	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED MAY 5 2003
1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 s 5. Cut off wellhead, clean lo	35' of cement on top. Circulate hole with 25 sacks Class "C" cement. - 1420' with 20 sacks Class "C" cement. sacks Class "C" cement. Spot 9.5# per ga	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED APPROV
1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 s 5. Cut off wellhead, clean lo APROVED FOR 3 AV 605 The COMPANY of the foregoing is true and signed with the foregoing with the foregoin	35' of cement on top. Circulate hole with 2.5 300' with 20 sacks Class "C" cement. - 1420' with 20 sacks Class "C" cement. sacks Class "C" cement. Spot 9.5# per gate cation and reclaim surface. Plugging Proceeds Title Production Analyst	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED APPROV
nanner. 1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 s 5. Cut off wellhead, clean locations APPROVED FOR 3 AV 605 I hENDING at the foregoing is true and assigned with the foregoing with the foregoing is true and assigned with the foregoing with the fo	35' of cement on top. Circulate hole with 2.5 acks Class "C" cement. - 1420' with 20 sacks Class "C" cement. Sacks Class "C" cement. Spot 9.5# per gate cation and reclaim surface. Proceeding 1 in 19 proceeding 1 in 19 procedure.	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED APPROV
1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 second plug at 1320' 5. Cut off wellhead, clean locations of approval, i.	35' of cement on top. Circulate hole with 25 sacks Class "C" cement. - 1420' with 20 sacks Class "C" cement. sacks Class "C" cement. Spot 9.5# per gate cation and reclaim surface. Plugging Title Production Analyst APPROVAL SUBJE	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED APPROV
1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 s 5. Cut off wellhead, clean locations of approval, is	35' of cement on top. Circulate hole with 2.5 300' with 20 sacks Class "C" cement. - 1420' with 20 sacks Class "C" cement. sacks Class "C" cement. Spot 9.5# per gate cation and reclaim surface. Plugging Proceeding Proceeding Proceeding Proceeding Proceeding Procedure Proce	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED APPROV
1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 second plug at 1320' 5. Cut off wellhead, clean locations of approval, i.	35' of cement on top. Circulate hole with 2.5 300' with 20 sacks Class "C" cement. - 1420' with 20 sacks Class "C" cement. sacks Class "C" cement. Spot 9.5# per gate cation and reclaim surface. 1420	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED APPROV
manner. 1. Set CIBP at 6700'. Place 2. Set first plug at 3200' - 33 3. Set second plug at 1320' 4. Set surface plug with 10 s 5. Cut off wellhead, clean lo APROVED FOR 3 A J 605 I hENDING at the foregoing is true and Signed AJ 605 (This space for Federal or State office use) Approved by Conditions of approval, i.	35' of cement on top. Circulate hole with 2.5 300' with 20 sacks Class "C" cement. - 1420' with 20 sacks Class "C" cement. sacks Class "C" cement. Spot 9.5# per gate cation and reclaim surface. Plugging Proceeding Proceeding Proceeding Proceeding Proceeding Procedure Proce	9.5# per gallon mud. ENTERED IN AFMSS allon mud between each plug. APPROVED APPROVED APPROVED APPROVED Date CT TO CT TO