Office	State of	New Mexico	Form C-103
DISTRICT 1625 N. French Dr., Hobbs NM 88240	Energy, Minerals a	nd Natural Resources	Revised March 25, 1999
DISTRICT II 1301 W. Grand Avenue, Artesia NM 88210	OIL CONSERVATION DIVISION		WELL API NO. 30-025-35964
DISTRICT III	1220 00411 011 1411010 211		5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec NM 87410 Santa Fe, New Mexico 87504-2088			STATE X FEE
DISTRICT IV 1220 S. St. Francis Dr., Santa Fe, NM 87505			6. State Oil & Gas Lease No.
			VO-6649
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name
1. Type of Well:			West Echols State Unit
Oil Well Gas Well X Other			
2. Name of Operator			8. Well No.
Yates Petroleum Corporation			1
3. Address of Operator			9. Pool Name or Wildcat
105 South 4th Str., Artesia, NM 88210			Wildcat Mississippian
4. Well Location			
Unit Letter J: 1980	feet from the South	line and1980	feet from the <u>East</u> line
Section 17	Township 11S Range	38E NMPM	County Lea
10. E	Elevation (Show whether DF, RKI 3904' GR	B, RT, GR, etc.)	
11. Check Appropriate Bo	ox to Indicate Nature of Notic	e Report or Other Data	The state of the s
	NTENTION TO:	SUBSEQUENT	DEDORT OF:
PERFORM REMEDIAL WORK			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT X
PULL OR ALTER CASING	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB	
OTHER:		OTHER:	 1
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.			
5-15-03 to 5-19-03 P&A well as follows:			
RIH w/5-1/2" CIBP and set @ 6150'. Cap w/35' cement. RIH w/tubing open-ended to 6100'. Circulated hole w/mud-laden fluid. Pull uphole to 4850'. Load hole w/mud-laden fluid. Spotted 50 sx Class C Neat. WOC. Tagged plug @ 4338'. Perforated 5-1/2" casing @ 2278'. RIH w/open-ended tubing to 2329'. Spotted 25 sx Class C Neat. WOC. Tagged plug @ 2095'. Perforated 5-1/2" casing @ 445'. Circulated 120'sx Class C Neat down 5-1/2" casing and up to surface of 8-5/8" casing. Cut off wellhead. Installed by hole markers. WELL IS PLUGGED AND ABANDONED. FINAL REPORT.			
Approved as to plugging of the Well Bore. Liability under bond is retained until surface restoration is completed. Thereby certify that the information above a true and complete to the best of my knowledge and belief.			2000 PT ST
(/a			
SIGNATURE	Drawns TITLE	Regulatory Compliance Techni	cian DATE 5/22/03
	mi Davis		Telephone No. 505-748-1471
APPROVED BY 1 2 AND 1 1 2 AND			
APPROVED BY Law W. W. METHELD REPRESENTATIVE II/STAFF MANAGER DATE			