State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 5-27-2004

FILE IN TRIPLICATE	OIL CONSERVA	ATION DIVISION		
DISTRICT I 1625 N. French Dr. , Hobbs, NM 88240	1220 South St. Francis Dr. Santa Fe, NM 87505		WELL API NO.)25-37152
<u>DISTRICT II</u>			5. Indicate Type of Lease	
1301 W. Grand Ave, Artesia, NM 88210			STATE X	FEE
DISTRICT III			6. State Oil & Gas Lease No	0.
1000 Rio Brazos Rd, Aztec, NM 87410	THOUGH AND DEPONTS ON WE		7. Lease Name or Unit Agre	eament Name
SUNDRY NOTICES AND REPORTS ON WELLS				
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (Form C-101) for such proposals.)			NORTH HOBBS (G/SA) UNIT Section 24	
1. Type of Well:			8. Well No. 622	
Oil Well Gas Well Other Injector				
2. Name of Operator			9. OGRID No. 157984	,
Occidental Permian Ltd. 3. Address of Operator			10. Pool name or Wildcat	HOBBS (G/SA)
1017 W. Stanolind Rd., HOBBS,	NM 88240 505/39	7-8200		
4. Well Location				
Unit Letter J: 2482	Feet From The South		t From The east	Line
Section 24	Township 18-S 11. Elevation (Show whether DF, RF)	Range 37-F	E NMPM	LEA County
	3670' GR	D, Ar GA, Cit.)		
Pit or Below-grade Tank Application	or Closure			
Pit Type Depth of Groun	d Water Distance from n	earest fresh water well	Distance from nearest	t surface water
Pit Liner Thickness mil	Below-Grade Tank: Volume	bbls; Construction Ma	terial	
12	L. A	ture of Nation Domant on (Oth on Data	
12. Chec NOTICE OF INT	k Appropriate Box to Indicate Na ENTION TO:		SEQUENT REPORT	OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERI	ING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OP	NS. PLUG	& ABANDONMENT
PULL OR ALTER CASING	Multiple Completion	CASING TEST AND CEMEN	NT JOB	
OTHER:		OTHER:	New Well Complete	ion
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any				
	For Multiple Completions: Attach w			
1 BUBU Deill out DV tool @2490), To a BDTD @4241,			
 RUPU. Drill out DV tool @3480'. Tag PBTD @4341'. Perforate the following intervals; 4174-80, 4188-4208, 4228-38, 4244-62, 4270-88, and 4297-4311 using 2 spf, 120 deg sp ph. (182 holes). 				
	4100 g 15% NEFE HCL acid in 49			
	XL on/off tool w/1.875 "F" nipple		g . Pkr set @4109'.	
 Circ csg w/100 bbl pkr fluid. Tes RDPU. Clean Location. 	st csg to 620 psi for 30 min and cha	rt for the NMOCD.		
o. RDI o. Cican Escation.				71
Rig Up Date: 08/17/2005				2° 48 28 29 29 29 29 29 29 29 29 29 29 29 29 29
Rig Down Date: 08/20/2005			الله	(a) 1 (c)
				4 A
I hereby certify that the information above is constructed or	true and complete to the best of my know	ledge and belief. I further certify	that any pit or below-grade tar	nk has been/will be
closed according to NMOCD guidelines	, a general permit	or an (attached) alternativ	e OCD-approved	The state of the s
SIGNATURE Total	Libert	_ ·	npletion Specialist D.	 ATE 08/23/2005
TYPE OR PRINT NAME Robert Gill	pert AE-mail address:	robert_gilbert@oxy.com	TELEPHONE 1	
For State Use Only	1,10			
APPROVED BY Lawly). Wink	TITLE	E. Bulling Bank	DATE SFP 1 9 26
CONDITIONS OF APPROVAL HANY: OC FIELD REPRESENTATIVE II/STAFF MANAGER OC FIELD REPRESENTATIVE II/STAFF MANAGER				

