

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003 WELL API NO. 30-025-37305 5. Indicate Type of Lease STATE ☐ FEE ☒ State Oil & Gas Lease No.
--	---	---

WELL COMPLETION OR RECOMPLETION REPORT AND LOG											
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER		7. Lease Name or Unit Agreement Name GRIZZELL									
2. Name of Operator Apache Corporation		8. Well No. 14									
3. Address of Operator 6120 South Yale, Suite 1500 Tulsa, OK 74136-4224		9. Pool name or Wildcat Penrose Skelly; Grayburg (50350)									
4. Well Location Unit Letter O : 330 Feet From The South Line and 1750 Feet From The East Line Section 8 Township 22S Range 37E NMPM Lea County											
10. Date Spudded 07/02/2005	11. Date T.D. Reached 07/10/2005	12. Date Compl. (Ready to Prod.) 07/25/2005	13. Elevations (DF& RKB, RT, GR, etc.) 3403								
15. Total Depth 4610'	16. Plug Back T.D. 3895' RBP	17. If Multiple Compl. How Many Zones? 	18. Intervals Drilled By X								
19. Producing Interval(s), of this completion - Top, Bottom, Name Grayburg			20. Was Directional Survey Made No								
21. Type Electric and Other Logs Run DLL/MG, SD/DSN			22. Was Well Cored No								
23. CASING RECORD (Report all strings set in well)											
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE								
8-5/8"	24#	432'	12-1/4"								
5-1/2"	17#	4610'	7-7/8"								
CEMENTING RECORD		AMOUNT PULLED									
375 sx / cjr		1050 sx / 340' CBL									
24. LINER RECORD											
SIZE	TOP	BOTTOM	SACKS CEMENT								
25. TUBING RECORD											
SIZE	DEPTH SET	PACKER SET									
2-7/8"	3842'										
26. Perforation record (interval, size, and number) San Andres 3932-38,90-96,4016-40,52-64,72-80,4096-4100,14-32 & 4136-46 2 JSPF Grayburg 3660-64,3725-27,77-80,3838-42 & 3868-72' 2 JSPF											
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="text-align: left;">DEPTH INTERVAL</th> <th style="text-align: left;">AMOUNT AND KIND MATERIAL USED</th> </tr> <tr> <td>3932 - 4146'</td> <td>Acidize with 5500 gals 15% Dx Bx Anti-sludge</td> </tr> <tr> <td>3660 - 3872'</td> <td>Acidize with 2000 gals 15% HCl NeFe Dx Bx</td> </tr> <tr> <td>3660 - 3872'</td> <td>Frac with 43k gel with 101k 16/30 sand</td> </tr> </table>				DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	3932 - 4146'	Acidize with 5500 gals 15% Dx Bx Anti-sludge	3660 - 3872'	Acidize with 2000 gals 15% HCl NeFe Dx Bx	3660 - 3872'	Frac with 43k gel with 101k 16/30 sand
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED										
3932 - 4146'	Acidize with 5500 gals 15% Dx Bx Anti-sludge										
3660 - 3872'	Acidize with 2000 gals 15% HCl NeFe Dx Bx										
3660 - 3872'	Frac with 43k gel with 101k 16/30 sand										
28. PRODUCTION											
Date First Production 07/25/2005		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping									
Well Status (Prod. or Shut-in) Producing											
Date of Test 08/27/2005	Hours Tested 24	Choke Size 	Prod'n For Test Period 								
Flow Tubing Press. 	Casing Pressure 	Calculated 24-Hour Rate 	Oil - Bbl. 								
Gas - MCF 48		Water - Bbl. 216									
Gas - Oil Ratio 5333		Oil Gravity - API - (Corr.) 40.0									
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold			Test Witnessed By Apache Corporation								
30. List Attachments Logs, Deviation Report, C-102, C-104											
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief											
Signature		Printed Name Elaine Linton Title Engineering Technician Date 09/01/2005									
E-mail Address elaine.linton@apachecorp.com											

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2591'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2818'	T. Devonian	T. Menefee	T. Madison
T. Queen 3321'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3593'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3901'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T. Rustler 1110'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology