District I		State of Ne				Form C-
ffice <u>istrict I</u> 625 N. French Dr., Hobbs, NM 87240 istrict II					WELL API NO.	Revised March 25, 30-025-351
811 South First, Artesia, NM 87210	OII	. CONSERVA			5. Indicate Type of	
District III 1000 Rio Brazos Rd., Aztec, NM 874	410	2040 Sout			STATE [FEE X
District IV 2040 South Pacheco, Santa Fe, NM 8		Santa Fe, N	NM 87505	,	6. State Oil & G	
SUNDRY N (DO NOT USE THIS FORM FOR PF DIFFERENT RESERVOIR. USE "A PROPOSALS.) 1. Type of Well:	NOTICES AND ROPOSALS TO DR PPLICATION FOR	ULL OR TO DEEPE	EN OR PLU	G BACK TO A SUCH	7. Lease Name or Burrus	Unit Agreement N
Oil Well X Gas We	<u>ell 🗌 O</u>	ther			0 111 11 11	
2. Name of Operator Ricks Exploration, Inc.					8. Well No. 2A	
3. Address of Operator 110 W. Louisiana, Ste. 410 Midland, Texas 79701					9. Pool name or Wildcat Trinity; Wolfcamp	
4. Well Location						-
Unit Letter Ø P	<u>· 900</u>	_feet from the	South	line and <u>600</u>	feet from	n the <u>East</u>
Section 22		Township 12S	Ra	nge 38E	NMPM	County Lea
	37	97 GR		RKB, RT, GR, etc.)		
11. Che	ck Appropria	te Box to Indi	cate Na		eport or Other I	
NOTICE OF PERFORM REMEDIAL WORK	F INTENTIC K 🔲 PLUG A	NN TO: ND ABANDON		SUB REMEDIAL WORI		PORT OF: ALTERING CASI
TEMPORARILY ABANDON	CHANG	E PLANS		COMMENCE DRI	LING OPNS.	PLUG AND
PULL OR ALTER CASING				CASING TEST AN CEMENT JOBS		ABANDONMENT
OTHER:				OTHER:Operation	for sidetrack begar	L
12. Describe proposed or cor	npleted operatio work). SEE RU	ons. (Clearly stat LE 1103. For M	e all perti ultiple Co	nent details, and giv mpletions: Attach d	e pertinent dates, in liagram of proposed	completion
of starting and proposed v		aida traals and la	toral			
of starting and proposed of or recompletion. 5-13-03 Began operations to of 5-14-03 Test BOP, blind & pi	ipe rams, ck mai	nifold to 3000 ps	si. Doors	leaked on pipe & b	lind rams. Installed	new door gaskets.
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window	ipe rams, ck man ves to 3000 psi w w/starting mil	nifold to 3000 ps - ok. 1 @ 8867'. Mad	si. Doors le 0' in 24	hrs. Tag CIBP @ 3	3880'.	-
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne	ipe rams, ck man yes to 3000 psi w w/starting mil s @ 8879', made	nifold to 3000 ps - ok. 1 @ 8867'. Mad = 12' in 24 hrs. N	si. Doors le 0' in 24 Mill starti	hrs. Tag CIBP @ 3 19 cut in 7" csg fror	3880'. n 8866 to 8867.5'. +	Cut & ream window
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95	ipe rams, ck mar ves to 3000 psi w w/starting mil s @ 8879', made w hole to 8879', 49'	nifold to 3000 ps - ok. 1 @ 8867'. Mad 2 12' in 24 hrs. M , Pump 25 bbls S	si. Doors le 0' in 24 Mill startin Super Swe	hrs. Tag CIBP @ 3 ng cut in 7" csg fror ep & circ out(1), Je	3880'. n 8866 to 8867.5'. +	Cut & ream window
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95 5-22-03 Ran 4 1/2", 11.6# L-8	ipe rams, ck mar ves to 3000 psi w w/starting mil s @ 8879', made w hole to 8879', 49' 80 STL perf'd lin	nifold to 3000 ps - ok. 1 @ 8867'. Mad 2 12' in 24 hrs. M , Pump 25 bbls S ner set @ 9549'.	si. Doors le 0' in 24 Mill startin Super Swe Released	hrs. Tag CIBP @ 5 ng cut in 7" csg fror ep & circ out(1), Je trig @ 4 PM CST.	3880'. n 8866 to 8867.5'. t & clean shale pit (Cut & ream windov (1/2), Mud up & cir
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95 5-22-03 Ran 4 1/2", 11.6# L-8 5-28-03 Disp hole w/2% KCl. acid. Pulled 2 7/8" & LD 2 3/	ipe rams, ck mar ves to 3000 psi w w/starting mil s @ 8879', made w hole to 8879', 49' 80 STL perf'd lin . Picked up 2 7/8	nifold to 3000 ps - ok. 1 @ 8867'. Mad e 12' in 24 hrs. M , Pump 25 bbls S ner set @ 9549'. 8" tbg. & run to	si. Doors e 0' in 24 Mill startin Super Swe Released PBTD @	hrs. Tag CIBP @ 5 ng cut in 7" csg fror ep & circ out(1), Je l rig @ 4 PM CST. 9562', Disp. hole w	3880'. n 8866 to 8867.5'. t & clean shale pit (/2% KCl. Spot 100	Cut & ream windov (1/2), Mud up & cir
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95 5-22-03 Ran 4 1/2", 11.6# L-8 5-28-03 Disp hole w/2% KC1.	ipe rams, ck mar ves to 3000 psi w w/starting mil s @ 8879', made w hole to 8879', 49' 80 STL perf'd lin . Picked up 2 7/8	nifold to 3000 ps - ok. 1 @ 8867'. Mad e 12' in 24 hrs. M , Pump 25 bbls S ner set @ 9549'. 8" tbg. & run to	si. Doors e 0' in 24 Mill startin Super Swe Released PBTD @	hrs. Tag CIBP @ 5 ng cut in 7" csg fror ep & circ out(1), Je l rig @ 4 PM CST. 9562', Disp. hole w	8880'. n 8866 to 8867.5'. t & clean shale pit (/2% KCl. Spot 100 esting tbg to 8000 p	Cut & ream windov (1/2), Mud up & cir
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95: 5-22-03 Ran 4 1/2", 11.6# L-8 5-28-03 Disp hole w/2% KCl. acid. Pulled 2 7/8" & LD 2 3/ @ 8732'.	ipe rams, ck mar ves to 3000 psi w w/starting mil s @ 8879', made w hole to 8879', 49' 80 STL perf'd lin . Picked up 2 7/8	nifold to 3000 ps - ok. 1 @ 8867'. Mad e 12' in 24 hrs. M , Pump 25 bbls S ner set @ 9549'. 8" tbg. & run to	si. Doors e 0' in 24 Mill startin Super Swe Released PBTD @	hrs. Tag CIBP @ 5 ng cut in 7" csg fror ep & circ out(1), Je l rig @ 4 PM CST. 9562', Disp. hole w	8880'. n 8866 to 8867.5'. t & clean shale pit (/2% KCl. Spot 100 esting tbg to 8000 p	Cut & ream windov (1/2), Mud up & cir 0 gals 90/10 15% F si above slips. Set j
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95: 5-22-03 Ran 4 1/2", 11.6# L-8 5-28-03 Disp hole w/2% KCl. acid. Pulled 2 7/8" & LD 2 3/ @ 8732'.	ipe rams, ck mar res to 3000 psi w w/starting mil s @ 8879', made w hole to 8879', 449' 80 STL perf'd lin . Picked up 2 7/8 /8" tbg. Run WI	nifold to 3000 ps ok. 1 @ 8867'. Mad 2 12' in 24 hrs. M Pump 25 bbls S ner set @ 9549'. 8" tbg. & run to re-entry guide	si. Doors le 0' in 24 Mill startin Super Swe Released PBTD @ w/1X pkr	hrs. Tag CIBP @ 8 ng cut in 7" csg fror ep & circ out(1), Je l rig @ 4 PM CST. 9562'. Disp. hole w w/SN w/2 7/8" & t	8880'. n 8866 to 8867.5'. t & clean shale pit (/2% KCl. Spot 100 esting tbg to 8000 p	Cut & ream windov (1/2), Mud up & cir 0 gals 90/10 15% H si above slips. Set p
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95: 5-22-03 Ran 4 1/2", 11.6# L-8 5-28-03 Disp hole w/2% KC1. acid. Pulled 2 7/8" & LD 2 3/ @ 8732'. Began swabbing.	ipe rams, ck mar res to 3000 psi w w/starting mil s @ 8879', made w hole to 8879', 449' 80 STL perf'd lin . Picked up 2 7/8 /8" tbg. Run WI	nifold to 3000 ps ok. 1 @ 8867'. Mad 2 12' in 24 hrs. M Pump 25 bbls S ner set @ 9549'. 8" tbg. & run to re-entry guide	si. Doors le 0' in 24 Mill startin Super Swe Released PBTD @ w/1X pkr	hrs. Tag CIBP @ 8 ng cut in 7" csg fror ep & circ out(1), Je l rig @ 4 PM CST. 9562'. Disp. hole w w/SN w/2 7/8" & t	8880'. n 8866 to 8867.5'. t & clean shale pit (/2% KCl. Spot 100 esting tbg to 8000 p can belief.	Cut & ream windoy (1/2), Mud up & cir 0 gals 90/10 15% F si above slips. Set p 578970 E0 E0 E0 E0 E0
of starting and proposed v or recompletion. 5-13-03 Began operations to o 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95. 5-22-03 Ran 4 1/2", 11.6# L-8 5-28-03 Disp hole w/2% KCl. acid. Pulled 2 7/8" & LD 2 3/ @ 8732'. Began swabbing.	ipe rams, ck man res to 3000 psi w w/starting mil s @ 8879', made tw hole to 8879', i49' 80 STL perf'd lin . Picked up 2 7/8 /8" tbg. Run WI	nifold to 3000 ps ok. 1 @ 8867'. Mad 2 12' in 24 hrs. M Pump 25 bbls S ner set @ 9549'. 8" tbg. & run to re-entry guide	si. Doors le 0' in 24 Mill startin Super Swe Released PBTD @ w/1X pkr	hrs. Tag CIBP @ 8 ng cut in 7" csg fror ep & circ out(1), Je l rig @ 4 PM CST. 9562'. Disp. hole w w/SN w/2 7/8" & to	8880'. n 8866 to 8867.5'. t & clean shale pit (/2% KCl. Spot 100 esting tbg to 8000 p can belief.	Cut & ream window (1/2), Mud up & cir 0 gals 90/10 15% H si above slips. Set p $\overline{578970}$
of starting and proposed or recompletion. 5-13-03 Began operations to a 5-14-03 Test BOP, blind & pi hydril to 1500 psi, safety valv 5-15-03 Began cutting window 5-16-03 TOH w/window mills from 8866' to 8875'. Cut 4' ne hole w/polymer mud. 5-21-03 TD 6 1/8" hole @ 95 5-22-03 Ran 4 1/2", 11.6# L-8 5-28-03 Disp hole w/2% KCl. acid. Pulled 2 7/8" & LD 2 3/ @ 8732'. Began swabbing. I hereby certify that the inform SIGNATURE	ipe rams, ck man res to 3000 psi w w/starting mil s @ 8879', made tw hole to 8879', i49' 80 STL perf'd lin . Picked up 2 7/8 /8" tbg. Run WI	nifold to 3000 ps ok. 1 @ 8867'. Mad 2 12' in 24 hrs. M Pump 25 bbls S ner set @ 9549'. 8" tbg. & run to re-entry guide	si. Doors le 0' in 24 Mill startin Super Swe Released PBTD @ w/1X pkr te to the b	hrs. Tag CIBP @ 8 ng cut in 7" csg fror ep & circ out(1), Je l rig @ 4 PM CST. 9562'. Disp. hole w w/SN w/2 7/8" & t est of my knowledg egulatory Analyst	8880'. n 8866 to 8867.5'. t & clean shale pit (/2% KCl. Spot 100 esting tbg to 8000 p can belief.	Cut & ream window (1/2), Mud up & cir 0 gals 90/10 15% H si above slips. Set p 378970 ED Hord ATE 06/04/200 0C0 bhone No. (915)683

l