Submit 3 Copies To Appropriate District Office	State of Ne		-		Form C-103
District I 1625 N. French Dr., Hobbs, NM 87240	Energy, Minerals and Natural Resources			Revised March 25, 1999 WELL API NO.	
District II 811 South First, Artesia, NM 87210	OIL CONGERVATION DRUGION			30-025-36087	
District III	2040 South Pacheco			5. Indicate Type of Lease STATE X FEE	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505			6. State Oil & Gas Lease No.	
2040 South Pacheco, Santa Fe, NM 87505					
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:				7. Lease Name or Unti Agreement Name Madera "36" State	
Oil Well Gas Well X Other				8. Well No. 1	
2. Name of Operator Pure Resources, L. P.				I I	
3. Address of Operator 500 W. Illinois Midland, Texas 79701				9. Pool name or Wildcat Wildcat (Morrow)	
4. Well Location					<u></u>
Unit Letter A <u>660</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>East</u> line					
Section 36	Township 26 S		inge 34 E	NMPM	County Lea
	10. Elevation (Show wh 3,197'	hether DR,	RKB, RT, GR, etc.)		
	ppropriate Box to Ind	licate Na			
	TENTION TO: PLUG AND ABANDON		SUB REMEDIAL WOR		REPORT OF:
	CHANGE PLANS		COMMENCE DRI		PLUG AND
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TEST AI CEMENT JOBS	ND X	
OTHER:			OTHER:		
 Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work). SEE RULE 1103. For Multiple Completions: Attach diagram of proposed completion or recompletion. 9-5/8" Intermediate Casing Cement/Test: On 3/09/2003, 149 Jts. 9-5/8" 53.5#, L-80, BTC csg (w/mfrgs rated internal yield pressure of 9,410 psi) was RIH and cmt'd @ 5,319' w/1,300 sx 35:65 POZ "C" cmt. w/6% Bentonite, 5% NACL, 25 PPS Cello mixed @ 11.6 Gal/sk (Yld: 2.10, Wt: 12.40)-Lead followed by 500 sx Class "C" cmt w/1% CaCl2 mixed @ 6.4 Gal/sk (Yld: 1.34, Wt: 14.80)-Tail. Displaced rubber plug to FC @ 5, 244' w/371 Bbls FW. Bump plug w/1,850 psi. Floats held OK. PD-CIP @ 5:00 am on 3/08/2003. Circ. 324 sx cmt to pit. TOC @ surface by circ. Est. BHST @ 5,300' = 100 deg F, BHCT @ 5,300' = 82 deg F, Max BHCT @ 3,640' = 87 deg F. Est. cmt. strength @ time of test is 2,020 psi (Tail). Cmt. in place 24.5 hrs prior to test. Tested 9-5/8" on 3/10/2003 to 3,000 psi w/rig pump for 30 min held OK. 					
					A LUN PER
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE alante Do	hlmg	_TITLE]	Regulatory Analyst		DATE 06/20/2003
Type or print name Alan W. Bohlir	1g			Te	elephone No. (915)498-8662
(This space for State use)					ACER ILIN O
APPROVED BY Harry W	1. Wink	TITLE	REPRESENTATIV	E II/STAFF MAN	AGER JUN 2 6 2003
Conditions of approval, if any:		مر بيد مور و ا لي م ر م			