Office District 1 – (575) 393-6161 Energy, Minerals and Natural Resources	Form C-103 Revised August 1, 2011
District I – (575) 393-6161 Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240 Color Conservation District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 District III – (505) 334-6178 District III – (505) 334-6178 Energy, Minerals and Natural Resources 1220 South St. Francis Dr.	WELL API NO.
District II - (575) 748-1283	30-025-40739
District III – (505) 334-6178 District III – (505) 334-6178 District III – (505) 334-6178	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 4 2012 Sonto Eq. NIM 97505	STATE X FEE :
District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NA	6. State Oil & Gas Lease No.
87505 CEN/PP	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	7. Lease Name or Unit Agreement Name VACUUM GLORIETA EAST UNIT 33
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	8. Well Number 19
2. Name of Operator	9. OGRID Number
ConocoPhillips Company	217817
3. Address of Operator P. O. Box 51810	10. Pool name or Wildcat
Midland, TX 79710	VACUUM GLORIETA
4. Well Location	
Unit Letter M: 968 feet from the SOUTH line and 733	feet from the WEST line
Section 32 Township 17S Range 35E	NMPM County LEA
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
3972' GL	
	•
12. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data
NOTICE OF INTENTION TO	
	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORLD REMPORABLY ABANDON CHANGE PLANS COMMENCE DRI	
TEMPORARILY ABANDON	
DOWNHOLE COMMINGLE	у у
DOWNHOLE COMMINGLE	
OTHER: OTHER: SPUD	$\overline{\lambda}$
13. Describe proposed or completed operations. (Clearly state all pertinent details, and	l give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Cor	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion.	
	npletions: Attach wellbore diagram of
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	npletions: Attach wellbore diagram of RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP. Circulated Rig Release Date:	RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @ X (86bbls) of class C tail cmt. Disp w/ 50
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP.	RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @ X (86bbls) of class C tail cmt. Disp w/ 50
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP. Circulated Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledge.	RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @ X (86bbls) of class C tail cmt. Disp w/ 50
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP. Circulated Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledge.	RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @ X (86bbls) of class C tail cmt. Disp w/ 50
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP. Circulated Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledge SIGNATURE MILL Staff Regulatory Technicia	RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @ X (86bbls) of class C tail cmt. Disp w/ 50
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP. Circulated Rig Release Date: Thereby certify that the information above is true and complete to the best of my knowledge SIGNATURE TITLE Staff Regulatory Technicia Type or print name Ashley Martin E-mail address: Ashley.Martin@c	RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @ X (86bbls) of class C tail cmt. Disp w/ 50
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP. Circulated Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledge SIGNATURE MILL Staff Regulatory Technicia	RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @ X (86bbls) of class C tail cmt. Disp w/ 50 e and belief. DATE 12/05/2012
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud_well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP. Citalada Rig Release Date: Thereby certify that the information above is true and complete to the best of my knowledge. SIGNATURE TITLE Staff Regulatory Technicia Type or print name Ashley Martin E-mail address: Ashley.Martin@c For State Use Only	e and belief. DATE 12/05/2012 conocophillips.cd?filONE: (432)688-6938
proposed completion or recompletion. 12/2/12 MIRU Prec 822. 12/03/12 Spud well w/12 1/4" bit. Drilled to 1651' (spud TD). 1537'. Pre flush w/ 20 bbls FW. Pumped 700 SX (214 bbls) of class C lead cmt & 360 S bbls of FW & bumped plug to surf. NU BOP. Circulated Rig Release Date: Thereby certify that the information above is true and complete to the best of my knowledge SIGNATURE TITLE Staff Regulatory Technicia Type or print name Ashley Martin E-mail address: Ashley.Martin@c	RIH w/35 jts, 8 5/8", 24#, J-55 csg & set @ X (86bbls) of class C tail cmt. Disp w/ 50 e and belief. DATE 12/05/2012