

Results of Directional Survey

API number:	30-025-40369		
OGRID:		Operator:	EOG RESOURCES INC
		Property:	BLACK BEAR 36 STATE # 2H

surface	ULSTR:	P	36	T	25S	R	33E
				220	FSL	1310	FEL

BH Loc	ULSTR:	A	36	T	25S	R	33E
14350	MD	9477.8	TVD	224	FNL	1062	FEL
				5056	FSL		

Top Perf/OH	ULSTR:	P	36	T	25S	R	33E
9939	MD	9550.2	TVD	648	FSL	1043	FEL

Bot Perf/OH	ULSTR:	A	36	T	25S	R	33E
14230	MD	9479.9	TVD	343	FNL	1058	FEL
				4937	FSL		

	MD	N/S	E/W	VD
	9902	390.90	267.00	9550.6
TOP PERFS/OH	9939	427.90	267.08	9550.16
	9995	483.90	267.20	9549.50
	14230	4716.50	252.50	9479.90
BOT PERFS/OH	14230	4716.50	252.50	9479.90
	14306	4792.40	249.90	9478.80

NEXT TO LAST	14306	4792.40	249.90	9478.80
LAST READING	14350	4836.40	247.70	9477.80
TD	14350	4836.40	247.70	9477.80

Surface Location	220	FS	1310	FE
Projected BHL	5056	FS	1062	FE
Location of				
Top Perfs/OH	648	FS	1043	FE
Bottom Perfs/OH	4937	FS	1058	FE

SUMMARY of Subsurface Locations

Surface Location	P-36-25S-33E	220	FS	1310	FE	Vert. Depth
Top Perfs/OH	P-36-25S-33E	648	FS	1043	FE	9550.16
Bottom Perfs/OH	A-36-25S-33E	4937	FS	1058	FE	9479.90
Projected TD	A-36-25S-33E	5056	FS	1062	FE	9477.80



EOG Resources, Inc.

Lea County

Black Bear "36" State

#2H

OH

Design: OH

PathfinderX & Y Report

22 August, 2012

HOBBS OCD
DEC 14 2012
RECEIVED

SUR: P-36-25s-33e, 220/S & 1310/E
BHL: A-36-25s-33e, 5056/S & 1062/E
API # 30-025-40369

PATHFINDER®
A Schlumberger Company

Company:	EOG Resources, Inc.	Local Co-ordinate Reference:	Well #2H
Project:	Lea County	TVD Reference:	KB = 25 @ 3348.9usft (Cactus 139)
Site:	Black Bear "36" State	MD Reference:	KB = 25 @ 3348.9usft (Cactus 139)
Well:	#2H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

Project	Lea County	System Datum:	Mean Sea Level
Map System:	US State Plane 1927 (Exact solution)		
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	Black Bear "36" State				
Site Position:		Northing:	393,927.000 usft	Latitude:	32.080437
From:	Map	Easting:	750,632.000 usft	Longitude:	-103.524134
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.43 °

Well	#2H					
Well Position	+N/-S	0.0 usft	Northing:	393,853.000 usft	Latitude:	32.080215
	+E/-W	0.0 usft	Easting:	751,513.000 usft	Longitude:	-103.521291
Position Uncertainty		0.0 usft	Wellhead Elevation:	usft	Ground Level:	3,323.9 usft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF200510	11/30/2011	7.49	60.07	48,528

Design	OH				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.0	0.0	0.0	2.99	

Survey Program	Date	8/22/2012			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
1,067.0	14,350.0	MWD #1 (OH)	MWD	MWD - Standard	

Company: EOG Resources, Inc.
Project: Lea County
Site: Black Bear "36" State
Well: #2H
Wellbore: OH
Design: OH

Local Co-ordinate Reference: Well #2H
TVD Reference: KB = 25 @ 3348.9usft (Cactus 139)
MD Reference: KB = 25 @ 3348.9usft (Cactus 139)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.1 Single User Db

Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (%/100usft)	Northing (usft)	Easting (usft)	
925.0	0.40	179.95	925.0	-2,423.9	-4.5	0.4	-4.5	0.00	393,848.52	751,513.42	
1,067.0	0.44	151.85	1,067.0	-2,281.9	-5.5	0.7	-5.4	0.15	393,847.54	751,513.68	
1,252.0	0.44	199.45	1,252.0	-2,096.9	-6.8	0.8	-6.7	0.19	393,846.25	751,513.78	
1,436.0	0.62	187.42	1,436.0	-1,912.9	-8.4	0.4	-8.4	0.11	393,844.59	751,513.41	
1,627.0	0.53	187.62	1,627.0	-1,721.9	-10.3	0.2	-10.3	0.05	393,842.69	751,513.16	
1,816.0	0.97	200.85	1,815.9	-1,533.0	-12.7	-0.5	-12.7	0.25	393,840.33	751,512.48	
2,006.0	0.79	221.68	2,005.9	-1,343.0	-15.1	-2.0	-15.2	0.19	393,837.85	751,511.03	
2,196.0	1.32	44.80	2,195.9	-1,153.0	-14.6	-1.3	-14.6	1.11	393,838.43	751,511.70	
2,385.0	1.49	40.88	2,384.9	-964.0	-11.2	1.8	-11.1	0.10	393,841.83	751,514.85	
2,574.0	1.32	57.09	2,573.8	-775.1	-8.1	5.3	-7.8	0.23	393,844.87	751,518.28	
2,764.0	1.14	32.22	2,763.8	-585.1	-5.3	8.1	-4.9	0.29	393,847.66	751,521.13	
2,950.0	1.32	6.63	2,949.7	-399.2	-1.6	9.4	-1.2	0.31	393,851.35	751,522.36	
3,139.0	1.32	44.00	3,138.7	-210.2	2.1	11.1	2.7	0.45	393,855.08	751,524.12	
3,329.0	0.53	81.49	3,328.6	-20.3	3.8	13.5	4.5	0.50	393,856.78	751,526.51	
3,517.0	0.88	337.24	3,516.6	167.7	5.2	13.8	6.0	0.60	393,858.24	751,526.82	
3,706.0	0.97	275.97	3,705.6	356.7	6.7	11.7	7.3	0.50	393,859.75	751,524.66	
3,895.0	0.88	277.00	3,894.6	545.7	7.1	8.6	7.5	0.05	393,860.09	751,521.63	
4,083.0	2.02	51.06	4,082.6	733.7	9.4	9.8	9.8	1.44	393,862.35	751,522.78	
4,272.0	1.14	4.82	4,271.5	922.6	13.3	12.5	14.0	0.78	393,866.32	751,525.52	
4,460.0	0.88	16.97	4,459.5	1,110.6	16.6	13.1	17.2	0.18	393,869.56	751,526.10	
4,648.0	0.53	115.80	4,647.4	1,298.5	17.6	14.3	18.3	0.58	393,870.56	751,527.31	
4,838.0	1.67	140.93	4,837.4	1,488.5	15.0	16.8	15.9	0.64	393,868.03	751,529.84	
5,008.0	1.76	157.81	5,007.3	1,658.4	10.7	19.4	11.7	0.30	393,863.69	751,532.39	
5,208.0	1.58	179.79	5,207.3	1,858.4	5.1	20.6	6.2	0.33	393,858.09	751,533.56	
5,397.0	3.69	132.34	5,396.1	2,047.2	-1.6	25.1	-0.3	1.52	393,851.39	751,538.07	
5,587.0	6.16	123.32	5,585.3	2,236.4	-11.3	38.1	-9.3	1.36	393,841.67	751,551.11	
5,776.0	5.80	122.37	5,773.3	2,424.4	-22.0	54.6	-19.1	0.20	393,830.98	751,567.65	

Company: EOG Resources, Inc.
Project: Lea County
Site: Black Bear "36" State
Well: #2H
Wellbore: OH
Design: OH

Local Co-ordinate Reference:
TVD Reference: Well #2H
MD Reference: KB = 25 @ 3348.9usft (Cactus 139)
North Reference: KB = 25 @ 3348.9usft (Cactus 139)
Survey Calculation Method: Grid
Database: Minimum Curvature
EDM 5000.1 Single User Db

Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)	Northing (usft)	Easting (usft)	
5,966.0	6.33	126.73	5,962.3	2,613.4	-33.4	71.1	-29.7	0.37	393,819.58	751,584.15	
6,156.0	6.42	124.84	6,151.1	2,802.2	-45.8	88.3	-41.1	0.12	393,807.25	751,601.26	
6,345.0	5.36	125.49	6,339.1	2,990.2	-56.9	104.1	-51.4	0.56	393,796.09	751,617.12	
6,534.0	5.63	119.90	6,527.2	3,178.3	-66.7	119.3	-60.3	0.32	393,786.34	751,632.35	
6,723.0	5.80	123.00	6,715.3	3,366.4	-76.5	135.4	-69.3	0.19	393,776.52	751,648.39	
6,912.0	5.98	126.62	6,903.3	3,554.4	-87.6	151.3	-79.5	0.22	393,765.44	751,664.30	
7,101.0	5.63	124.70	7,091.3	3,742.4	-98.7	166.8	-89.9	0.21	393,754.29	751,679.83	
7,291.0	5.45	129.01	7,280.4	3,931.5	-109.7	181.5	-100.1	0.24	393,743.31	751,694.50	
7,480.0	5.80	129.26	7,468.5	4,119.6	-121.4	195.9	-111.0	0.19	393,731.61	751,708.87	
7,669.0	5.80	125.55	7,656.5	4,307.6	-133.0	211.0	-121.8	0.20	393,720.02	751,724.03	
7,859.0	6.24	122.12	7,845.5	4,496.6	-144.1	227.6	-132.0	0.30	393,708.95	751,740.59	
8,049.0	4.04	133.39	8,034.7	4,685.8	-154.1	241.2	-141.3	1.27	393,698.86	751,754.20	
8,239.0	3.87	123.22	8,224.3	4,875.4	-162.3	251.4	-148.9	0.38	393,690.75	751,764.43	
8,428.0	3.25	126.23	8,412.9	5,064.0	-168.9	261.1	-155.1	0.34	393,684.09	751,774.09	
8,617.0	2.11	122.42	8,601.7	5,252.8	-173.9	268.3	-159.7	0.61	393,679.05	751,781.35	
8,734.0	1.41	139.34	8,718.6	5,369.7	-176.2	271.1	-161.8	0.74	393,676.81	751,784.10	
8,923.0	1.06	176.71	8,907.6	5,558.7	-179.7	272.7	-165.2	0.45	393,673.30	751,785.72	
9,082.0	2.99	8.69	9,066.5	5,717.6	-177.1	273.4	-162.6	2.54	393,675.93	751,786.43	
KOP - 9082.0 'MD, 9066.5 'TVD, -177.1 'N, 273.4 'E											
9,113.0	7.91	6.27	9,097.4	5,748.5	-174.1	273.8	-159.6	15.88	393,678.85	751,786.78	
9,144.0	13.72	5.76	9,127.8	5,778.9	-168.4	274.4	-153.8	18.74	393,684.63	751,787.39	
9,175.0	18.29	4.78	9,157.6	5,808.7	-159.9	275.2	-145.3	14.77	393,693.14	751,788.16	
9,206.0	21.19	4.28	9,186.8	5,837.9	-149.4	276.0	-134.8	9.37	393,703.58	751,788.99	
9,238.0	24.53	3.21	9,216.3	5,867.4	-137.0	276.8	-122.4	10.52	393,715.98	751,789.79	
9,269.0	27.26	2.12	9,244.2	5,895.3	-123.5	277.4	-108.8	8.94	393,729.51	751,790.41	
9,301.0	29.99	0.53	9,272.3	5,923.4	-108.2	277.8	-93.5	8.86	393,744.83	751,790.76	
9,333.0	33.68	0.18	9,299.4	5,950.5	-91.3	277.9	-76.7	11.55	393,761.71	751,790.86	

Company:	EOG Resources, Inc.	Local Co-ordinate Reference:	Well #2H
Project:	Lea County	TVD Reference:	KB = 25 @ 3348.9usft (Cactus 139)
Site:	Black Bear "36" State	MD Reference:	KB = 25 @ 3348.9usft (Cactus 139)
Well:	#2H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	EDM 5000.1 Single User Db

Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)	Northing (usft)	Easting (usft)	
9,364.0	37.11	359.50	9,324.7	5,975.8	-73.3	277.8	-58.7	11.14	393,779.66	751,790.80	
9,396.0	40.19	357.97	9,349.7	6,000.8	-53.4	277.4	-38.8	10.08	393,799.63	751,790.35	
9,427.0	43.35	357.96	9,372.8	6,023.9	-32.7	276.6	-18.2	10.19	393,820.27	751,789.62	
9,459.0	46.34	357.75	9,395.5	6,046.6	-10.2	275.8	4.2	9.36	393,842.82	751,788.78	
9,490.0	48.80	358.16	9,416.4	6,067.5	12.7	275.0	27.0	8.00	393,865.68	751,787.96	
9,522.0	50.74	358.56	9,437.1	6,088.2	37.1	274.3	51.4	6.14	393,890.10	751,787.26	
9,553.0	54.61	358.55	9,455.9	6,107.0	61.7	273.6	75.9	12.48	393,914.74	751,786.64	
9,585.0	58.65	358.29	9,473.5	6,124.6	88.4	272.9	102.6	12.64	393,941.45	751,785.90	
9,616.0	61.82	357.96	9,488.9	6,140.0	115.3	272.0	129.4	10.27	393,968.34	751,785.02	
9,648.0	65.16	358.12	9,503.1	6,154.2	144.0	271.0	157.9	10.45	393,996.96	751,784.04	
9,680.0	68.59	358.26	9,515.7	6,166.8	173.4	270.1	187.2	10.73	394,026.37	751,783.11	
9,711.0	72.46	358.25	9,526.0	6,177.1	202.6	269.2	216.3	12.48	394,055.57	751,782.22	
9,742.0	75.45	358.62	9,534.6	6,185.7	232.4	268.4	246.0	9.71	394,085.35	751,781.41	
9,773.0	78.52	359.28	9,541.6	6,192.7	262.5	267.9	276.2	10.12	394,115.55	751,780.86	
9,804.0	82.22	359.89	9,546.8	6,197.9	293.1	267.6	306.7	12.09	394,146.10	751,780.64	
9,836.0	86.97	359.39	9,549.8	6,200.9	325.0	267.4	338.5	14.92	394,177.95	751,780.44	
9,867.0	89.43	359.67	9,550.8	6,201.9	355.9	267.2	369.4	7.99	394,208.93	751,780.18	
LP - 9867.0 'MD, 9550.8 'TVD, 355.9 'N, 267.2 'E											
9,902.0	91.01	359.83	9,550.6	6,201.7	390.9	267.0	404.3	4.54	394,243.93	751,780.03	
9,995.0	90.40	0.38	9,549.5	6,200.6	483.9	267.2	497.2	0.88	394,336.92	751,780.20	
10,088.0	89.96	0.57	9,549.2	6,200.3	576.9	268.0	590.1	0.52	394,429.92	751,780.97	
10,183.0	91.45	2.27	9,548.0	6,199.1	671.9	270.3	685.1	2.38	394,524.88	751,783.33	
10,277.0	89.60	357.73	9,547.2	6,198.3	765.8	270.3	778.9	5.21	394,618.84	751,783.33	
10,370.0	90.40	357.82	9,547.2	6,198.3	858.8	266.7	871.5	0.87	394,711.77	751,779.71	
10,465.0	90.84	356.02	9,546.1	6,197.2	953.6	261.6	966.0	1.95	394,806.63	751,774.61	
10,560.0	91.28	358.31	9,544.4	6,195.5	1,048.5	256.9	1,060.5	2.45	394,901.49	751,769.91	
10,653.0	93.47	0.56	9,540.5	6,191.6	1,141.4	256.0	1,153.2	3.37	394,994.39	751,769.00	

Company: EOG Resources, Inc.
Project: Lea County
Site: Black Bear "36" State
Well: #2H
Wellbore: OH
Design: OH

Local Co-ordinate Reference: Well #2H
TVD Reference: KB = 25 @ 3348.9usft (Cactus 139)
MD Reference: KB = 25 @ 3348.9usft (Cactus 139)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.1 Single User Db

Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)	Northing (usft)	Easting (usft)	
10,745.0	92.15	0.93	9,536.0	6,187.1	1,233.3	257.2	1,245.0	1.49	395,086.27	751,770.19	
10,840.0	92.24	1.08	9,532.4	6,183.5	1,328.2	258.9	1,339.9	0.18	395,181.19	751,771.86	
10,934.0	91.36	0.77	9,529.4	6,180.5	1,422.1	260.4	1,433.8	0.99	395,275.13	751,773.37	
11,027.0	89.96	359.48	9,528.3	6,179.4	1,515.1	260.6	1,526.6	2.05	395,368.11	751,773.58	
11,120.0	91.10	359.12	9,527.5	6,178.6	1,608.1	259.4	1,619.5	1.29	395,461.10	751,772.44	
11,214.0	93.12	358.13	9,524.0	6,175.1	1,702.0	257.2	1,713.1	2.39	395,555.01	751,770.19	
11,308.0	91.80	358.47	9,520.0	6,171.1	1,795.9	254.4	1,806.7	1.45	395,648.88	751,767.40	
11,401.0	90.04	359.67	9,518.5	6,169.6	1,888.8	252.9	1,899.5	2.29	395,741.85	751,765.89	
11,495.0	89.78	2.27	9,518.6	6,169.7	1,982.8	254.5	1,993.4	2.78	395,835.82	751,767.48	
11,590.0	90.92	1.87	9,518.1	6,169.2	2,077.8	257.9	2,088.4	1.27	395,930.76	751,770.91	
11,684.0	90.66	0.72	9,516.8	6,167.9	2,171.7	260.0	2,182.3	1.25	396,024.72	751,773.04	
11,778.0	92.24	0.53	9,514.4	6,165.5	2,265.7	261.1	2,276.2	1.69	396,118.69	751,774.06	
11,871.0	91.54	359.49	9,511.3	6,162.4	2,358.6	261.1	2,369.0	1.35	396,211.63	751,774.08	
11,965.0	89.78	359.04	9,510.2	6,161.3	2,452.6	259.9	2,462.8	1.93	396,305.61	751,772.87	
12,059.0	91.54	358.61	9,509.2	6,160.3	2,546.6	257.9	2,556.6	1.93	396,399.58	751,770.95	
12,153.0	91.36	358.62	9,506.8	6,157.9	2,640.5	255.7	2,650.3	0.19	396,493.53	751,768.67	
12,247.0	89.78	359.18	9,505.8	6,156.9	2,734.5	253.9	2,744.0	1.78	396,587.50	751,766.87	
12,341.0	89.60	359.63	9,506.3	6,157.4	2,828.5	252.9	2,837.8	0.52	396,681.50	751,765.89	
12,435.0	90.13	358.77	9,506.6	6,157.7	2,922.5	251.6	2,931.6	1.07	396,775.48	751,764.58	
12,530.0	87.93	359.97	9,508.2	6,159.3	3,017.5	250.5	3,026.4	2.64	396,870.46	751,763.54	
12,625.0	88.99	0.04	9,510.7	6,161.8	3,112.4	250.5	3,121.3	1.12	396,965.42	751,763.55	
12,720.0	90.40	358.79	9,511.2	6,162.3	3,207.4	249.6	3,216.1	1.98	397,060.41	751,762.58	
12,814.0	92.51	359.29	9,508.8	6,159.9	3,301.4	248.0	3,309.8	2.31	397,154.36	751,761.00	
12,909.0	91.36	358.34	9,505.6	6,156.7	3,396.3	246.0	3,404.5	1.57	397,249.29	751,759.04	
13,004.0	91.89	359.69	9,502.9	6,154.0	3,491.2	244.4	3,499.2	1.53	397,344.23	751,757.40	
13,099.0	90.57	359.67	9,500.9	6,152.0	3,586.2	243.9	3,594.0	1.39	397,439.20	751,756.87	
13,193.0	88.55	359.96	9,501.6	6,152.7	3,680.2	243.6	3,687.9	2.17	397,533.20	751,756.57	

Company: EOG Resources, Inc.
Project: Lea County
Site: Black Bear "36" State
Well: #2H
Wellbore: OH
Design: OH

Local Co-ordinate Reference: Well #2H
TVD Reference: KB = 25 @ 3348.9usft (Cactus 139)
MD Reference: KB = 25 @ 3348.9usft (Cactus 139)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.1 Single User Db

Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)	Northing (usft)	Easting (usft)
13,288.0	90.13	358.86	9,502.7	6,153.8	3,775.2	242.6	3,782.7	2.03	397,628.18	751,755.59
13,381.0	89.87	0.29	9,502.7	6,153.8	3,868.2	241.9	3,875.5	1.56	397,721.18	751,754.90
13,475.0	91.98	2.68	9,501.2	6,152.3	3,962.1	244.3	3,969.5	3.39	397,815.12	751,757.34
13,569.0	93.03	2.23	9,497.1	6,148.2	4,055.9	248.4	4,063.4	1.22	397,908.94	751,761.36
13,664.0	93.47	0.65	9,491.7	6,142.8	4,150.8	250.7	4,158.2	1.72	398,003.76	751,763.74
13,758.0	92.86	0.48	9,486.5	6,137.6	4,244.6	251.7	4,252.0	0.67	398,097.61	751,764.67
13,850.0	91.45	0.98	9,483.1	6,134.2	4,336.5	252.8	4,343.8	1.63	398,189.53	751,765.84
13,946.0	89.87	0.02	9,482.0	6,133.1	4,432.5	253.7	4,439.7	1.93	398,285.52	751,766.68
14,041.0	91.01	0.07	9,481.2	6,132.3	4,527.5	253.8	4,534.6	1.20	398,380.51	751,766.75
14,136.0	90.13	359.69	9,480.3	6,131.4	4,622.5	253.6	4,629.4	1.01	398,475.51	751,766.55
14,230.0	90.31	358.98	9,479.9	6,131.0	4,716.5	252.5	4,723.2	0.78	398,569.50	751,765.46
14,306.0	91.36	357.11	9,478.8	6,129.9	4,792.4	249.9	4,799.0	2.82	398,645.44	751,762.87
14,350.0	91.36	357.11	9,477.8	6,128.9	4,836.4	247.7	4,842.7	0.00	398,689.38	751,760.65
PROJECTED BHL - 14350.0 'MD, 9477.8 'TVD, 4836.6 'N, 246.5 'E										

Design Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
9,082.0	9,066.5	-177.1	273.4	KOP - 9082.0 'MD, 9066.5 'TVD, -177.1 'N, 273.4 'E
9,867.0	9,550.8	355.9	267.2	LP - 9867.0 'MD, 9550.8 'TVD, 355.9 'N, 267.2 'E
14,350.0	9,477.8	4,836.4	247.7	PROJECTED BHL - 14350.0 'MD, 9477.8 'TVD, 4836.6 'N, 246.5 'E

Checked By: _____ Approved By: _____ Date: _____