

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

October 13, 2009

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30 009 20023
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Moberly Trust
8. Well Number 1
9. OGRID Number 294149
10. Pool name or Wildcat Wildcat, Santa Rosa

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator CurryTex, LLC	
3. Address of Operator 10,000 North Central Expressway, Suite 1350 Dallas, TX 75231	
4. Well Location Unit Letter O : 330 feet from the South line and 2310 feet from the East line Section 23 Township 5N Range 32E NMPM Curry County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4633 GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS ☒ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Commenced drilling a 12 1/4" hole at 6:00 pm, 12/11/12. Drilled 12 1/4" hole to a depth of 396'.

Ran 9 joints (396' of New 8 5/8" 24# J-55 casing equipped with Texas Pattern Shoe, Insert float and 3 centralizers. 8 5/8" casing was cemented with 257 sx Class C w/ 2% CaCl. Circulated 94 sx to surface. The plug was landed at 1:55 am, 12/12/12.

WOC 18 hours, Install BOP and test same to 500 psi. Drilled a 7 7/8" hole to 1744' and the well was logged on 12/16/2012.

Ran 43 joints (1744') used 5 1/2" 17# J-55 casing equipped with Cement Guide shoe, float collar and 4 centralizers. The 5 1/2" casing was cemented with 124 sx Lead cement: Class C +25#CF+4%gel+2% CaCl and 200 sx Tail: Class C+ .5%FL-62. Circulated 45 sx to surface, plug down @ 1:55 am 12/17/2012.

Spud Date:

12/11/2012

Rig Release Date:

12/17/2012

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Agent

DATE 12/18/2012

Type or print name Phelps White

E-mail address: pwiv@zianet.com

PHONE: 575 626 7660

For State Use Only

APPROVED BY:

TITLE Compliance Officer

DATE 12-21-2012

Conditions of Approval (if any):

JAN 08 2013