		OCD Art		
Form 3160-5	UNITED ST.		HOBIGETVED	FORM APPROVED
(August 2007)	DEPARTMENT OF T		JAN 1 4 2013	OMB No. 1004-0137 Expires: July 31, 2010
	BUREAU OF LAND M	IANAGEMENT	JAN 1	5. Lease Serial No.
SUNDR	Y NOTICES AND R	EPORTS ON WE	LLS	NM 15035
Do not use	e this form for proposa well. Use Form 3160-3	als to drill or to re-e	nter an RECEIVED	6. If Indian, Allottee or Tribe Name
SUBMIT IN	TRIPLICATE - Other	r instructions on p	age 2	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well				,
	Other			8. Well Name and No.
2. Name of Operator	/			Triple A Federal #1
Siana Operating, LLC	3b, P	hone No. (include area code		30-025-24993
PO Box 10303, Midland, T		-687-6600	·	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., F			· · · · · · · · · · · · · · · · · · ·	Antelope Ridge; Wolfcamp
1580 FNL & 2414 FWL Sec. 10, T-23-S; R-34-E				11. County or Parish, State
	PROPRIATE BOX(ES)	TO INDICATE NAT	TURE OF NOTICE, REPO	DRT, OR OTHER DATA
TYPE OF SUBMISSION	1		TYPE OF ACTION	
	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off
Notice of Intent	Alter Casing	Fracture Treat	Reclamantion	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	Other
	Change Plans	Plug and Abandon	Temporarily Abandon	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	
following completion of the involution to the involution of the in	 Ived operations. If the operational operation of the operation oper	ion results in a multiple c be filed only after all r n well ND wellhead 77 jts. 2 7/8 tbg. RI ed 230 BBLS mud	ompletion or recompletion in a equirements, including reclaman d. H w/ 1800' tbg. laden fluid. Spotted 1	subsequent reports shall be filed within 30 days new interval, a Form 3160-4 shall be filed once ntion, have been completed, and the operator has RECLAMATION DUF 300 sx Class H cement 11086-11660.
Attach the Bond under which the following completion of the invol- testing has been completed. Fina determined that the site is ready for 11/19/12 MIRU plugging e 11/20/12 Finish ND wellhe 11/21/12 Finished RIH w/ POH w/ 2500' tbg. WOC. 11/26/12 Tagged plug @ 1 tbg. to 7078'. Circulated 23 to bullhead sqz cement into 11/27/12 Tagged plug @ 6 Spotted 125 sx class C cement 11/28/12 Tagged plug @ 3 @ 945'. Spotted 25 sx class cement to surface. 11/29/12 Rigged down mov- hours. Welded on Dry Hole	 Ived operations. If the operation of the operati	ion results in a multiple c be filed only after all r n well ND wellhead 7 jts. 2 7/8 tbg. RI ed 230 BBLS mud bg. to 8542'. Spotte id. Spotted 90 sx C d up on csg. Closed Spotted 90 sx class K'd by Marlan Des g. to 1169'. Spotted 2. POH WOC. Tag ckhoe and welder. C	ompletion or recompletion in a equirements, including reclaman d. H w/ 1800' tbg. laden fluid. Spotted 1 ed 50 sx class H cemen Class C cement @ 6637 d well in w/ 500 psi. C cement. POH to 40 aton to combine plugs. l 50 sx class C cement ged plug @ 595'. RIH Dug out cellar. Cut off leadmen and cleaned l	new interval, a Form 3160-4 shall be filed once ntion, have been completed, and the operator has INTERCLAMATION DUE_5-22-7 00 sx Class H cement 11086-11660. At from 8297-8542'. Layed down 7-7078'. POH to 6000' w/ tbg. Tried 45'. WOC. Tagged plug @ 4821'. .). POH w/ tbg. @ 1169-924. WOC. Tagged plug to 60'. Spotted 20 sx class C f wellhead. Waited on BLM for 2 location. Moved off.
Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready for 11/19/12 MIRU plugging e 11/20/12 Finish ND wellhe 11/21/12 Finished RIH w/ POH w/ 2500' tbg. WOC. 11/26/12 Tagged plug @ 11 tbg. to 7078'. Circulated 23 to bullhead sqz cement into 11/27/12 Tagged plug @ 6 Spotted 125 sx class C cement 11/28/12 Tagged plug @ 3 @ 945'. Spotted 25 sx class cement to surface. 11/29/12 Rigged down move hours. Welded on Dry Hold excepted as to plugging of the ability under bond is retained rface restoration is completed	ved operations. If the operations of the operation of the	ion results in a multiple c be filed only after all r n well ND wellhead 7 jts. 2 7/8 tbg. RI ed 230 BBLS mud bg. to 8542'. Spotte id. Spotted 90 sx C d up on csg. Closed Spotted 90 sx class K'd by Marlan Des g. to 1169'. Spotted 2. POH WOC. Tag ckhoe and welder. C	ompletion or recompletion in a equirements, including reclaman d. H w/ 1800' tbg. laden fluid. Spotted 1 ed 50 sx class H cemen Class C cement @ 6637 d well in w/ 500 psi. C cement. POH to 40 aton to combine plugs. l 50 sx class C cement ged plug @ 595'. RIH Dug out cellar. Cut off leadmen and cleaned l	new interval, a Form 3160-4 shall be filed once ntion, have been completed, and the operator has INFCLAMATION DUF_5-22-27 00 sx Class H cement 11086-11660. At from 8297-8542'. Layed down 7-7078'. POH to 6000' w/ tbg. Tried 45'. WOC. Tagged plug @ 4821'. .). POH w/ tbg. @ 1169-924. WOC. Tagged plug to 60'. Spotted 20 sx class C f wellhead. Waited on BLM for 2
Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready for 11/19/12 MIRU plugging e 11/20/12 Finish ND wellhe 11/21/12 Finished RIH w/ POH w/ 2500' tbg. WOC. 11/26/12 Tagged plug @ 11 tbg. to 7078'. Circulated 23 to bullhead sqz cement into 11/27/12 Tagged plug @ 6 Spotted 125 sx class C cement 11/28/12 Tagged plug @ 3 @ 945'. Spotted 25 sx class cement to surface. 11/29/12 Rigged down move hours. Welded on Dry Hold cepted as to plugging of the ability under bond is retained rface restoration is completed (A. Thereby certify that the foregoing is Name (Printed/Typed)	ved operations. If the operations of the operation of the	ion results in a multiple c be filed only after all r n well ND wellhead 77 jts. 2 7/8 tbg. RI ed 230 BBLS mud bg. to 8542'. Spotted id. Spotted 90 sx Closed Gotted 90 sx class K'd by Marlan Des g. to 1169'. Spotted 2. POH WOC. Tag ckhoe and welder. Cellar. Removed of 199 i ng Coh	ompletion or recompletion in a equirements, including reclaman d. H w/ 1800' tbg. laden fluid. Spotted 1 ed 50 sx class H cemen Class C cement @ 6637 d well in w/ 500 psi. C cement. POH to 40 aton to combine plugs. l 50 sx class C cement ged plug @ 595'. RIH Dug out cellar. Cut off leadmen and cleaned l	new interval, a Form 3160-4 shall be filed once ntion, have been completed, and the operator has INECLAMATION DUE_5.22/7 00 sx Class H cement 11086-11660. at from 8297-8542'. Layed down 7-7078'. POH to 6000' w/ tbg. Tried 45'. WOC. Tagged plug @ 4821'.). POH w/ tbg. @ 1169-924. WOC. Tagged plug to 60'. Spotted 20 sx class C f wellhead. Waited on BLM for 2 location. Moved off. 2m ber 29, 2012.
Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready for 11/19/12 MIRU plugging e 11/20/12 Finish ND wellhe 11/21/12 Finished RIH w/ POH w/ 2500' tbg. WOC. 11/26/12 Tagged plug @ 11 tbg. to 7078'. Circulated 23 to bullhead sqz cement into 11/27/12 Tagged plug @ 6 Spotted 125 sx class C cement 11/28/12 Tagged plug @ 3 @ 945'. Spotted 25 sx class cement to surface. 11/29/12 Rigged down move hours. Welded on Dry Hold ccepted as to plugging of the ability under bond is retained rface restoration is completed 14. Thereby certify that the foregoing is	ived operations. If the operations of the operation of th	ion results in a multiple c be filed only after all r n well ND wellhead 77 jts. 2 7/8 tbg. RI ed 230 BBLS mud bg. to 8542'. Spotted id. Spotted 90 sx Closed Gootted 90 sx class K'd by Marlan Des g. to 1169'. Spotted 2. POH WOC. Tag ckhoe and welder. Cellar. Removed of Jgg ing Con Title	completion or recompletion in a equirements, including reclaman d. H w/ 1800' tbg. laden fluid. Spotted 1 ed 50 sx class H cemen Class C cement @ 6637 d well in w/ 500 psi. C cement. POH to 40 aton to combine plugs. I 50 sx class C cement ged plug @ 595'. RIH Dug out cellar. Cut off leadmen and cleaned 1 npletecl NoveOperation	new interval, a Form 3160-4 shall be filed once ntion, have been completed, and the operator has RECLAMATION DUESSIZZE 00 sx Class H cement 11086-11660. at from 8297-8542'. Layed down 7-7078'. POH to 6000' w/ tbg. Tried 45'. WOC. Tagged plug @ 4821'. b). POH w/ tbg. @ 1169-924. WOC. Tagged plug to 60'. Spotted 20 sx class C f wellhead. Waited on BLM for 2 location. Moved off. 2m ber 29, 2012. Manager 01.2:
Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready for 11/19/12 MIRU plugging e 11/20/12 Finish ND wellhe 11/21/12 Finished RIH w/ POH w/ 2500' tbg. WOC. 11/26/12 Tagged plug @ 11 tbg. to 7078'. Circulated 23 to bullhead sqz cement into 11/27/12 Tagged plug @ 6 Spotted 125 sx class C cement 11/28/12 Tagged plug @ 3 @ 945'. Spotted 25 sx class cement to surface. 11/29/12 Rigged down move hours. Welded on Dry Hold cepted as to plugging of the ability under bond is retained rface restoration is completed (A. Thereby certify that the foregoing is Name (Printed/Typed)	ived operations. If the operations of the operation of th	ion results in a multiple c be filed only after all r n well ND wellhead 77 jts. 2 7/8 tbg. RI ed 230 BBLS mud bg. to 8542'. Spotted id. Spotted 90 sx Closed Gootted 90 sx class K'd by Marlan Des g. to 1169'. Spotted 2. POH WOC. Tag ckhoe and welder. Cellar. Removed of Jgg ing Con Title	completion or recompletion in a equirements, including reclaman d. H w/ 1800' tbg. laden fluid. Spotted 1 ed 50 sx class H cemen Class C cement @ 6637 I well in w/ 500 psi. C cement. POH to 40 aton to combine plugs. I 50 sx class C cement ged plug @ 595'. RIH Dug out cellar. Cut off leadmen and cleaned I $p \int e fect N 0 \sqrt{e}$	new interval, a Form 3160-4 shall be filed once ntion, have been completed, and the operator has RECLAMATION DUESSIZZE 00 sx Class H cement 11086-11660. at from 8297-8542'. Layed down 7-7078'. POH to 6000' w/ tbg. Tried 45'. WOC. Tagged plug @ 4821'. b). POH w/ tbg. @ 1169-924. WOC. Tagged plug to 60'. Spotted 20 sx class C f wellhead. Waited on BLM for 2 location. Moved off. 2m ber 29, 2012. Manager 01.2:
Attach the Bond under which the following completion of the invol testing has been completed. Fina determined that the site is ready for 11/19/12 MIRU plugging e 11/20/12 Finish ND wellhe 11/21/12 Finished RIH w/ POH w/ 2500' tbg. WOC. 11/26/12 Tagged plug @ 11 tbg. to 7078'. Circulated 23 to bullhead sqz cement into 11/27/12 Tagged plug @ 6 Spotted 125 sx class C cement 11/28/12 Tagged plug @ 3 @ 945'. Spotted 25 sx class cement to surface. 11/29/12 Rigged down move hours. Welded on Dry Hold cepted as to plugging of the ability under bond is retained rface restoration is completed (A. Thereby certify that the foregoing is Name (Printed/Typed)	ived operations. If the operations of the operation of th	ion results in a multiple c be filed only after all r n well ND wellhead 77 jts. 2 7/8 tbg. RI ed 230 BBLS mud bg. to 8542'. Spotted id. Spotted 90 sx Closed Gopotted 90 sx class K'd by Marlan Des g. to 1169'. Spotted 2. POH WOC. Tag ckhoe and welder. Cellar. Removed of Jgg i ng Con Title Date FOR FEDERAL O	completion or recompletion in a equivements, including reclamaned. H w/ 1800' tbg. laden fluid. Spotted 1 ed 50 sx class H cement class C cement @ 6637 d well in w/ 500 psi. C cement. POH to 40 aton to combine plugs. I 50 sx class C cement ged plug @ 595'. RIH Dug out cellar. Cut off leadmen and cleaned I plefecl Nove Operation I 2 - 6 - 2 PR STATE OFFICE U Title Office	new interval, a Form 3160-4 shall be filed once ntion, have been completed, and the operator has RFCLAMATION DUE <u>5</u> ·22/2 00 sx Class H cement 11086-11660. at from 8297-8542'. Layed down 2-7078'. POH to 6000' w/ tbg. Tried 45'. WOC. Tagged plug @ 4821'. b). POH w/ tbg. @ 1169-924. WOC. Tagged plug to 60'. Spotted 20 sx class C f wellhead. Waited on BLM for 2 location. Moved off. 2. <u>Manager</u> <u>01.2:</u>

1