

Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87401
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-30493

5. Indicate Type of Lease
DATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Bear

8. Well Number 1

9. OGRID Number 243978

10. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PLUGS TO ABANDON OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Saber Oil & Gas Ventures, LLC

3. Address of Operator
400 W Illinois, Ste 950, Midland, TX 79701

4. Well Location

Unit Letter F : 1980 feet from the North line and 1980 feet from the

West line

Section 11 Township 18S Range 38E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3636' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

CIBP @ 4800' w/ 25sx 'C' cmt (San Andres)
Circ hole bottoms up w/ 10# mud laden fluid
25sx @ 4155' - 4055' (Queen)
Perf & Sqz @ 3318' w/ 30sx Tag no lower than 3218' (Yates)
Perf & Sqz @ 2063' w/ 30sx Tag no lower than 1963' (Anhy)
Perf & Sqz @ 400' w/ 125sx to surf
Cut off wellhead and install dry hole marker

Perf @ 450'

Spud Date:

1/24/89

Rig Release Date:

TD @ 2/4/89

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Danny Cox

TITLE

Plugging Supervisor

DATE

1-16-13

Type or print name
For State Use Only

Danny Cox

E-mail address:

dbubbarov@gmail.com

PHONE:

432-557-5554

APPROVED BY:

[Signature]

TITLE

DIST MGR

DATE

1-16-2013

Conditions of Approval (if any):

Bear # 1 - 1980' FNL & 1980' FWL of Sec. 11, T-18S, R38E - Unit Letter F - Lea Co., NM

Spud Date: 1 / 24 / 89

TD'ed Date: 2/4/89

Compl Date: 4/24/89

Elev: 3636' - GL - 3649.6' KB

Field: East Bishop Canyon (San Andres)

API #: 30 - 025 - 30493

County: Lea, NM

8 5/8" - 24 # Casing Set @ 400' - cmt with 300 sxs - Circ'd 75 sxs

10/12/89 Shot sqz holes @ 4072' - 4073' (4 holes) Set Retainer @ 4020' & sqz'd w/ 50 sxs. D/O & test. Sva Queen perfs - heavy salt
(4/17/89) Re-Perf Queen: 4111', 4112', 4113' (3 holes) 4110' - 4119' (10 holes)
(10/16/89) Set cmt ret @ 4055' - sqz with 100 sxs - 3200# with 25 sxs in formation

10/11/89 Shot sqz holes @ 4190' - 4191' (4 holes) could not pump into sqz holes

San Andres perfs: 4889.5', 4890.5', 4891.5', 4919.5', 4920.5', 4921.5' (6 holes)
3/89 perf: 4864' to 4868' (5 holes) 100 gals acid / Set cmt ret @ 4878' & sqz 25 sxs

PBTD @ 4942'

5 1/2" - 16.5# & 17# casing @ 4980' (17# casing from 4303' - 4714')
cemented with 400 sxs - TOC @ 3300'

Bear # 1 - 1980' FNL & 1980' FWL of Sec. 11, T-18S, R38E - Unit Letter F - Lea Co., NM

Spud Date: 1 / 24 / 89

TD'ed Date: 2/4/89

Compl Date: 4/24/89

Elev: 3636' - GL - 3649.6' KB

Field: East Bishop Canyon (San Andres)

API #: 30 - 025 - 30493

County: Lea, NM

8 5/8" - 24 # Casing Set @ 400' - cmt with 300 sxs - Circ'd 75 sxs

100 gals 15% Acid

10/12/89 Shot sqz holes @ 4072' - 4073' (4 holes) Set Retainer @ 4020' & sqz'd w/ 50 sxs. D/O & test.

(4/17/89) Re-Perf Queen: 4111', 4112', 4113' (3 holes) 4110' - 4119' (10 holes)
(10/16/89) Set cmt ret @ 4055' - sqz with 100 sxs - 3200# with 25 sxs in formation

10/11/89 Shot sqz holes @ 4190' - 4191' (4 holes) could not pump into sqz holes

350 gals 16% HCL acid

San Andres perms: 4889.5', 4890.5', 4891.5', 4919.5', 4920.5', 4921.5' (6 holes)
3/89 perf: 4864' to 4868' (5 holes) 100 gals acid / Set cnt ret @ 4878' & sqz 25 sxs

PBTD @ 4942'

6 1/2" - 15.5# & 17# casing @ 4960' (17# casing from 4303' - 4714')
cemented with 400 sxs - TOC @ 3300'