

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OGD

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

JAN 22 2013

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-05565
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator OXY USA Inc.		6. State Oil & Gas Lease No. E 3289
3. Address of Operator P.O. Box 50250 Midland, TX 79710		7. Lease Name or Unit Agreement Name NM CE State
4. Well Location Unit Letter <u>F</u> : <u>1655</u> feet from the <u>north</u> line and <u>330</u> feet from the <u>west</u> line Section <u>6</u> Township <u>19S</u> Range <u>37E</u> NMPM County <u>Lea</u>		8. Well Number <u>1</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>3733'</u>		9. OGRID Number <u>16696</u>
10. Pool name or Wildcat <u>Enmad Yates TR Qn</u>		

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of
C-103 (Specifically for Subsequent Report of Well
Plugging) which may be found at OGD web page
www.emnrd.state.nm.us/ogd
PULL OR ALTER
DOWNHOLE COMMINGLED

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐ OTHER: ☐
13. Describe proposed or completed operations. (State all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/26/12 MIRU PU, RIH & tag @ 2730'
12/27/12 Circ well w/ 10# MLF, test csg to 500#, held OK. RIH bit, DC, RU swivel, Drill on CIBP.
12/28/12 Continue to drill out CIBP, push to bottom, tag up @ 4007'. POOH, LD.
12/31/12 RIH & set CIBP @ 3845', circ hole w/ 10# MLF, test csg to 550#, held OK. Spot 25sx CL C cmt, Calc TOC 3467'. PUH to 2713', spot 25sx CL C cmt, PUH, WOC.
1/2/13 RIH & set pkr @ 1162', RIH & tag cmt @ 2285', PUH & perf @ 1525', circ hole w/ 10# MLF, pkr failed, Repl pkr, EIR @ 1000#, w/ partial circ, load backside to 700#, pkr leaking, bled off, POOH.
1/3/13 RIH & set pkr @ 1162', EIR into perms @ 1525' @ 1.5BPM @ 1000#, sqz 65sx CL C cmt, WOC.
1/7/13 RIH & tag cmt @ 1310', Mark Whitaker-NMOCD Appr cont w/ surface plug, PUH, set pkr @ 60', RIH & perf @ 300', EIR, circ 90sx CL C cmt to surf. ND BOP, top off csg, RDPU.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Regulatory Advisor DATE 1/23/13

Type or print name David Stewart E-mail address: david_stewart@oxy.com PHONE: 432-685-5717
For State Use Only

APPROVED BY: [Signature] TITLE Dist MGR DATE 1-23-2013
Conditions of Approval (if any):