Submit 1 Copy To Appropriate District Office State of New Mexico	Form C-103
District I – (575) 393-6161 Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240	Revised August 1, 2011 WELL API NO.
District II - (575) 748-1283 811 S. First St., Artesia, NM 8821036 OCD OIL CONSERVATION DIVISION	30-025-40408 5. Indicate Type of Lease
811 S. First St., Artesia, NM 88210 SOLD OIL CONSERVATION DIVISION District III – (505) 334-61784 OBS 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410	STATE FEE
District IV - (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505 87505	6. State Oil & Gas Lease No. VB-1186/VB-1194
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name Undaunted BSD State Com
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	8. Well Number
1. Type of Well: Oil Well Gas Well Other	1H
2. Name of Operator Yates Petroleum Corporation	9. OGRID Number / 025575
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210	10. Pool name or Wildcat Wildcat; Bone Spring, Upper Shale
	feet from the <u>East</u> line
Unit Letter	feet from the East line 2200 feet from the East line
Section 2 Township 25S Range 32E	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc., 3515'GR	
12. Check Appropriate Box to Indicate Nature of Notice, R	eport or Other Data
NOTICE OF INTENTION TO: SUB	SEQUENT REPORT OF: K
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRI	LLING OPNS P AND A
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN DOWNHOLE COMMINGLE CASING/CEMEN CASIN	ГЈОВ 🔲
OTHER: OTHER: Product 13. Describe proposed or completed operations. (Clearly state all pertinent details, and	
	i give pertinent dates, including estimated
date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.	
proposed completion or recompletion.	
proposed completion or recompletion 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu	e Completions: Attach wellbore diagram of lated off cement at 10,228'. Circulated 95
proposed completion or recompletion 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through the 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling.	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally.
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423': Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231": Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,464.	e Completions: Attach wellbore diagram of lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'.
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,460 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cemented stage 1 with 10 cemented stage 1	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" +
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,460 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% and stage 2 with 450 sx 35:65 Poz "H" + 5 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,466 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 +	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 6 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3%
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,46 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 6 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3%
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,466 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 + 0.2 with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6).	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 5 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3%
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,466 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 +	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 6 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3%
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423': Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231": Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,46 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 + 0.2 with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6).	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 5 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3% 2% PF153 (yld 2.05, wt 12.6). Tailed in
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423': Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231": Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,46 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 + 0.2 with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6).	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 6 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3% PF153 (yld 2.05, wt 12.6). Tailed in
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,46 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 + 0.2 with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Spud Date: 6/28/12 Rig Release Date:	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 65 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3% PF153 (yld 2.05, wt 12.6). Tailed in
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231'. Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,46 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 + 0.2 with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Spud Date: 6/28/12 Rig Release Date: Title Regulatory Reporting Super Type or print name Tina Huerta E-mail address stinata@vatespetroleur	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 5 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3% PF153 (yld 2.05, wt 12.6). Tailed in
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423': Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231". Drilled cement to 10,415'. Worked through the 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,46 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 + 0.2 with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Spud Date: 6/28/12 Rig Release Date: Title Regulatory Reporting Super Type or print name Tina Huerta E-mail address ** stination squares petroleum For State Use Only Petrolaum Fresionaem	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 6 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3% PF153 (yld 2.05, wt 12.6). Tailed in 1/27/13 e and belief. 1/27/13 PHONE:575-748-4168
proposed completion or recompletion. 1/14/13 – TD 8-3/4" pilot hole to 11,100' at 9:30 AM. 1/17/13 – Whipstock set at 10,423'. Set cement plug with 377 sx Class "H" cement. Circu sx to half round. Tagged cement at 10,231'. Drilled cement to 10,415'. Worked through to 1/19/13 – Drilled to 11,021' and reduced hole to 8-1/2" and continued drilling. 1/24/13 – Reached TD 8-1/2" hole to 15,464'. Set 5-1/2" 17# P-110 LT&C casing at 15,46 External casing packer at 7510'. Float collar at 15,416'. Cemented stage 1 with 871 sx PV PF151 + 0.2% PF153 + 5% PF174 + 0.7% PF606 + 0.2% PF800 (yld 1.87, wt 13). Cement 0.3% PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 in with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Circulated 245 sx. Cemented PF013 + 6% PF020 + 0.125#/sx PF029 + 3#/sx PF042 + 5% PF044 + 0.25#/sx PF046 + 0.2 with 100 sx Class "H" + 0.4% PF013 (yld 1.18, wt 15.6). Spud Date: 6/28/12 Rig Release Date: Title Regulatory Reporting Super Type or print name Tina Huerta E-mail address stinata@vatespetroleur	lated off cement at 10,228'. Circulated 95 to 10,418'. Continued to drill directionally. 4'. DV/stage tool at 7508' and 10,373'. L + 0.55% PF013 + 0.25#/sx PF046 + 30% ted stage 2 with 450 sx 35:65 Poz "H" + 5 + 0.2% PF153 (yld 2.05, wt 12.6). Tailed stage 3 with 625 sx 35:65 Poz "H" + 0.3% PF153 (yld 2.05, wt 12.6). Tailed in