

Submit 1 Copy To Appropriate District
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103

October 13, 2009

HOBBS OGD

JAN 09 2013

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-025-04359

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

State E-28

8. Well Number 1

9. OGRID Number

180387

10. Pool name or Wildcat

Eumont:Yates-7rivers

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Finley Resources, Inc

3. Address of Operator

1308 Lake Street Fort Worth, TX 76102

4. Well Location

Unit Letter N : 660 feet from the S line and 1980 feet from the W line

Section 28 Township 20S Range 36E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. RU - Drill out cement plug (183' to 1752')

2. Circulate and clean out to CIBP @ 3748

3. Test csg and evaluate

4. Drill out CIBP and clean out to below 3900'

5. Acidize perms, test and

6. Install Rod pump & equipment to restore to production

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE April Wilkerson TITLE Regulatory Analyst DATE 1/03/2013

Type or print name April Wilkerson E-mail address: awilkerson@finley PHONE: 817-231-8735

For State Use Only

APPROVED BY: [Signature] TITLE Dist MGR DATE 3-6-2013

Conditions of Approval (if any):

MAR 06 2013

State E-28 #1

660' FSL, 1980' FWL, Sec 28N
T20S, R36E Lea Co., NM
Eumont Field completion Date: 1/18/55

KB 3619' (10')
API # 30 025 04359
NM ID 1150042

Status: TA

Tops:
Anhyd 1802'
T. Salt 1930'
B. Salt 3308'
Yates 3622'
7 Rivers 3858'

8 5/8" 24# @ 330' w/ 280 sx. Circ.

Cmt from 1752 - 183'

Potential:

In WF area.
If remains producer
Add upper 7R & Yates
From 3545-3745'. Frac
All zones.

Activity:

1/55: DST#1 3752-3882' Rec 1100' HGCM, DST#2 3870-3919'
Rec 180' GCM, 330' MCO, 300' oil. Perf 3860-98', 500 gal MCA
10000 gal oil, 10000# sd.
5/78: sqz 300 sx @ 750 & 780'. Perf 3758-67', 84-95', 3810-24', 60-98'
2000 gal acid, 24000 gal gel wtr, 37000# sd.
8/82: 2000 gal acid
10/83: 1000 gal acid
10/05: MIT failed. Leaks 1691 - 307'.
12/05: Set CIBP 3748'. Test to 1000# - OK. Spot 160 sx cmt 1752 to 210'.
WOC. Tag cmt 470'. Spot 35 sx cmt to 133'. Tag @ 183'. NU wellhead.
MIT to 580#. Lost 40# in 30 min. Witness by Sylvia Dickey (NMOCD).
Well TA.

CIBP @
3748'

Current
12/2005

7 Rivers:

3758-3898'
3860-98'

5 1/2" 14# J-55 @ 3934' w/ 1150 sx, TOC 1080'