

Submit 1 Copy To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88401  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
October 13, 2009

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-04381
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Finley Resources, Inc		6. State Oil & Gas Lease No. 32214
3. Address of Operator 1308 Lake Street Fort Worth, TX 76102		7. Lease Name or Unit Agreement Name State E-33
4. Well Location Unit Letter F : 1650 feet from the N line and 1980 feet from the W line Section 33 Township 20S Range 36E NMPM County Lea		8. Well Number 3
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3600 GL		9. OGRID Number 180387
		10. Pool name or Wildcat Eumont:Yates-7rivers

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. RU - Drill out cement plug (500' to 1415')
2. Circulate and clean out to CIBP @ 3793
3. Test csg and evaluate
4. Drill out CIBP and clean out CIBP @ 3793 and clean out to below 3900
5. Acidize perfs, test
6. Install Rod pump & equipment to restore to production

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE April Wilkerson TITLE Regulatory Analyst DATE 1/03/2013

Type or print name April Wilkerson E-mail address: awilkerson@finley PHONE: 817-231-8735

For State Use Only

APPROVED BY: [Signature] TITLE Director DATE 3-6-2013  
Conditions of Approval (if any):

MAR 06 2013

# State E 33 #3

1650' FNL, 2340' FWL, Sec 33F  
T20S, R36E Lea Co., NM  
Eumont Field completion Date: 5/7/55

KB 3607' (9')  
API # 30 025 04381  
NM ID 1150056

Status: TA

