

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised August 1, 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-025-33524

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
19256

7. Lease Name or Unit Agreement Name  
"26" STATE "A"

8. Well Number: 5

9. OGRID Number:  
4323

10. Pool name or Wildcat  
MONUMENT; ABO

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other Water Injection

2. Name of Operator  
Chevron U.S.A. INC.

3. Address of Operator  
15 Smith Road Midland, TX 79705

4. Well Location  
Unit Letter L : 1980 feet from the SOUTH line and 330 feet from the West line  
Section 26 Township 19-S Range 36-E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3701' DF

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

| NOTICE OF INTENTION TO:                        |                                                      | SUBSEQUENT REPORT OF:                            |                                          |
|------------------------------------------------|------------------------------------------------------|--------------------------------------------------|------------------------------------------|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input checked="" type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/>           | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/>   | CHANGE PLANS <input type="checkbox"/>                | COMMENCE DRILLING OPNS. <input type="checkbox"/> | P AND A <input type="checkbox"/>         |
| PULL OR ALTER CASING <input type="checkbox"/>  | MULTIPLE COMPL <input type="checkbox"/>              | CASING/CEMENT JOB <input type="checkbox"/>       |                                          |
| DOWNHOLE COMMINGLE <input type="checkbox"/>    |                                                      |                                                  |                                          |
| OTHER: <input type="checkbox"/>                |                                                      | OTHER: <input type="checkbox"/>                  |                                          |

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD-7700' PB-7606' PERFS-7366'-7390',  
11-3/4" 42# csg @ 405' w/260 sx, 14-3/4" hole, TOC Surf  
8-5/8" 24# csg @ 2804' w/740 sx, 11" hole, TOC Surf  
5-1/2" 15.5# & 17# csg @ 7700' w/500 sx, 7-7/8" hole, TOC 4500'

- MIRUWSU. NDWH. NUBOP.
- Set CIBP @ 7266' w/25 sks of Class C cement. → CIRC WELL w/ MLF
- Pressure Test casing to 500 psi and record/report findings.
- Perf & Sqz 50 sks of C cement 4375'-4175' CTOC. WOC & TAG, ( San Andres )
- Perf & Sqz 75 sks of Class C cement 2875' - 2525', WOC & TAG, ( Shoe, Bottom of Salt )
- Perf & Sqz 40 sks of Class C cement 1453' - 1253', WOC & TAG, ( Top of Salt )
- Perf & Circulate 140 sks of C cement 455'-Surface.
- Cut off wellhead and anchors 3' below grade. Weld on dry hole marker. Clean location.

The Oil Conservation Division Must be notified  
24 hours prior to the beginning of plugging operations.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert Holden TITLE Representative DATE 03/07/2013

Type or print name Robert Holden E-mail address: rholden@keyenergy.com PHONE: 432-523-5155

For State Use Only

APPROVED BY [Signature] TITLE Dist MGR DATE 3-13-2013  
Conditions of Approval (if any):

MAR 14 2013

## CURRENT

# WELL DATA SHEET

**FIELD: Monument**

**WELL NAME: State A "26" #5**

**FORMATION: Abo**

LOC: \_1980' FSL & 330' FWL  
TOWNSHIP: 19S  
RANGE: 36E  
LOT: L

SEC: 26  
COUNTY: Lea  
STATE: NM

GL: 3701'  
KB to GL: 13'  
DF to GL:

CURRENT STATUS: PS  
API NO: 30-025-33524  
REFNO: Bi 1927  
WELL BORE 100702

Date Completed: 9-07-96  
Initial Formation: Abo

11-3/4", 42#, H-40 Csg  
Set @ 405' w/260 sx cmt.  
Circulated.

8-5/8", 24#, K-55 Csg  
Set @ 2804' w/740 sx cmt.  
Circulated.

Tubing Detail (07/06/04)  
SEE TBG DETAIL FOR  
SUB PUMP INSTALLATION

### Rod Detail

5-1/2", 15.5/17#, K-55 Csg  
Set @ 7700' w/860 sx cmt  
TOC @ 2600'.

Perf 7366'-7390' w/1 JHPF @ 120 deg. phsg (24 holes).  
Acidz w/750 gals 6% HCL, dropping 36 RCNB's.

3/1/02 - Install art-lift equip & removed pkr. Started pumping to existing btry. F. Trevino

5/22/03 Install sub pump. RIH w/scrapper to 7608' no fill.  
Trevino

7366'-7390'

PBTD 7606'

TD 7700'

# WELL DATA SHEET

Proposed

FIELD: Monument

WELL NAME: State A "26" #5

FORMATION: Abo

LOC: 1980' FSL & 330' FWL  
TOWNSHIP: 19S  
RANGE: 36E  
LOT: L

SEC: 26  
COUNTY: Lea  
STATE: NM

GL: 3701'  
KB to GL: 13'  
DF to GL:

CURRENT STATUS: PS  
API NO: 30-025-33524  
REFNO: Bi 1927  
WELL BORE 100702

Date Completed: 9-07-96  
Initial Formation: Abo

11-3/4", 42#, H-40 Csg  
Set @ 405' w/260 sx cmt.  
Circulated.

Perf & Circulate 140 sks of cmt  
455' - surface w/ 140 sks of  
Class C cmt

8-5/8", 24#, K-55 Csg  
Set @ 2804' w/740 sx cmt.  
Circulated.

Perf & Sqz 40 sks of  
cmt @ 1453' - 1253',  
WOC & TAG ( Top of  
Salt )

Tubing Detail (07/06/04)  
SEE TBG DETAIL FOR  
SUB PUMP INSTALLATION

Rod Detail

Perf & Sqz 75 sks of cmt @  
2875' - 2525', WOC & TAG ( Shoe, Bottom of Salt )

Perf & Sqz 50 sks @ 4375' -  
4175' WOC & TAG ( San  
Andres )

7366'-7390'

PBTD 7606'

Set CIBP @ 7266'  
w/25 sks of cmt

5-1/2", 15.5/17#, K-55 Csg  
Set @ 7700' w/860 sx cmt  
TOC @ 2600'.

TD 7700'

P  
e  
r  
f  
o  
r  
m  
a  
n  
c  
e  
@  
1  
2  
0  
0  
f  
e  
e  
t