

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

Revised August 1, 2011

HOBBS OGD  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505  
MAR 27 2013

RECEIVED

WELL API NO. 30-025-36479
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VA-1894
7. Lease Name or Unit Agreement Name Cash BND State Com
8. Well Number 1
9. OGRID Number 025575
10. Pool name or Wildcat Wildcat; Permo Penn <i>Inbe</i>

4. Well Location Unit Letter <u>J</u> : <u>1980</u> feet from the <u>South</u> line and <u>1980</u> feet from the <u>East</u> line Section <u>31</u> Township <u>10S</u> Range <u>34E</u> NMPM <u>Lea</u> County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4234' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/28/13 - NU BOP.

3/1/13 - Set a 4-1/2" CIBP at 10,000' with 35' cement on top.

3/5/13 - Tagged at 9932'. Spotted 25 sx Class "H" Neat cement at 7222'. Calc TOC at 6844'. Spotted 25 sx Class "C" Neat cement at 4215'. Calc TOC at 3837'.

3/6/13 - Tagged plug at 3847'. Spotted 25 sx Class "C" Neat cement at 2124'. Calc TOC at 1746'. Pumped 35 sx Class "C" Neat cement at 490' and circulated to surface. ND BOP. Topped out casing.

3/25/13 - Dug out cellar and cut off wellhead. Installed dry hole marker. Filled cellar. **WELL IS PLUGGED AND ABANDONED.**

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OGD Web Page under  
Forms, [www.emnrd.state.nm.us/ogd](http://www.emnrd.state.nm.us/ogd).

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Tina Huerta* TITLE Regulatory Reporting Supervisor DATE March 25, 2013

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: *[Signature]* TITLE Petroleum Engineer DATE MAR 28 2013

Conditions of Approval (if any):