

Submit 1 Copy To Appropriate District Office  
 District I - (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II - (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III - (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV - (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised August 1, 2011

HOBBS OGD  
 MAR 25 2013

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. 30-025-36818
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VO-5605
7. Lease Name or Unit Agreement Name Clint BFC State
8. Well Number 1
9. OGRID Number 025575
10. Pool name or Wildcat Wildcat; San Andres
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4230'GR

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well  Gas Well  Other P&A

2. Name of Operator  
Yates Petroleum Corporation

3. Address of Operator  
105 South Fourth Street, Artesia, NM 88210

4. Well Location  
 Unit Letter I : 1980 feet from the South line and 990 feet from the East line  
 Section 4 Township 10S Range 34E NMPM Lea County Lea

Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page www.emnrd.state.nm.us/oed

PERMITS TO PLUG TEMPORARILY TO PULL OR ALTER CEMENT DOWNHOLE COMMINGLE

Appropriate Box to Indicate Nature of Notice, Report or Other Data

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK  ALTERING CASING   
 COMMENCE DRILLING OPNS.  P AND A   
 CASING/CEMENT JOB

OTHER:

13. Describe proposed or completed operations. State all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.4 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 3/6/13 - NU BOP.
- 3/7/13 - Loaded hole with fresh water. Spotted 30 sx cement at 6884'. Calc TOC 6581'.
- 3/8-10/13 - Spotted 30 sx Class "C" Neat cement at 4941'. WOC. Tagged at 4639'. Perforated 4 holes at 4180'. Pumped 40 sx Class "C" Neat cement. Calc to 4080'. WOC.
- 3/11/13 - Tagged plug at 4047'. Perforated 4 holes at 2100'. Pumped 40 sx Class "C" Neat cement with 2% CaCl. WOC 4 hrs. Tagged at 1954'.
- 3/12/13 - Perforated 4 holes at 477'. Pumped down 5-1/2", circulated out 9-5/8" x 5-1/2", pumped 150 sx Class "C" Neat and circulated to surface. ND BOP. Topped out casing.
- 3/20/13 - Dug out cellar and cut off wellhead. Installed dry hole marker. Filled cellar. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:  Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Reporting Supervisor DATE March 21, 2013

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

**For State Use Only**  
 APPROVED BY: [Signature] TITLE Dist. Mgr DATE 3-28-2013  
 Conditions of Approval (if any):  
 MAR 28 2013