Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
<u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources	Revised August 1, 2011 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283	OU CONCERNATION DURIGION	30-025-25493
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III – (505) 334-6178 HOBBS (1000 Rio Brazos Rd., Aztec, NM 87410		STATE X FEE X
District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NMAPR <b>0 8</b> 87505	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES	AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS)  DIFFERENT RESERVOIR. USE "APPLIES HE PROPOSALS.)	TOP PRILL OR TO DEEPEN OR PLUG BACK TO A ON FOR PERMIT" (FORM C-101) FOR SUCH	QUAIL QUEEN UNIT
	Well Other SWD	8. Well Number 14
2. Name of Operator Chevron, U S A,	Inc.	9. OGRID Number 4323
3. Address of Operator 15 Smith Road	705	10. Pool name or Wildcat
Midland, TX 79 4. Well Location	705	SWD; QUEEN (96117)
Unit Letter G: 1980	y feet from the North line and 168	30' feet from the East line
Section 14 Township 19S Range 34E NMPM County Lea		
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
39	957' GR	34°
12. Check Appr	opriate Box to Indicate Nature of Notice,	Report or Other Data
NOTICE OF INTER	NTION TO: SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ REMEDIAL WORK ☐ ALTERING CASING		
	ANGE PLANS   COMMENCE DR	<del>_</del>
	JLTIPLE COMPL	T JOB 🔯
DOWNHOLE COMMINGLE		
OTHER:	OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
Please find attached our procedure for P&A, well bore diagram, and C-144(CLEZ) pit permit.		
-		
•		
The Oil Co		
The Oil Conservation Division Must be notified  24 hours prior to the beginning of plugging operations.		
the beginning of plugging operations		
	·	ons.
	•	
[		
Spud Date:	Rig Release Date:	
Limanian de describitos de la companya del la companya de la compa	1	
Lhereby certify that the information above	e is true, and complete to the best of my knowledg	re and helief
	o is a popular complete to the desc of my knowledge	e did belief.
SIGNATURE //	TITLED	DATE 04/04/2012
SIGNATURE // / Lu	TITLE Regulatory Specialist II	DATE <u>04/04/2013</u>
Type or print name Bryan Arrant (Agent)	E-mail address: bryan.arrant@ch	k.com PHONE: (405)935-3782
For State Use Only		/
APPROVED BY Come	Ken TITLE / JET!/1472	DATE 4-8-2013
Conditions of Approval (if any):		
		APR 09 2013

## Quail Queen Unit # 14 Lea County NM.

## Procedures:

- 1. M.I. R.U. N.D. W.H. N.U. B.O.P.
- 2. Pooh. Tbg. and Pkr.
- 3. Rig up Wireline. Set CIBP. @ 5,024'. Cap w/ 3 sx. cmt.
- 4. Rih. Tbg.Circulate hole mud laden fluid.
- 5. Puh. to 2,000' spot 35 sx. Cmt.
- 6. Puh. to 1,650' spot 30 sx. Cmt.WOC & Tag.
- 7. Puh. To 475' spot 55 sx. Cmt. WOC & Tag.
- 8. 10 sx. Cmt. 30<sup>7</sup> to 3<sup>7</sup>
- 9. R.D.M.O.

## **Current Wellbore Schematic**

WELL (PN): QUAIL QUEEN UNIT 14(CVX) (891056)
FIELD OFFICE: HOBBS
FIELD: QUAIL QUEEN
STATE / COUNTY: NEW MEXICO / LEA
LOCATION: SEC 14-19S-34E, 1980 FNL & 1680 FEL
ROUTE: HOB-NM-ROUTE 11- ADAM FLORES
ELEVATION: GL: 3,957.4 KB: 3,967.0 KB Height: 9.6
DEPTHS: TD: 5,570.0

Chesapeake

API #: 3002525493

SPUD DATE: 3/28/1977
RIG RELEASE: 4/25/1977
1ST SALES GAS:
1ST SALES OIL:
CURRENT STATUS: SHUTIN

Report Printed: 4/4/2013

Original Hole, 4/4/2013 10:15:33 AM Original Hole, 4/4/2013 10:15:33 AM Vertical schematic (actual) Cement Plug; 9.6 ftKB; 30.0 ftKB 10 sxs Cmt from 30' to 3' 9 5/8 in; 36.00 lb/ft; Unknown; 9.6-415.0 ftKB Surface Casina Cement: Cmt w/ 190 sx. Circ 9.6 ftKB; 415.0 ftKB Spot 55 sxs Cmt Cement Plug; 475.0 ftKB; 1,000.0 ftKB. · · Spot 30 sxs Cmt Cement Plug; 1,650.0 ftKB; 1,750.0 ftKB Production Casing Cement; 9.6 ftKB; 1,937.0 DV Tool Spot 35 sxs Cmt ×× Cement Plug; 2,000.0 #KB; 3,000.0 ffKB 鑫 Cemented Bridge Plug; 4 1/2 in; 5,024.0 ftKB B) B (B 2 3/8 in; 9.6-5,068.6 ftKB 万分をおりあいるなどのないの 5,124.0-5,226.0; 5,124.0-5,226.0; 6/24/2009 6/24/2009 5,178.0-5,186.0; 5,178.0-5,186.0; 4/30/1977 4/30/1977 Plug Back Total Depth; 1 "Auto cement plug; **T** 5,531.0 ftKB; 5,570.0 ftKB 5,531.0 Cmt w/ 1205 s Production Casing -Cement; 1,937.0 ftKB; 4 1/2 in; 10.50 lb/ft; J-55 9.6-5,570.0 ftKB 5,570.0 ftKB

Page: 1/1