

District I - (575) 393-6161

Energy, Minerals and Natural Resources

Revised August 1, 2011

1625 N. French Dr., Hobbs, NM 88240

HOBBS OGD

District II - (575) 748-1283

OIL CONSERVATION DIVISION

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

APR 30 2013

220 South St. Francis Dr.

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

Santa Fe, NM 87505

1220 S. St. Francis Dr., Santa Fe, NM 87505

RECEIVED

WELL API NO.

30-025-34446

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
MONUMENT "14" STATE

8. Well Number: 24

9. OGRID Number:

4323

10. Pool name or Wildcat
MONUMENT; ABO NORTH

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other Water Injection

2. Name of Operator

Chevron U.S.A. INC.

3. Address of Operator

15 Smith Road Midland, TX 79705

4. Well Location

Unit Letter I : 1760 feet from the SOUTH line and 990 feet from the EAST line

Section 14 Township 19-S Range 36-E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3732' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD-7500' OH: 7316'-7500' CIBP: 7280'

8-5/8" 23# csg @ 1410' w/450 sks of Class C cement, Hole size 11" Circulated to Surface

5-1/2" 15.5# csg @ 7316' w/ 990 sks Class C cement, Hole size 7-7/8" TOC @ 3800' CBL

1. MIRUWSU. NDWH. NUBOPE.

2. Tag CIBP @ 7280' w/25 sks of C cement

3. Pressure Test casing to 500 psi and record/report findings.

4. Perf & Sqz, w/60 sks of Class C cement @ 3850' - 3650', WOC & TAG, (plug between CIBP & Salts)

5. Perf & Sqz w/60 sks of Class C cement @ 2728' - 2528', CTOC. WOC & TAG, (Bottom of Salt)

6. Perf & Sqz w/60 sks of Class C cement @ 1600' - 1350', CTOC. WOC & TAG, (Top of Salt & Shoe)

7. Perf & Circulate 100 sx of C cement 100'-Surface. 1460 - 1210

8. Cut off wellhead and anchors 3' below grade. Weld on dry hole marker. Clean location.

→ SPOT 25 SX5 CMT @ 5700'.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Representative

DATE

004/25/2013

Type or print name

Robert Holden

E-mail address:

rholden@keyenergy.com

PHONE: 432-523-5155

For State Use Only

APPROVED BY:

TITLE

Compliance Officer

DATE

5/2/2013

Conditions of Approval (if any):

PM

MAY 02 2013

Oil Conservation Division - Hobbs Office: Must be Notified 24 hours prior to the beginning of Plugging Operations begin.

CURRENT

WELL DATA SHEET

FIELD: Monument North

WELL NAME: Monument 14 State #24

FORMATION:

LOC: 1760' FEL & 990' FEL, Unit I
TOWNSHIP: 19S
RANGE: 36E
GPS: 32.65796 -103.31903

SEC: 14
COUNTY: Lea
STATE: NM

GL: 3732'
KB to GL: 13'
DF to GL:

CURRENT STATUS: TA'D
API NO: 30-025-34446
CHEVNO: BT2033

Spud Date: 8/2/1998
Date Completed: 8/29/1998
Last Production: 5/31/2000

8 5/8", 23#, WC-50 Csg
Set @ 1410' w/450 sx cmt
Circulated to surface
Hole Size: 11"

TOC @ 3800'

TOC @ 7245'
CIBP @ 7280'
capped w/ 35' cmt

5 1/2", 15.5/17#, K-55 Csg
Set @ 7316' w/990 sx cmt.
Cmt circulated to surface
TOC @ 3800' by CBL.
Hole Size: 7-7/8"

8/25/98

Spot 500 gals 20% acid in OH 7316'-7500'. TIH w/45A4 ASI-X Pkr to 7265'.

8/26/98

Acidz OH w/11,500 gals 20% HCL.

4/2000

Shut in uneconomical, tbg leak.

2/2001

TA'D well. Set CIBP @ 7280',
Capped w/ 35' cmt. (TOC @ 7245')
Circ 220 bls pkr fluid w/2% KCL.

T. Anby	1384
T. Salt	1478
B. Salt	2628
T. Yates	2776
T. 7 Rivers	3064
T. Queen	3666
T. Grayburg	4014
T. San Andres	4358
T. Glorieta	
T. Paddock	5753
T. Blinbry	6310
T. Tubb	6570
T. Drinkard	6640
T. Abo	7185

TD 7500'

WELL DATA SHEET

PROPOSED

FIELD: Monument North.

WELL NAME: Monument 14 State #24

FORMATION:

LOC: 1760' FEL & 990' FEL, Unit I
TOWNSHIP: 19S
RANGE: 36E
GPS: 32.65796 -103.31903

SEC: 14
COUNTY: Lea
STATE: NM

GL: 3732'
KB to GL: 13'
DF to GL:

CURRENT STATUS: TA'D
API NO: 30-025-34446
CHEVNO: BT2033

Spud Date: 8/2/1998
Date Completed: 8/29/1998
Last Production: 5/31/2000

8 5/8", 23#, WC-50 Csg
Set @ 1410' w/450 sx cmt
Circulated to surface
Hole Size: 11"

Perf & Sqz, w/ 60 sks
of Class C cement, @
3850' - 3650', CTOC,
WOC & TAG, (plug
between CIBP &
Bottom Salt)

TOC @ 3800'

SPOT 25 SKS
@ 5700' →

TOC @ 7245'
CIBP @ 7280'
capped w/ 35' cmt

5 1/2", 15.5/17#, K-55 Csg
Set @ 7316' w/990 sx cmt.
Cmt circulated to surface
TOC @ 3800' by CBL.
Hole Size: 7-7/8"

Perf & Circ w/ 100
sks of Class C cement
100' to Surface

Perf & Sqz w/60 sks of
class C cement @
1600' - 1350', CTOC,
WOC & TAG, (Top of
Salt & Shoe)

Perf & Sqz w/60 sks of Class C
cement, @ 2728' - 2528', CTOC,
WOC & TAG, (Bottom of Salt)

T. Anby	1384
T. Salt	1478
B. Salt	2628
T. Yates	2776
T. 7 Rivers	3064
T. Queen	3666
T. Grayburg	4014
T. San Andres	4358
T. Glorieta	
T. Paddock	5753
T. Blinbry	6310
T. Tubb	6570
T. Drinkard	6640
T. Abo	7185

Tag CIBP @ 7280' w/25 sks
of Class C cement

WBD Updated 4/18/2013
By Bob Hall

TD 7500'

8 5/8" - 23# WC-50 Csg