

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OCD State of New Mexico
 Energy, Minerals and Natural Resources
APR 24 2013
RECEIVED
OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-40627
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other P&A <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No. VO-3900/VB-1384
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Belfast BSL State Com
4. Well Location Unit Letter <u>Lot 13</u> : <u>2700</u> feet from the <u>South</u> line and <u>660</u> feet from the <u>West</u> line Unit Letter <u>Lot 4</u> : <u>320</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>West</u> line Section <u>6</u> Township <u>21S</u> Range <u>34E</u> NMPM <u>Lea</u> County		8. Well Number 1H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3740'GR		9. OGRID Number 025575
10. Pool name or Wildcat Berry; Bone Spring, North		

Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page www.emnrd.state.nm.us/ocd

TEMPORARY PULL OR ALTER CASING
 DOWNHOLE COMMINGLE

Box to Indicate Nature of Notice, Report or Other Data

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/3/13 - Resumed drilling at 12:30 PM. TD 17-1/2" hole to 547'. Set 13-3/8" 48# J-55 ST&C casing at 547'. Cemented with 540 sx Class C + 2% PF001 (yld 1.34, wt 14.8). Circulated 138 sx to pit. Tagged top of float collar at 499'. Drilled float collar and cement to 514'. Tested casing starting psi 693, end psi 655. WOC 22 hrs 30 min. Reduced hole to 12-1/4" and resumed drilling.
 4/7/13-4/13/13 - TD 12-1/4" hole to 4579'. Lost circulation. Lost complete returns at 4532'. Pumped high vis sweep, did not break circulation. Unable to work past tight spot at 3327'. Worked down to 3436' - looking for free point. Run freepoint - 50% free and 2770', 100% free at 2748'. Top of fish at 2724'. Washed and reamed to 779'. Hole packing off. Circulated and cleaned hole. Washed and reamed to top of fish at 2718'. Cleaned hole. Washed and reamed to top of fish at 2718'. Cleaned hole.

CONTINUED ON NEXT PAGE:

Spud Date: 2/25/13 Rig Release Date: 4/16/13

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Tina Huerta* TITLE Regulatory Reporting Supervisor DATE April 22, 2013

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168


For State Use Only
 APPROVED BY: *Tina Huerta* TITLE Petroleum Engineer DATE MAY 06 2013
 Conditions of Approval (if any): 7m.

Form C-103 continued:

4/14/13 – Received orders to P&A well. Notified E.L. Gonzales with NMOCD-Hobbs of operations. Set bottom plug at 2734' with 130 sx Class "C" with 3% CaCl.

4/15/13 – Tagged bottom cement plug with drill pipe at 2625'. Cemented 2nd plug from 1860'-1660' with 130 sx Class "C" Neat. Cemented 3rd plug from 632'-525' with 110 sx Class "C" Neat. Cemented 4th plug at 70' up to surface with 100 sx Class "C" Neat. Circulated 10 sx to surface. ND BOP.

4/16/13 – **WELL IS PLUGGED AND ABANDONED.**


Regulatory Reporting Supervisor
April 22, 2013

-5
 -3
 0
 25
 65
 70
 80
 82
 105
 501
 503
 525
 545
 547
 550
 632
 1,660
 1,860
 2,625
 2,734
 3,080
 3,100
 3,805
 3,823
 4,000
 4,579
 5,350
 5,826
 5,828
 5,850
 5,869
 5,870
 9,000
 10,273
 15,429

