Submit 1 Copy To Appropriate District Office State	e of New Mexico	Form C-103
Submit I Copy To Appropriate District Office District I = (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 District II = (575) 748-1283 811 S. First St., Artesia, NM 88210 District III = (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 District IV = (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505		Revised August 1, 2011 WELL API NO.
		30-25-38826
		5. Indicate Type of Lease
		STATE FEE
		6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		7. Lease Name or Unit Agreement Name
PROPOSALS.)		Christmas 28 8. Well Number
1. Type of Well: Oil Well Gas Well Other		003
Name of Operator Range Operating New Mexico, LLC		9. OGRID Number 227588
3. Address of Operator		10. Pool name or Wildcat
100 Throckmorton St., Ste. 1200, Fort Worth, TX 76102		Blinebry O&G, Tubb O&G, Drinkard, Waltz; Abo
4. Well Location		
Unit Letter M : 990 feet from the South line and 330 feet from the West line		
Section 228 Township 228 Range 37E NMPM County 11. Elevation (Show whether DR, RKB, RT, GR, etc.)		
3398		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO:	SUBS	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABAN		
TEMPORARILY ABANDON	COMMENCE DRIL	
PULL OR ALTER CASING MULTIPLE COMP DOWNHOLE COMMINGLE	L CASING/CEMENT	JOB []
OTHER: Added Pool & Commingled all Pools 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of		
proposed completion or recompletion.		
8-07-2012 - DO CIBP 6380'. Washed hole to CIBP @ 6730 and DO. Washed hole to 6730' and drilled out.		
3-11-2010 - MIRU PU/PT. Unseat pmp, POOH w/rods and 1 1/4" pmp. POOH w/tbg. RIH w/CIBP on setting tool and 3 1/8" Slick Guns (.40" hole, 36" penetration). To 6150' w/CIBP. Correlated to log dated 7-21-2008 and set CIBP @ 6150', Tst CIBP & csg to 4600 psi.		
Good tst. Perf'd 5946 - 5949, 3 spf, 9 shots and 6016' - 6020', 3 spf, 12 shots.		
3-12-2010 - TIH w/ 2 7/8" tbg, flush w/22 bbls of 2% KCL wtr across perfs 5946 - 6020'. RD. POOH w/tbg to 4936' (above all perf &		
acid). RU. Frac w/24 bbls 15% NEFE acid. & 34 bbls 2% KCL wtr. Released pressure. RD. POOH w/tbg. 3-15-1010 - DO CIBP @ 6150'. Hang on well. Test to 500 psi. Good test.		
		•
	011	C-HOB-506
	DA	CAUBSON
Spud Date: 7-26-2008	Rig Release Date: 8-08-2008	
		·
I hereby certify that the information above is true and cor	aplete to the best of my knowledge	and belief.
	. , , ,	
SIGNATURE	FITLE Sr. Reg. Sp.	DATE 5-02-2010
Type or print name Paula Hale For State Use Only	E-mail address: phale@rangeresc	PHONE: 817-869-4216
TO BLACE OSE OTHY		MAV 1 0 0040
	Petroleum Engine	er DATE MAY 1 3 2013
Conditions of Approval (if any):	Ł "	