Submit 1 Copy To Appropriate District State of New Mexico Office Minorula and Disturd Bacaumas	Form C-103 Revised August 1, 2011
District 1 – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240	WELL API NO.
District II - (575) 748-1283 811 S. First St., Artesia, NM 88210 District III - (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 District IV - (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM FEB 07 Santa Fe, NM 87505 ENED	30-025-40675
$\frac{\text{District III}}{1000 \text{ Rio Brazos Rd., Aztec, NM 87410}} = 320 \text{ South St. Francis Dr.}$	5. Indicate Type of Lease STATE STATE
$\frac{District IV}{1220 \text{ S. St. Francis Dr., Santa Fe, NM} FEB V Summary Summary Statistics (1000000000000000000000000000000000000$	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	39181 7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR_SUCH	Tres Equis 5 State
PROPOSALS.)	8. Well Number
1. Type of Well: Oil Well       Gas Well       Other       Dry Hole         2. Name of Operator	9. OGRID Number
Cimarex Energy Co.	215099
<ol> <li>Address of Operator</li> <li>600 N. Marienfeld, Suite 600; Midland, TX 79701</li> </ol>	10. Pool name or Wildcat Triple X; Bone Spring, West
4. Well Location	The A, Bone oping, West
	and <u>1980</u> feet from the <u>West</u> line
Section 5 Township 24S Range 3. 11. Elevation (Show whether DR, RKB, RT, GR,	BE NMPM LEA County
11. Elevation (Snow whether Dik, NKB, KT, OK, 3661 GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
··· ·	
NOTICE OF INTENTION TO: S PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL V	
TEMPORARILY ABANDON CHANGE PLANS COMMENCE	DRILLING OPNS.
PULL OR ALTER CASING  MULTIPLE COMPL CASING/CEN DOWNHOLE COMMINGLE	IENT JOB
OTHER: OTHER: OTHER: Dr 13. Describe proposed or completed operations. (Clearly state all pertinent details	ill and Abandon 🛛 🖾 and give pertinent dates, including estimated date
13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple	, and give pertinent dates, including estimated date
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> </ul>	, and give pertinent dates, including estimated date
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> </ul>	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri</li> </ul>	s, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor,
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> </ul>	s, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor, Il pipe, safety jt, agitator, shock sub. Total fish =
<ol> <li>Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> </ol>	s, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor, Il pipe, safety jt, agitator, shock sub. Total fish = tag @ 4795'.
<ol> <li>Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and</li> </ol>	s, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor, Il pipe, safety jt, agitator, shock sub. Total fish = tag @ 4795'.
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¼" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spot hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> </ul>	s, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor, Il pipe, safety jt, agitator, shock sub. Total fish = tag @ 4795'. ot, bent pipe and broke off leaving 859' of fish in DP, 12 jts of 4.5" DP and 3.10 stick up).
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¼" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spe hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o</li> </ul>	<ul> <li>and give pertinent dates, including estimated date</li> <li>Completions: Attach wellbore diagram of</li> <li>I pipe and BHA. BHA= Bit #11, 1.5 mud motor,</li> <li>II pipe, safety jt, agitator, shock sub. Total fish =</li> <li>tag @ 4795'.</li> <li>bt, bent pipe and broke off leaving 859' of fish in</li> <li>DP, 12 jts of 4.5" DP and 3.10 stick up).</li> <li>x Class C cmt, 14.8 ppg, 1.33 yield from 5000'-</li> <li>f cement retainer from 4654'-4185'. PUH to</li> </ul>
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¼" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spot hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o 1332'. Mix &amp; pump 75 sx Class C, 14.8 ppg, 1.33 yield cmt plug @ 1098-1332'. PUH</li> </ul>	<ul> <li>and give pertinent dates, including estimated date</li> <li>Completions: Attach wellbore diagram of</li> <li>I pipe and BHA. BHA= Bit #11, 1.5 mud motor,</li> <li>II pipe, safety jt, agitator, shock sub. Total fish =</li> <li>tag @ 4795'.</li> <li>bt, bent pipe and broke off leaving 859' of fish in</li> <li>DP, 12 jts of 4.5" DP and 3.10 stick up).</li> <li>x Class C cmt, 14.8 ppg, 1.33 yield from 5000'-</li> <li>f cement retainer from 4654'-4185'. PUH to</li> </ul>
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¼" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spe hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o</li> </ul>	<ul> <li>and give pertinent dates, including estimated date</li> <li>Completions: Attach wellbore diagram of</li> <li>I pipe and BHA. BHA= Bit #11, 1.5 mud motor,</li> <li>II pipe, safety jt, agitator, shock sub. Total fish =</li> <li>tag @ 4795'.</li> <li>bt, bent pipe and broke off leaving 859' of fish in</li> <li>DP, 12 jts of 4.5" DP and 3.10 stick up).</li> <li>x Class C cmt, 14.8 ppg, 1.33 yield from 5000'-</li> <li>f cement retainer from 4654'-4185'. PUH to</li> <li>I to 400'. Mix &amp; pump145 sx Class C, 14.8 ppg,</li> </ul>
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TlH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¾" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spot hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o 1332'. Mix &amp; pump 75 sx Class C, 14.8 ppg, 1.33 yield cmt plug @ 1098-1332'. PUH 1.33 yield cmt plug at 400'. Circulated 2 bbls cmt to surface.</li> <li>10/13/2012 Cut &amp; pull wellhead 4' below ground level and weld on identification plat</li> </ul>	<ul> <li>and give pertinent dates, including estimated date</li> <li>Completions: Attach wellbore diagram of</li> <li>I pipe and BHA. BHA= Bit #11, 1.5 mud motor,</li> <li>II pipe, safety jt, agitator, shock sub. Total fish =</li> <li>tag @ 4795'.</li> <li>bt, bent pipe and broke off leaving 859' of fish in</li> <li>DP, 12 jts of 4.5" DP and 3.10 stick up).</li> <li>x Class C cmt, 14.8 ppg, 1.33 yield from 5000'-</li> <li>f cement retainer from 4654'-4185'. PUH to</li> <li>I to 400'. Mix &amp; pump145 sx Class C, 14.8 ppg,</li> </ul>
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¾" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spot hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o 1332'. Mix &amp; pump 75 sx Class C, 14.8 ppg, 1.33 yield cmt plug @ 1098-1332'. PUH 1.33 yield cmt plug at 400'. Circulated 2 bbls cmt to surface.</li> <li>10/13/2012 Cut &amp; pull wellhead 4' below ground level and weld on identification plat</li> </ul>	<ul> <li>and give pertinent dates, including estimated date</li> <li>Completions: Attach wellbore diagram of</li> <li>I pipe and BHA. BHA= Bit #11, 1.5 mud motor,</li> <li>II pipe, safety jt, agitator, shock sub. Total fish =</li> <li>tag @ 4795'.</li> <li>bt, bent pipe and broke off leaving 859' of fish in</li> <li>DP, 12 jts of 4.5" DP and 3.10 stick up).</li> <li>x Class C cmt, 14.8 ppg, 1.33 yield from 5000'-</li> <li>f cement retainer from 4654'-4185'. PUH to</li> <li>I to 400'. Mix &amp; pump145 sx Class C, 14.8 ppg,</li> <li>e. Rig down.</li> </ul>
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¾" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spo hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o 1332'. Mix &amp; pump 75 sx Class C, 14.8 ppg, 1.33 yield cmt plug @ 1098-1332'. PUH 1.33 yield cmt plug at 400'. Circulated 2 bbls cmt to surface.</li> <li>10/13/2012 Cut &amp; pull wellhead 4' below ground level and weld on identification plat</li> <li>Spud Date:</li> </ul>	s, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor, Il pipe, safety jt, agitator, shock sub. Total fish = tag @ 4795'. ot, bent pipe and broke off leaving 859' of fish in DP, 12 jts of 4.5" DP and 3.10 stick up). x Class C cmt, 14.8 ppg, 1.33 yield from 5000'- f cement retainer from 4654'-4185'. PUH to I to 400'. Mix & pump145 sx Class C, 14.8 ppg, e. Rig down. 10/13/2012
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¼" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spot hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o 1332'. Mix &amp; pump 75 sx Class C, 14.8 ppg, 1.33 yield cmt plug @ 1098-1332'. PUH 1.33 yield cmt plug at 400'. Circulated 2 bbls cmt to surface.</li> <li>10/13/2012 Cut &amp; pull wellhead 4' below ground level and weld on identification plat</li> <li>Spud Date: 8/23/12</li> </ul>	<ul> <li>and give pertinent dates, including estimated date Completions: Attach wellbore diagram of</li> <li>I pipe and BHA. BHA= Bit #11, 1.5 mud motor, Il pipe, safety jt, agitator, shock sub. Total fish = tag @ 4795'.</li> <li>bt, bent pipe and broke off leaving 859' of fish in DP, 12 jts of 4.5" DP and 3.10 stick up).</li> <li>ax Class C cmt, 14.8 ppg, 1.33 yield from 5000'-f cement retainer from 4654'-4185'. PUH to I to 400'. Mix &amp; pump145 sx Class C, 14.8 ppg,</li> <li>e. Rig down.</li> <li>10/13/2012</li> </ul>
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¾" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spt hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o 1332'. Mix &amp; pump 75 sx Class C, 14.8 ppg, 1.33 yield cmt plug @ 1098-1332'. PUH 1.33 yield cmt plug at 400'. Circulated 2 bbls cmt to surface.</li> <li>10/13/2012 Cut &amp; pull wellhead 4' below ground level and weld on identification plat</li> <li>Spud Date: <u>8/23/12</u> Rig Release Date:</li> <li>I hereby certify that the information above is true and complete to the best of my know</li> </ul>	a, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor, II pipe, safety jt, agitator, shock sub. Total fish = tag @ 4795'. Dt, bent pipe and broke off leaving 859' of fish in DP, 12 jts of 4.5" DP and 3.10 stick up). x Class C cmt, 14.8 ppg, 1.33 yield from 5000'- f cement retainer from 4654'-4185'. PUH to I to 400'. Mix & pump145 sx Class C, 14.8 ppg, e. Rig down. 10/13/2012 ledge and belief. 
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¾" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spot hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o 1332'. Mix &amp; pump 75 sx Class C, 14.8 ppg, 1.33 yield cmt plug @ 1098-1332'. PUH 1.33 yield cmt plug at 400'. Circulated 2 bbls cmt to surface.</li> <li>10/13/2012 Cut &amp; pull wellhead 4' below ground level and weld on identification plat</li> <li>Spud Date: 8/23/12 Rig Release Date: 18/23/12 Rig Release Date: 18/23/12</li> <li>I hereby certify that the information above is true and complete to the best of my know</li> <li>SIGNATURE Michelle Chappell E-mail address: mchappe</li> </ul>	a, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor, II pipe, safety jt, agitator, shock sub. Total fish = tag @ 4795'. Dt, bent pipe and broke off leaving 859' of fish in DP, 12 jts of 4.5" DP and 3.10 stick up). x Class C cmt, 14.8 ppg, 1.33 yield from 5000'- f cement retainer from 4654'-4185'. PUH to I to 400'. Mix & pump145 sx Class C, 14.8 ppg, e. Rig down. 10/13/2012 ledge and belief. 
<ul> <li>13. Describe proposed or completed operations. (Clearly state all pertinent details of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.</li> <li>9/3/12 Test csg to 3500 psi for 30 min. Okay</li> <li>9/23/12 Drill 7 7/8" hole to TD @15,178</li> <li>9/26/12 Tag fish @ 4882'. Mill from 4884' to 4895'. Left in hole 276 jts NorAM dril FNMDC for MWD, LCP/G MWD, CSNMP, filter sub, change over sub, 45 jts 4 ½ dri 10,306'.</li> <li>9/29/12 Set cement retainer. Cmt with 300 sx Class C, 14.8 ppg, 1.33 yield. TIH and 9/30/12 TIH w/ whipstock. Top of whipstock @ 4776', bottom of window @ 4789'.</li> <li>10/10/12 Drill 8 ¾" hole to 10,548'. Hit tight spot @ 4890'. Attempt to work tight spt hole (BHA, PDC 1.8 MTR, MWD, Flex Monel, filter sub, x-o, 9 – 6.25" DC, 3 jts HW 10/11/12 TIH to top of fish at 4885'. Mill @ 4885' to 4890'.</li> <li>10/12/12 TIH &amp; set cmt retainer @ 4750'. Sting into cmt retainer. Mix &amp; pump 400 s 4750'. PUH to 4654'. Mix &amp; pump 150 sx Class C cmt, 14.8 ppg, 1.33 yield on top o 1332'. Mix &amp; pump 75 sx Class C, 14.8 ppg, 1.33 yield cmt plug @ 1098-1332'. PUH 1.33 yield cmt plug at 400'. Circulated 2 bbls cmt to surface.</li> <li>10/13/2012 Cut &amp; pull wellhead 4' below ground level and weld on identification plat</li> <li>Spud Date: <u>8/23/12</u> Rig Release Date:</li> <li>I hereby certify that the information above is true and complete to the best of my know</li> </ul>	a, and give pertinent dates, including estimated date Completions: Attach wellbore diagram of I pipe and BHA. BHA= Bit #11, 1.5 mud motor, II pipe, safety jt, agitator, shock sub. Total fish = tag @ 4795'. ot, bent pipe and broke off leaving 859' of fish in DP, 12 jts of 4.5" DP and 3.10 stick up). x Class C cmt, 14.8 ppg, 1.33 yield from 5000'- f cement retainer from 4654'-4185'. PUH to I to 400'. Mix & pump145 sx Class C, 14.8 ppg, e. Rig down. 10/13/2012 ledge and belief. 

MAY 2 3 2013