

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

HOBBS OCD
JUN 12 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-20088
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name EUNICE COM
8. Well Number: 2
9. OGRID Number: 4323
10. Pool name or Wildcat PENROSE SKELLY GRAYBURG

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other Water Injection

2. Name of Operator

Chevron USA INC.

3. Address of Operator

15 Smith Road Midland, TX 79705

4. Well Location

Unit Letter L: 1980' feet from the South line and 560' feet from the West line
Section 19 Township 21-S Range 37-E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3515'GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

TD- 6700' PB 4720' PERFS - 6575' - 6667' OH
13-3/8" 48# csg @ 355' w/350 sks, 17-1/2" hole, TOC: SURFACE
9-5/8" 36# csg @ 3700' w/1300 400 sks, 12-1/4" hole, TOC: 2450' Temp Survey
7" Liner OD, 23# @ 6673', TOL @ 3601'

1. MIRUWSU. NDWH. NUBOP.
2. Set CIBP @ 3700', w/25 sks, (TOL & Shoe) WOC - TAG 3500'
3. Circulate well with 9.5 PPG plugging mud. Pressure Test casing to 500 psi and record/report findings.
4. Perf & Sqz w/60 sks of Class C cement @ 3300' - 3100', WOC & TAG, (Bottom of Salt)
5. Perf & Sqz, w/60 sks of Class C cement @ 1700' - 1500', WOC & TAG, (Top of Salt)
6. Perf & Circulate, w/150 sks of Class C cement @ 425' to Surface, (Shoe)
7. Cut off wellhead and anchors 3' below grade. Weld on dry hole marker. Clean location.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

Representative

DATE

06/06/2013

Type or print name Robert Holden

E-mail address: rholden@keyenergy.com PHONE: 432-523-5155

For State Use Only

APPROVED BY:

TITLE

Dist. MGR

DATE

6-13-2013

Conditions of Approval (if any):

Oil Conservation Division - Hobbs office: **Must be Notified**
24 hours prior to the beginning of Plugging Operations begin.

JUN 13 2013

Well: **Eunice Com # 2**
(formerly Graham State I # 2)

Field: **Eumont**

Reservoir: **Yates/7 Rivers/Queen**

Location:

1980' FSL & 560' FWL
Section: 19
Township: 21S
Range: 37E
County: Lea State: NM

Elevations:

GL: 3515'
KB: 3526'
DF: 3525'

**Current
Wellbore Diagram**

Well ID Info:

Chevno: FB3576
API No: 30-025-20088
L5/L6: U314700
Spud Date: 11/18/62
Compl. Date: 1/11/63

Surf. Csg: 13 3/8", 48#, H-40
Set: @ 355' w/ 350 sks
Hole Size: 17 1/2"
Circ: Yes **TOC:** Surface
TOC By: Circulated

Perfs:

Status: 12/27/2001

3374'	3493'	3522'	Cmt Squeezed
3377'	3497'	3543'	Cmt Squeezed
3394'	3502'	3547'	Cmt Squeezed
3397'	3510'	3577'	Cmt Squeezed
3481'	3514'	3582'	Cmt Squeezed

Interm. Csg: 9 5/8", 36#, J-55
Set: @ 3700' w/ 400 sks
Hole Size: 12 1/4"
Circ: No **TOC:** 2450'
TOC By: Temperature Survey

Perfs:

Status:

3722-24'	Penrose Skelly - Cmt Sqzd
3744-46'	Penrose Skelly - Cmt Sqzd
3793-95'	Penrose Skelly - Cmt Sqzd

TOL @ 3601'

PKR @ 3626'

← 3650' - 3890' **OPEN (7/29/2004)**

TOP OF FILL
@ 4720'

CICR @ 5100'
(24' cmt on top)

5176-86' Paddock - Cmt Sqzd

Tubing Detail: (9/2/2008)

#Jts:	Size:	Footage
	KB Correction	11.00
1	2-7/8" X 6' Tbg Sub	6.07
	2-7/8" X 4' Tbg Sub	4.14
115	Jts. 2-7/8" 6.5# J-55 Tbg	3604.68
1	7" AS1-X Packer	7.41

117 Bottom Of String >> 3633.30

Baker Mod D Pkr @ 6500'
(w/ BP'd seal assembly)
(35' cmt on top)

PBTD: 4720"
TD: 6700'

Updated: 5/30/2013

By: Bob Hall

Perfs:

Status:

6575'	Drinkard - Below Plug
6614'	Drinkard - Below Plug
6631'	Drinkard - Below Plug
6667'	Drinkard - Below Plug

Liner: 7" OD 23# J-55
Set: @ 6673' w/ top @ 3601'
Hole Size: 8 3/4"
Circ: Yes **TOC:** 3601' (Top of liner)
TOC By: Circulated

Well: **Eunice Com # 2**
(formerly Graham State I # 2)

Field: **Eumont**

Reservoir: **Yates/7 Rivers/Queen**

Location:
1980' FSL & 560' FWL
Section: 19
Township: 21S
Range: 37E
County: Lea State: NM

Elevations:
GL: 3515'
KB: 3526'
DF: 3525'

Proposed Wellbore Diagram

Well ID Info:
Chevno: FB3576
API No: 30-025-20088
L5/L6: U314700
Spud Date: 11/18/62
Compl. Date: 1/11/63

Surf. Csg: 13 3/8", 48#, H-40
Set: @ 355' w/ 350 sks
Hole Size: 17 1/2"
Circ: Yes TOC: Surface
TOC By: Circulated

Perf & Circulate w/ 150 sks of Class C cement @ 425' to Surface, (Shoe)

Perf & Sqz w/ 60 sks of Class C cement, @ 1700' - 1500', WOC & TAG, (Top Salt)

Perf & Sqz w/ 60 sks of Class C cement @ 3300' - 3100', WOC & TAG, (Bottom of Salt)

Set CIBP @ 3700', w/ 25 sks, (TOL & Shoe)

WOC - TAG @ 3500'

TOL @ 3601'

PKR @ 3626'

TOP OF FILL @ 4720'

CICR @ 5100' (24' cmt on top)

← 3650' - 3890' OPEN (7/29/2004)

5176-86' Paddock - Cmt Sqzd

Tubing Detail: (9/2/2008)

#Jts:	Size:	Footage
	KB Correction	11.00
1	2-7/8" X 6' Tbg Sub	6.07
	2-7/8" X 4' Tbg Sub	4.14
115	Jts. 2-7/8" 6.5# J-55 Tbg	3604.68
1	7" AS1-X Packer	7.41

117 Bottom Of String >> 3633.30

Baker Mod D Pkr @ 6500'
(w/ BP'd seal assembly)
(35' cmt on top)

PBTD: 4720'
TD: 6700'

Perfs:
6575' Drinkard - Below Plug
6614' Drinkard - Below Plug
6631' Drinkard - Below Plug
6667' Drinkard - Below Plug

Liner: 7" OD 23# J-55
Set: @ 6673' w/ top @ 3601'
Hole Size: 8 3/4"
Circ: Yes TOC: 3601' (Top of liner)
TOC By: Circulated

Updated: 5/30/2013

By: Bob Hall