

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87400
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OCD

AUG 19 2013

RECEIVED

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-35584
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name LAUGHLIN
8. Well Number 005
9. OGRID Number 162683
10. Pool name or Wildcat MONUMENT; TUBB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
CIMAREX ENERGY CO. OF COLORADO

3. Address of Operator
600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701

4. Well Location
Unit Letter: H : 2310 feet from the NORTH line and 330 feet from the EAST line
Section 04 Township 20S Range 37E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3555' - GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1) SET 4-1/2" CIBP @ 6,500'; PUMP 25 SXS. CMT. @ 6,500'-6,340'; CIRC. WELL W/ PXA FLUID.
- 2) PUMP 25 SXS. CMT. @ 5,342'-5,192' (T/GLOR.).
- 3) PUMP 55 SXS. CMT. @ 3,875'-3,462' (T/GB, T/QN., DV TOOL); WOC X TAG CMT. PLUG.
- 4) PUMP 40 SXS. CMT. @ 2,910'-2,575' (T/7R, T/YATES, B/SALT); WOC X TAG CMT. PLUG.
- 5) PUMP 25 SXS. CMT. @ 1,450'-1,225' (8-5/8" CSG.SHOE, T/SALT); WOC X TAG CMT. PLUG.
- 6) MIX X CIRC. TO SURF. 15 SXS. CMT. @ 100'-3'.
- 7) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD STEEL PLATE ONTO CSGS. X INSTALL DRY HOLE MARKER.

DURING THIS PROCEDURE WE PLAN TO USE THE CLOSED-LOOP SYSTEM WITH A STEEL TANK AND HAUL CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RULE 19.15.17.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David A. Eyler TITLE: AGENT

DATE: 08/14/13

Type or print name: DAVID A. EYLER

E-mail address: DEYLER@MILAGRO-RES.COM

PHONE: 432.687.3033

For State Use Only

APPROVED BY: [Signature] TITLE: Dist Mgr

DATE: 8-21-2013

Conditions of Approval (if any):

OIL CONSERVATION DIVISION - Hobbs office **Must Be Notified**
24 hours prior to the beginning of Plugging Operations.

AUG 21 2013



KB: 12' above GL

Cimarex Energy Co. of Colorado

Laughlin #5 (Monument Field)

2310' FNL & 330' FEL

Sec. 4, T-20S, R-37E, Lea Co., NM

H. Eads

6/5/2012

API 30-025-35584

12-1/4" Hole

8-5/8" 24# J-55 csg @ 1400' - 33 jts
cmtd w/ 640 sx, 100 sx cmt circ

DV Tool @ 3821'

Rods : 180 - 3/4" Trico T-66 rods

79 - 7/8" Trico D rods

Pump: 2" X 1-1/4" X 20' RHBC

209 jts 2-3/8" 4.7# 8rd J-55 Tbg

CIBP @ 6650'

Tubb perfs:

(6539' - 6542')

(6605' - 6608')

Tubb perfs: (6658' - 6662')

7-7/8" Hole

4-1/2", 11.6# N-80 csg @ 6901' - 162 jts
cmt w/ 1500 sx (Stg 1: 700, circ 98 & Stg 2: 800, circ 14)

PBTD @ 6650'

TD @ 6901'



KB: 12' above GL

Cimarex Energy Co. of Colorado

Laughlin #5 (Monument Field)

2310' FNL & 330' FEL

Sec. 4, T-20S, R-37E, Lea Co., NM

H. Eads J L H.

6/5/2012

API 30-025-35584

12-1/4" Hole

Circ. 15 sx s. cmt. ca 100' - 3' ,
20 sx 200' - 3'
✓ Pump 25 sx s. cmt. ca 1450' - 1225' - 716

8-5/8" 24# J-55 csg @ 1400' - 33 jts
cmt d w/ 640 sx, 100 sx cmt circ

✓ Pump. 40 sx s. cmt. ca 2910' - 2575' - 716

✓ Pump 55 sx s. cmt. ca 3875' - 3462' - 716

DV Tool @ 3821'

✓ Pump 25 sx s. cmt. ca 5342' - 5192' - 716

✓ Pump 25 sx s. cmt. ca 6500' - 6340' - 716

SET " 4-1/2" CIBP @ 6500'

Tubb perms:

(6539' - 6542')

(6605' - 6608')

Tubb perms: (6658' - 6662')

4-1/2", 11.6# N-80 csg @ 6901' - 162 jts

cmt w/ 1500 sx (Stg 1: 700, circ 98 & Stg 2: 800, circ 14)

CIBP @ 6650'

7-7/8" Hole

PBTD @ 6650'

TD @ 6901'