

Form 3160-5 (August 2007)

HOBBS OGD

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

New Mexico Oil Conservation Division 1625 N. French Drive Hobbs, NM 88240

APPROVED OMB No. 1004-0137 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2.

7. If Unit of CA/Agreement, Name and/or No.

1. Type of Well [X] Oil Well [ ] Gas Well [ ] Other

8. Well Name and No. Perseus 10 Federal Com4H

2. Name of Operator Chevron Operating Inc

9. API Well No. 30-005-29204

3a. Address 1400 Smith St. 43.076 Houston, TX 77002

3b. Phone No. (include area code) 832-714-0670

10. Field and Pool or Exploratory Area Undesignated-ABO-Wolfcamp

4. Location of Well (Footage, Sec., T., R., M., or Survey Description) At Surface NENE 660FNL 240FEL At proposed prod Zone NENE 660 FNL 330FWL

11. Country or Parish, State Sec 10 T15S R31E Mer NMP SME: FEE

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

Table with columns TYPE OF SUBMISSION and TYPE OF ACTION. Includes checkboxes for Notice of Intent, Subsequent Report, Final Abandonment Notice, and various actions like Acidize, Deepen, Production (Start/Resume), etc.

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recomplate in a new interval, a Form 3160-4 must be filed once testing has been completed. Final-Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Chevron respectfully requests the use of a Coflex hose. This is a follow up sundry for EC transaction #208895. Please see the attached certification information.

Your request for a variance to allow drilling of this well using a 15000 psi co-flex hose between the BOP and choke manifold is approved with the condition that the hose shall be anchored in a straight line with no more than a 30 degree turn.

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) Kyle Johnson Title Drilling Engineer Date 07/08/2013

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by /S/ DAVID R. GLASS PETROLEUM ENGINEER Date JUL 08 2013

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office ROSWELL FIELD OFFICE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

FOR RECORD ONLY

SEP 03 2013



**Robisco, Inc.**  
**OILFIELD RUBBER PRODUCTS**  
 4749 Eastpark Drive  
 Houston, TX 77028  
 United States of America

*Gates Corporation Authorized Rotary and Vibrator Hose Subcontracted Fabricator*

Hydrostatic Test Certification

Robisco, Inc. certifies that the following hose assembly has been tested to the Gates Oilfield Roughneck Agreement/Specification requirements and passed the hydrostatic test per API Spec 7K, Fifth Edition, June 2010, Test pressure 9.6.7 and per Table 9 to 15,000 psi in accordance with this product number. Hose burst pressure 9.6.7.2 exceeds the minimum of 2.25 times the working pressure per Table 9.

**Assembly Part Number**  
36332R3-1/16HUB10K-LL-L

**Serial Number / Date Code**  
L32461102512R112712-5

**Chart Recorder Information**

<b>Hose Size</b>	<b>Testers</b>	<b>Serial Number</b>	<b>Calibration Date</b>
<u>3.5IN X 32FT</u>	<u>OC CS</u>	<u>Recorder 22349</u>	<u>Oct. 19th 2012</u>

Lloyd's Register Type Approved for Fire Test OD/1000/499 Rev 1

Hydrostatic Test: Passed  
 Visual Inspection: Passed

  
 \_\_\_\_\_  
 QA Representative Signature

11/28/2012 f S  
 Date & Initial

**Shipper:**

**GHX - Robsco, Inc.**  
**4749 Eastpark Drive**

**Houston, TX 77028**  
**Rufus Dominguez 713-672-1777**

Shipment Reference: 9415989  
Consignee Reference: 491394-156JR  
Total Weight: 1687  
Total Shipment Pieces: 1

Label 1 of 1

Saia, Inc.  
853-1923-A  
11/29/2012

**Special Instruction**

DO NOT STAND CRATES ON END!!!!

DIM Weight: 1105  
qty: 1 (88 x 84 x 29)

00608423360 2

**TOTAL SERVICE SUPPLY LP**  
**1620 VICEROY**

**ODESSA, TX 79763**  
**ATTN: BRUCE**

---

*(Fold Sheet Here)*