

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBS OGD

OCT 10 2013

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr. Santa Fe, NM 87505

WELL API NO. 30-025-24164
5. Indicate Type of Lease STATE [X] FEE [ ]
6. State Oil & Gas Lease No. 1149417
7. Lease Name or Unit Agreement Name Warrior State
8. Well Number 2
9. OGRID Number 180387
10. Pool name or Wildcat Eumont: Yates-7 Rivers-Queen

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well [X] Gas Well [ ] Other [ ]

2. Name of Operator Finley Resources, Inc.

3. Address of Operator 1308 Lake St. Ft. Worth, TX 73102

4. Well Location
Unit Letter O : 4545 feet from the N line and 1980 feet from the E line
Section 2 Township 21 S Range 35 E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate

Indicate Nature of Notice, Report or Other Data

Approved for Plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page under forms/ www.emnrd.state.nm.us/oed

SUBSEQUENT REPORT OF:
REMEDIAL WORK [ ] ALTERING CASING [ ]
COMMENCE DRILLING OPNS: [ ] P AND A [X]
CASING/CEMENT JOB [ ]
OTHER: [ ]

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

09/23/13 MIRU plugging equipment. NU BOP.
09/24/13 RIH w/ tbg and tagged CIBP @ 3558'. Circulated hole w/ mud laden fluid. Pressured up on casing to 500 psi and held. Spotted 25 sx cement on top of CIBP 3558-3458. POH to 2397'. Spotted 25 sx cement @ 2397-2297. Pull out of hole w/ 34 jts. Perf'd csg @ 1550'. Pressured up on perfs to 1000 psi. Held. Spotted 25 sx cement @ 1600-1450, per Mark Whitaker w/ OCD. WOC. Tagged plug @ 1344'. Circulated hole w/ mud laden fluid. Perf'd csg @ 400'. Sqz'd 115 sx cement and circulated to surface. ND BOP.
09/25/13 rigged down moved off. Moved in welder and backhoe. Dug out cellar. Cut off wellhead. Welded on Above Ground Dry Hole Marker. Back filled cellar. Cut off dead men. Cleaned location and moved off.

Spud Date: [ ]

Rig Release Date: [ ]

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE April Wilkerson TITLE Regulatory Analyst DATE 10/1/13

Type or print name April Wilkerson E-mail address: awilkerson@rnr.resources PHONE: 817-231-8735

APPROVED BY [Signature] TITLE Dist. mgr DATE 10/15/2013
Conditions of Approval (if any):

OCT 15 2013