

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources
HOBBBS OCD
 OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 August 1, 2011

OCT 15 2013

RECEIVED

WELL API NO. 30-025-04362
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 32213
7. Lease Name or Unit Agreement Name State E 28
8. Well Number 4
9. OGRID Number 180387
10. Pool name or Wildcat
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Finley Resources, Inc.

3. Address of Operator
1308 Lake Street, Fort Worth, TX 76102

4. Well Location
 Unit Letter **L** : **1980** feet from the **S** line and **990** feet from the **W** line
 Section **28** Township **20-S** Range **36-E** NMPM County **Lea**

12. Check appropriate box to indicate Nature of Notice, Report or Other Data

PERFORMED UNDER BOND
 Approved for Plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page under forms! www.emnrd.state.nm.us/oed

REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/01/13 MIRU plugging equipment. ND well head and NU BOP. RIH w/ tbg to 3800'. Circulated hole w/ mud laden fluid. Tested casing and held 800 psi for 15 minutes. Spotted 55 sx cement @ 3800-3300. Ok'd by Mark Whitaker w/ OCD. Spotted 25 sx cement @ 2210-2100. Spotted 65 sx cement @ 1350-750. Pull out of cement.

10/02/13 Tagged plug @ 708'. POH. Perf'd csg @ 708'. Sqz'd 150 sx cement and circulated to surface. Riggged down and moved off. Moved in backhoe and welder. Cut off wellhead and welded on Above Ground Dry Hole Marker. Backfilled cellar. Cut off deadmen. Cleaned location and moved off.

Spud Date: Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE April Wilkerson TITLE Regulatory Analyst DATE 10/17/13

Type or print name April Wilkerson E-mail address: awilkerson@finleyresources.com PHONE: 817-831-8735

For State Use Only

APPROVED BY: [Signature] TITLE Dist. Mgr DATE 10-17-2013

Conditions of Approval (if any):

OCT 17 2013