

Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM

87505

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

RECEIVED

WELL API NO.

30-025- 26801

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

E-2109

7. Lease Name or Unit Agreement Name

Seay State

8. Well Number

1

9. OGRID Number

231429

10. Pool name or Wildcat

TULK; WOLFCAMP

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

SWD

2. Name of Operator

MANZANO, LLC

3. Address of Operator

PO BOX 2107 ROSWELL, NM 88202

4. Well Location

Unit Letter P : 660 feet from the SOUTH line and 660 feet from the EAST line

Section 30 Township 12S Range 34E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4202 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☒OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☐CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Propose to P & A as follows:

Set CIBP @ 9870' and cap w/ 35' of cement

Circulate hole w/ MLF

Pump 25sx plug @ 6870'

Perforate and squeeze 35sx plug @ 4300' (8 5/8" shoe @ 4200')

Pump 25sx plug @ 2350' (top of salt @ 2300')

Perforate and squeeze 35sx plug @ 401' (13 3/8" shoe @ 364')

Pump 10sx surface plug

→ circ cont to surface

OIL CONSERVATION DIVISION - Hobbs office **Must Be Notified**
24 hours prior to the beginning of Plugging Operations.

Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Craig Hanagan TITLE Operations Foreman DATE 9/9/2013Type or print name Craig Hanagan E-mail address: craig@manzanoenergy.com PHONE: 575-910-6154

For State Use Only

APPROVED BY: [Signature] TITLE Dist. Mgr DATE 10-17-2013

Conditions of Approval (if any):

OCT 17 2013

OCT 27 2013

Pm

Manzano LLC

WELLBORE DIAGRAM

Seay SWD

660' FSL & 660' FEL
Sec30-T-12S-R34E
Lea County, New Mexico
GL Elevation: 4209'
KB Elevation: 4224' (15')

13 3/8" to 364' cemented w/
400sx (circ)

8 5/8" to 4200' cemented w/
2200sx cement circulated

Perforate @ 4300' and sqz
35sx

11/28/80 Sqzd 7203'-7234'
hole in casing w/100sx

Pump 25sx plug @ 6870'

8TD 5 1/2" @ 10,423' cmt w/300

~~Pump 10sx surface plug~~

65 35sx
Perf and squeeze 35 sx @ 401' (surface shoe @ 343') *Circ to Surface*

Spot 25sx @ 2350' (top of salt 2300')

Tubulars

Size	No Jts	Wt	Grade/Thrds	Depth Set (RKB)
13 3/8"		48 #/ft	H40/ST&C	364
8 5/8"		24/28	J-55	4200'
5 1/2"		17 #/ft	K55-N80/LT&C	10423'

Plugging Information

Description

Spot 25sx @ 6870'

Perforate & squeeze 35sx @ 4300'

Spot 25sx @ 2350' (top of salt @ 2300')

Perf and squeeze 35 sx @ 401' (surface shoe @ 343')

Pump 10sx surface plug

TOC @ 8676" (Temp Survey)

Perfs 9920'-9946'