

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt	T. Strawn	T. Kirtland	T. Penn. "B"
T. Rustler 1325'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Salado 1544'	T. Miss	T. Pictured Cliffs	T. Penn. "D"
B Salt 4925'	T. Devonian	T. Cliff House	T. Leadville
T. Yates	T. Silurian	T. Menefee	T. Madison
T. Queen	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware 5189'	T. Morrison	
T. Drinkard	T. Bone Spring 9100'	T. Todilto	
T. Abo	T. 1 st BS Sand	T. Entrada	
T. Wolfcamp	T. 2 nd BS Lm	T. Wingate	
T. Penn	T. 2 nd BS Sand	T. Chinle	
T. Cisco (Bough C)	T. 3 rd BS Sand	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology



Stimulations Summary

District PERMIAN BASIN		County LEA		Field Name JOHNSON RANCH		Project Group DELAWARE BASIN		State/Province NM							
Surface Legal Location SEC33 T23S R33E		API/UWI 3002541032		Latitude (*) 32° 15' 18.009" N		Longitude (*) 103° 34' 46.111" W		Ground Elev... 3,660.50		KB - GL (ft) 25.00		Orig KB Elev (ft) 3,685.50		Tubing Head Elevation (ft)	
HYBRID , 7/29/2013 14:02 , BONE SPRING 2ND, OH , 15,265.5 ftKB - 15,605.8 ftKB, TRICAN , 100 MESH Bulk Sand 143145 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6240.41				4,138.0	7,279.0	80	8,047.0	81	3.36					
HYBRID , 8/28/2013 12:16 , BONE SPRING 2ND, OH , 14,840.0 ftKB - 15,174.0 ftKB, TRICAN , 100 MESH Bulk Sand 95002 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6155.98				4,563.0	6,896.0	79	7,092.0	81	4.42					
HYBRID , 8/29/2013 07:55 , BONE SPRING 2ND, OH , 14,409.0 ftKB - 14,742.0 ftKB, TRICAN , 100 MESH Bulk Sand 105693 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6370.48				4,217.0	7,066.0	81	7,597.0	81	4.33					
HYBRID , 8/29/2013 14:38 , BONE SPRING 2ND, OH , 13,977.0 ftKB - 14,311.0 ftKB, TRICAN , 100 MESH Bulk Sand 86654 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	5289.19				4,466.0	7,047.0	80	7,751.0	80	4.10					
HYBRID , 8/29/2013 20:01 , BONE SPRING 2ND, OH , 13,545.0 ftKB - 13,879.0 ftKB, TRICAN , 100 MESH Bulk Sand 89231 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6099.81				4,466.0	6,394.0	80	6,950.0	81	3.73					
HYBRID , 8/30/2013 06:30 , BONE SPRING 2ND, OH , 13,113.0 ftKB - 13,447.0 ftKB, TRICAN , 100 MESH Bulk Sand 86037 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6222.45				4,175.0	6,925.0	78	8,055.0	80	3.55					
HYBRID , 8/30/2013 10:30 , BONE SPRING 2ND, OH , 12,681.0 ftKB - 13,015.0 ftKB, TRICAN , 100 MESH Bulk Sand 93679 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6538.79				4,265.0	7,160.0	80	7,860.0	80	3.31					
HYBRID , 8/31/2013 06:30 , BONE SPRING 2ND, OH , 12,250.0 ftKB - 12,583.0 ftKB, TRICAN , 100 MESH Bulk Sand 80113 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6144.88				4,199.0	7,242.0	80	7,797.0	81	3.51					
HYBRID , 8/31/2013 13:01 , BONE SPRING 2ND, OH , 11,818.0 ftKB - 12,152.0 ftKB, TRICAN , 100 MESH Bulk Sand 85352 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6262.71				4,217.0	6,950.0	81	7,481.0	81	3.64					
HYBRID , 8/31/2013 18:42 , BONE SPRING 2ND, OH , 11,386.0 ftKB - 11,720.0 ftKB, TRICAN , 100 MESH Bulk Sand 90767 LB; CRC PREMIUM Resin															
Proppant De...	Total Clean Volu...	Pre Trt S/I Prs (psi)	Pst Trt S/I Prs (psi)	P Break (psi)	ISIP (psi)	Avg Treat Pressur...	Q Treat Avg (bbl/...	P Max (psi)	Q Treat Max (bbl/...	Conc Max...					
355,000.0	6142.57				4,469.0	6,920.0	81	7,187.0	81	3.28					