Submit 1 Copy To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
October 13, 2009

	WELL API NO. 30-025-38576
	5. Indicate Type of Lease STATE ☒ FEE ☐
	6. State Oil & Gas Lease No. V07530-0001
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well ☐ Gas Well ☐ Other Acid Gas Injection ☒	7. Lease Name or Unit Agreement Name Linam AGI
	8. Well Number #1
2. Name of Operator DCP Midstream LP	9. OGRID Number 36785
3. Address of Operator 370 17th Street, Suite 2500, Denver, CO 80202	10. Pool name or Wildcat AGI:Wolfcamp
4. Well Location Unit Letter K : 1980 feet from the South line and 1980 feet from the West line Section 30 Township 18S Range 37E NMPM County Lea	
	11. Elevation *(Show whether DR, RKB, RT, GR, etc.)* 3736 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
OTHER.		OTHER: ☒ Conduct MIT tests	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Based on the results of the workover of the Linam AGI #1 in May 2012, DCP and OCD-Hobbs have determined that a MIT should be conducted every six months until the well is repaired by adding a stacked packer to confirm that no communication exists between the well tubing and the annular space in the well (the annular space being inside the 7" casing) and that the portion of compromised casing above the current packer is maintaining its integrity.

The MIT was conducted on October 30, 2013. In order to conduct the MIT, the annular space pressure was adjusted to 560 psi by either adding or bleeding a small amount of corrosion inhibited diesel immediately before the test:

1. Initially the starting annular space pressure in 7" casing and tubing injection pressure was recorded and both were monitored during the test.
2. Bleed off or add annular fluid (corrosion inhibited diesel) was completed to bring observed annular space pressure to 0 psig.
3. Annular pressure was increased by introducing corrosion inhibited diesel to annulus to 560 psig.
4. The chart was placed on annular space and the annular space pressure was recorded for one 40 minutes.
5. Average tubing injection pressure was recorded during charting.
6. Bled off annular fluid ---TO ZERO PSI.

* DROP PRESSURE TO NORMAL OPER. PRESSURE DURING END OF TESTING

Geolex, Inc. and Pate Trucking/Hobbs will be conducting the test. met at the Linam AGI facility west of Hobbs at 8 am Wednesday 10/30/2013 and held a tailgate safety meeting upon arrival at the well location. The MIT was executed at 9:30 am.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE _____ TITLE: Consultant to DCP Midstream LP DATE: 10/30/2013

Type or print name Michael W. Selke E-mail address: mselke@geolex.com PHONE: 505-842-8000

For State Use Only

APPROVED BY: _____ TITLE Dist. Mgr DATE 10-30-2013

Conditions of Approval (if any):

OCT 30 2013


MIDNIGHT
NOON
6 PM
6 AM
Graphic Controls
9:35 am Start
DCP Midstream LP
LINAM AGI #1
API 30-025-38576
DATE 10/30/13
BR 2221
PRINTED IN U.S.A.
HIGH TEST
BLED TO ZERO PSI
540 PSI
Recorder #3219
1 HR CLOCK
1000 # SPRING
Calibrated 10/11/13
LOW END TEST
(STANDARD OPER PRESSURE)
560 PSI