Submit 3 Copies To Appropriate District Office HOBBS State of New Mexico Energy Minerals and Natural Resources	Form C-103 June 19, 2008
DISTRICT LINE BY, WHITE I AND WARRAND LINE BY, WHITE I AND THOUSE WARRAND	WELL API NO.
District II 1301 W. Grand Ave., Artesia, M822 0 7 2013 District III District III 1220 South St. Francis Dr.	30-025-25991 5. Indicate Type of Lease
L000 Rio Brazos Rd Aztec NM 8741 0	STATE FEE 6. State Oil & Gas Lease No.
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 87505	VB-1325
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Shetland SWD (SWD-1125-A)
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	8. Well Number 1
2. Name of Operator Mack Energy Corporation	9. OGRID Number 013837
3. Address of Operator	10. Pool Name or Wildcat
P.O. Box 960 Artesia, NM 88210 4. Well Location	SWD; Wolfcamp
Unit Letter K 1980 feet from the South line and	1980 feet from the West line
Section 18 Township 18S Range 35E	NMPM County Lea
11. Elevation (Show whether DR, RKB, RT, GR etc. 3964' GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIALWOR TEMPORARILY ABANDON CHANGE PLANS COMMENCE DR	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN	_
DOWNHOLE COMMINGLE	·
OTHER: OTHER:	Completion
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
10/16/2013 Perforated 10,521-10662' w/ 138 holes.	
10/17/2013 Set Pkr @ 10,627'. Acidized w/ 1500 gals 15% HCL. 10/21/2013 Acidized w/ 15,000 gals 20% Acid, 100 ball sealers and 2800# Rock Salt. Set comp. plug @ 10,350'. Perforated	
9,942.5-10,305' w/ 184 holes. Acidized w/ 20,000 gals 20% Acid, 30,000 gals 20# Linear Gel, 150 balls, 3600# Rock Salt.	
10/22/2013 Set Pkr @ 9890'. Perforated 9725-9839' w/ 90 holes. Acidized w/ 10,000 gals 20% acid, 15,000 gals 20# Linear gel.	
10/23/2013 Drilled out plugs. 10/25/2013 RIH w/ 296 jts. 2 7/8" J-55 6.5# @ 9656', 5 1/2" nickel plated arrow packer.	
[
Spud Date: Rig Release Date:	7/30/2013
I hereby certify that the information above is true slid complete to the best of my knowledge and belief.	
11/12	
SIGNATURE DATE 11. G. 13	
Type or print name Deana Weaver E-mail address: dweaver@mec.com PHONE: (575)748-1288	
For State Use Only	
APPROVED BY: Wash Whitaken TITLE Compliance	PHONE: (3/3)/48-1288 Wicer DATE 11-25-2013

