New Mexico Oil Conservation Division, District I 1625 N. French Drive Hobbs, NM 88240

	BUREAU OF LAND		Expires: March 31, 1993
	DONE TO OF EATE	FLAND MANAGEMENT	5. Lease Designation and Serial No. LC-NM2511
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals			6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation
1. Type of Weli Oil Gas Well X Well Other			8. Well Name and No.
2. Name of Operator			Meyer "B-28" A/C-2 No. 3
Doyle Hartman 3. Address and Telephone No. 500 N. Maio St. Midland TV 70701 (422) 694 4011			9. API Well No. 30-025-24877 10. Field and Pool, or Exploratory Area
500 N. Main St., Midland, TX 79701, (432) 684-4011 4. Location of Well (Footage, Şec., T., R., M., or Survey Description)			Eumont (Y-7R-Qn)
760' FNL & 1880' FEL (Unit C), Section 33, T-20-S, R-37-E, N.M.P.M.			11. County or Parish, State Lea, NM
12. CHECK APPI	ROPRIATE BOX(s) TO II	NDICATE NATURE OF NOTICE, REPORT, C	OR OTHER DATA
	TYPE OF SUBMISSION TYPE OF ACTION		
□ Notice of Inter		Abandonment	Change of Plans New Construction
Subsequent R	leport	☐ Recompletion ☐ Plugging Back	Non-Routine Fracturing
		Casing Repair	Water Shut-Off
Final Abandor	nment Notice	Altering Casing	Conversion to Injection
		X Other Plug and Abandon	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
directionally drilled, give subs	urface locations and measured and	ertinet details, and give pertinent dates, including estimated date of true vertical depths for all markders and zones pertinent to this erations, please refer to pages 2 thru 3 attached hereto,	and made a part hereof.
		7.7374 25 26 27.28	OSEI 81 TANCILLES
		Approved as to plugging of the wastlity under bond is retained was face restoration is completed.	d unta
14. I hereby certify that the forego	on is true and correct	Title Engineer	Date 10/12/2005
(This space for Federal or State	office use) DAVID R. GLASS	SETROLECAN ENGINEER	OCT 1 3 2005

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



Page 2 of 3 NMOCD Form C-103, dated October 12, 2005 Doyle Hartman Meyer "B-28" AC/2 No. 3 C-33-20S-37E API No. 30-025-24877

Details of Completed Plugging Operations

9-13-05 to 9-15-05:

Installed 5 1/2" x 2 7/8" O.D. tubinghead. Ran 2 7/8" O.D. work string equipped with stinger tool. Stung into retainer at 3530'.

Mixed and pumped 200 sx of API Class "C" cement containing 2% CaCl₂, 5 lb/sx Gilsonite, 0.25 lb/sx Flocele. Displaced cement with 18.5 bbls of water. Final displacement rate = 1 BPM. ISIP = 2931 psi. Pulled out of CICR. Dumped 2 bbls (84') of cement on top of CICR.

Raised bottom of tubing to 3466'. Circulated hole with salt-gel mud.

Raised bottom of 2 7/8" O.D. work string to 2739'. Set 30 sx API Class "C" cement plug from 2452' to 2739'. Raised tubing 35 jts. WOC 2.5 hrs. Tagged top of plug at 2452'.

Raised bottom 2 7/8" O.D. work string to 1526'. Spotted 38 sx API Class "C" cement plug from 1170' to 1526'.

Raised bottom of 2 7/8" O.D. work string to 470'. Spotted 47 sx API Class "C" cement plug from 0' to 470'. Pulled and laid down work string. Finished filling 5 1/2" O.D. casing with cement.

9-19-05

Installed dry-hole marker, cut off rig anchors, cleaned location. Well now P&A'd.

Page 3 of 3 BLM Form 3160-5 dated 10/12/2005 Doyle Hartman Meyer 'B-28' A/C-2 #3 C-33-20S-37E API No. 30-025-24877

Wellbore Schematic

Plugging and Abandonment Procedure
Meyer "B-28" A/C-2 No. 3
760' FNL & 1880' FEL (Unit C)
Section 33, T-20-S, R-37-E
Lea County, NM
Doyle Hartman

