

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

Revised August 1, 2011

HOBBS OCD
RECEIVED
JAN 23 2014

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-04056
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No. B-1431
7. Lease Name or Unit Agreement Name North Monument G/SA Unit Blk 9
8. Well Number 3
9. OGRID Number 873
10. Pool name or Wildcat Eunice Monument: G/SA
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3702' DF

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [X] Gas Well [] Other []
2. Name of Operator Apache Corporation
3. Address of Operator 303 Veterans Airpark Lane, Ste. 3000, Midland, Tx 79705
4. Well Location Unit Letter C 660 feet from the N line and 1980 feet from the W line
Section 25 Township 19S Range 36E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

PERIODIC NOTICE OF...
Approved for Plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page under forms! www.emnrd.state.nm.us/oecd

SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A [X]
CASING/CEMENT JOB []
OTHER: []

1. 1/6/14 Notify OCD of MIRU.
2. 1/7/14 RIH w/ 2-3/8 tbg tag CIBP @ 3815', pressure test casing to 1000 psi ok. Circulate well w/135 bbls MLF. Spot 30 x class "c" cmt @ 3815'.
3. 1/8/14 RIH tag TOC @ 3486', POH perf @ 2610' sqz 50 x class "c" cmt displace to 2350' SIP 1200 psi.
4. 1/9/14 RIH tag TOC @ 2285' POH perf @ 1330' sqz 50 x class "c" cmt displace to 1230' SIP 400 psi, woc 4 hrs. RIH tag TOC @ 1213', POH perf @ 250' sqz 160 x class "c" cmt to surface. Cmt was circulated behind 6-5/8 casing and 8-5/8 casing. Rig down all P&A equipment. Cut off wellhead, anchors and clean location. Install dryhole marker.

Spud Date: [] Rig Release Date: []

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Agent DATE 1/9/14
Type or print name Jimmy Bagley E-mail address: sunsetwellservice@yahoo.com PHONE: 432-561-8600

APPROVED BY: [Signature] TITLE Compliance Officer DATE 01-27-2014 PM

Authorized by Apache Foreman - Susan Rudo

JAN 27 2014