

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

RECEIVED JAN 28 2014 SUNDRIY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-35838
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator CIMAREX ENERGY CO. OF COLORADO		6. State Oil & Gas Lease No.
3. Address of Operator 600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701		7. Lease Name or Unit Agreement Name SHELLEY 35 STATE
4. Well Location Unit Letter G: 2310 feet from the NORTH line and 2310 feet from the EAST line Section 35 Township 19S Range 37E NMPM LEA County		8. Well Number 004
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,609' - KB		9. OGRID Number 162683
		10. Pool name or Wildcat MONUMENT; TUBB

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 6650' 6650 - 6490'
- 1) SET 4-1/2" CIBP @ 6,550'; PUMP 25 SXS. CMT. @ 6,550'-6,390'.
 - 2) SET 4-1/2" CIBP @ 5,200'; PUMP 25 SXS. CMT. @ 5,200'-5,050'; CIRC. WELL W/ PXA MUD.
 - 3) PUMP 40 SXS. CMT. @ 4,010'-3,720' (T/GRBG., DV TOOL, T/QN.); WOC X TAG CMT. PLUG.
 - 4) PUMP 25 SXS. CMT. @ 2,812'-2,692' (T/YATES, B/SALT); WOC X TAG CMT. PLUG.
 - 5) PUMP 25 SXS. CMT. @ 1,486'-1,350' (T/SALT, 8-5/8" CSG.SHOE); WOC X TAG CMT. PLUG.
 - 6) MIX X CIRC. TO SURF. 15 SXS. CMT. @ 100'-3'.
 - 7) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD ON STEEL PLATE TO CSGS. X INSTALL DRY HOLE MARKER.

DURING THIS PROCEDURE WE PLAN TO USE THE CLOSED-LOOP SYSTEM WITH A STEEL TANK AND HAUL CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RUNLE 19.15.17.

Spud Date:

Rig Release Date:

RECEIVED

JAN 17 2014

NMOCD ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

David A. Eyler

TITLE:

AGENT

DATE: 01/15/14

Type or print name: DAVID A. EYLER

E-mail address: DEYLER@MILAGRO-RES.COM

PHONE: 432.687.3033

For State Use Only

APPROVED BY:

Maley Brown

TITLE

Compliance Officer

DATE

1/29/2014

Conditions of Approval (if any)

OIL CONSERVATION DIVISION - Hobbs office **Must Be Notified**
24 hours prior to the beginning of Plugging Operations.

JAN 29 2014



KB: 17' above GL

Cimarex Energy Co. of Colorado

Shelley 35 State 4 (Monument Field)

2310' FNL & 2310' FEL

Sec. 35, T-19S, R-37E, Lea Co., NM

M. Ketter

12/20/2013

API #30-025-35838

8-5/8", 24# J-55 csg @ 1410'
cmt'd w/ 640 sx, circ'd cmt

Quantity	Description	Length	Setting Depth
	KB	11.00	11.00
210	2-3/8" J-55 8rd EUE	6633.74	6644.74
1	2-3/8" X 4-1/2" TAC	3.20	6647.94
5	2-3/8" J-55 8rd EUE	160.65	6808.59
1	2-3/8" Std SN	1.10	6809.69
1	2-3/8" Slotted SN	1.10	6810.79
1	2-3/8" X 2-7/8" MA	30.18	6840.97

DV Tool @ 3,855'

Quantity	Description	Length
1	1-1/2" PR	28
2	Pony Sub	12
86	7/8" Rods	2150
177	3/4" Rod	4425
6	1" K-Bars	150
1	2" X 1-1/4" X 16' RXBC Pump w/ HVR	16
1	1" X 20 GA	20
	TOTAL LENGTH	6799

Perfs:

5253'-58' & 5363'-74'

Glorieta Perfs:

5352'-58', 63'-74' & 5392'-5403'

Paddock Perfs:

5424'-35' & 5449'-62'

Drinkard Perfs:

6705'-08', 6764'-67 & 6804'-12'

Perfs:

6823'-28' & 6836'-42'

Lower Drinkard Perfs:

7010-7025'

4-1/2", 11.6# N-80 csg @ 7180'

cmt w/ 1,325 sxs; circ'd cmt

Sqz'd Perfs 5352'-56403' w/100 sxs cmt

Sqz'd Perfs 5424'-5469' w/200 sxs cmt

CIBP @ 6985' Topped w/15' Cmt

PBTD: 6970'

TD : 7180'

TD : 7180'