

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

JAN 28 2014

RECEIVED

WELL API NO. 30-025-38624
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name PENNZOIL B 36 STATE
8. Well Number 007
9. OGRID Number 162683
10. Pool name or Wildcat APACHE RIDGE; BONE SPRING

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐
2. Name of Operator CIMAREX ENERGY CO. OF COLORADO
3. Address of Operator 600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701
4. Well Location Unit Letter: A : 930 feet from the NORTH line and 660 feet from the EAST line Section 36 Township 19S Range 33E NMPM LEA County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3620' - GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1) SET 5-1/2" CIBP @ 9,400'; PUMP 25 SXS. CMT. @ 9,400'-9,210'; CIRC. WELL W/ PXA MUD.
- 2) PUMP 25 SXS. CMT. @ 8,335'-8,155' (T/B.S.); WOC X TAG CMT. PLUG.
- 3) PUMP 25 SXS. CMT. @ 5,496'-5346' (T/DLWR., 9-5/8" CSG.SHOE); WOC X TAG CMT. PLUG.
- 4) PUMP 25 SXS. CMT. @ 3,000'-2,870' (MID-PLUG).
- 5) PERF. X ATTEMPT TO SQZ. 55 SXS. CMT. @ 1,458'-1,348' (13-3/8" CSG.SHOE, T/ ANHY.); WOC X TAG CMT. PLUG.
- 6) PERF. X CIRC. TO SURF., FILLING ALL ANNULI, 25 SXS. CMT. @ 63'-3'.
- 7) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD ON STEEL PLATE TO CSGS. X INSTALL DRY HOLE MARKER.

DURING THIS PROCEDURE WE WILL USE THE CLOSED-LOOP SYSTEM WITH A STEEL TANK AND HAUL CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RULE 19.15.17.

Spud Date:

Rig Release Date:

OIL CONSERVATION DIVISION - Hobbs office **Must Be Notified**
24 hours prior to the beginning of Plugging Operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

David A. Eyer

TITLE: AGENT

DATE: 01/16/14

Type or print name: DAVID A. EYLER

E-mail address: DEYLER@MILAGRO-RES.COM

PHONE: 432.687.3033

For State Use Only

APPROVED BY:

Mary Brown

TITLE: Compliance Officer

DATE: 1/28/2014

Conditions of Approval (if any):

JAN 29 2014

CIMAREX**Cimarex Energy Co. of Colorado****Pennzoil "B-36" State #7**

API 30-025-38624

930' FNL & 660' FEL, Sec 36, T19S R33E

Lea County, NM

GL:3617' KB: 3642'

CIMAREX Property #309617-174

13 3/8" 48# 4-40 csg @ 1403'

Cmt w/1050 sx, circ 189 sx to surface

TOC 1600 by CBL

17 1/2" hole to 1403'

9 5/8" 40 & 53.5# P-110 BT&C @ 5421'

Cmt w/400 sx, TOC = 3007'

Top out w/2720 sx Premium Plus

*1" CMT TO
SURFACE.*

12 1/4" hole to 5421'

Quantity	Description	Length
1	26 X 1-1/4" PR	26.00
3	4.6.8 Pony Rods	18.00
126	7/8" Grade 97 Rods	3150.00
236	3/4" Grade 97 Rods	5900
1	RHR Tool	1.00
1	2' X 7/8" Guided Lift Sub	2.00
1	25-125-24' RHBM	24.00
TOTAL LENGTH		9121.00

Quantity	Description	Length	Setting Depth
287	2 7/8" 6.5# L-80 Ultra FX Tbg	9410.00	9410.00
1	2 7/8" TAC	2.80	9412.80
4	2-7/8" 6.5# L-80 8rd EUE Tbg	120.25	9533.05
1	2-7/8" Sub	8.20	9541.25
1	2 7/8" Mechanical SN	1.10	9542.35
1	Echometer GS	4.00	9546.35
1	2-7/8" 6.5# L-80 8rd EUE Tbg	32.79	9579.14

AIRSTRIP DOLOMITE & BONE SPRING PERFS:

9430 - 9582' 4 JSPF, 296 holes (3/7/08)

CIBP @ 9592 (3/7/08)**BS BASAL SAND PERFS:**

9596 - 9616' 3 JSPF, 120 holes (2/28/08)

5 1/2" 17# P-110 csg @ 10,400'

Cmt w/750 sx Interfill "H"

FB 650 sx PBM Super "H"

TOC @ 1600' by CBL ✓

PBTD: 9592'

TD: 10,400'

