

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTOCD: Hobbs  
HOBBS OCD

## APPLICATION FOR PERMIT TO DRILL OR REENTER

FEB 05 2014

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		7. If Unit or CA Agreement, Name and No. N/A
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		8. Lease Name and Well No. Ruby Federal 27
2. Name of Operator ConocoPhillips Company		9. API Well No. 30-025- 4/652
3a. Address 600 N. Dairy Ashford Rd., Off P10-4-4054 Houston, TX 77079	3b. Phone No. (include area code) (281)206-5281	10. Field and Pool, or Exploratory Maljamar; Yeso West
4. Location of Well (Report location clearly and in accordance with any State requirements.)* At surface 1480' FNL and 2380' FEL; UL G, Sec. 17, T17S, R32E (G) At proposed prod. zone 2425' FNL and 2230' FWL; UL F, Sec. 17, T17S, R32E (F)		11. Sec., T. R. M. or Blk. and Survey or Area Sec. 17, T17S, R32E
14. Distance in miles and direction from nearest town or post office* Approximately 3 miles south of Maljamar, New Mexico		12. County or Parish Lea County
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) About 215' at TD		13. State NM
16. No. of acres in lease 1601.96		17. Spacing Unit dedicated to this well 40
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 130'		20. BLM/BIA Bond No. on file ES0085
19. Proposed Depth 7030' TVD/7176' MD		21. Elevations (Show whether DF, KDB, RT, GL, etc.) 4011' GL
22. Approximate date work will start* 03/07/2014		23. Estimated duration 8 days

## 24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification   |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM.             |

25. Signature <i>Susan B. Maunder</i>	Name (Printed/Typed) Susan B. Maunder	Date 10/29/13
Title Senior Regulatory Specialist		
Approved by (Signature) <i>/s/ STEPHEN J. CAFFEY</i>	Name (Printed/Typed) STEPHEN J. CAFFEY	Date FEB - 4 2014
Title FIELD MANAGER		
Office CARLSBAD FIELD OFFICE		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)

Roswell Controlled Water Basin

SEE ATTACHED FOR  
CONDITIONS OF APPROVALApproval Subject to General Requirements  
& Special Stipulations Attached

FEB 10 2014

dm

Drilling Plan  
ConocoPhillips Company  
Maljamar; Grayburg-San Andres, Yeso (west)

Ruby Federal #27

Lea County, New Mexico

**1. Estimated tops of geological markers and estimated depths to water, oil, or gas formations:**

The datum for these depths is RKB (which is 13' above Ground Level).

Formations	Top Depth FT TVD	Top Depths FT MD	Contents
Quaternary	Surface	Surface	Fresh Water
Rustler	760	760	Anhydrite
Salado (top of salt)	938	938	Salt
Grayburg	3487	1960	Gas, Oil and Water
San Andres	3851	3523	Gas, Oil and Water
Glorieta	5340	3905	Gas, Oil and Water
Paddock	5424	5459	Gas, Oil and Water
Blinberry	6165	5545	Gas, Oil and Water
Tubb	6780	6297	Gas, Oil and Water
Deepest estimated perforation	6780	6297	Deepest estimated perf. is ~ Top of Tubb
Total Depth (maximum)	7030	7176	200' below deepest estimated perforation

All of the water bearing formations identified above will be protected by setting of the 8-5/8" surface casing 25' – 70' into the Rustler formation and circulating of cement from casing shoe to surface in accordance with the provisions of Onshore Oil and Gas Order No. 2 and New Mexico Oil Conservation Division Title 19.

The targeted oil and gas bearing formations identified above will be protected by setting of the 5-1/2" production casing 10' off bottom of TD and circulating of cement from casing shoe to surface in accordance with the provisions of Onshore Oil and Gas Order No. 2 and New Mexico Oil Conservation Division Title 19.

## 2. Proposed casing program:

*See COA*

Type	Hole Size	Interval MD RKB (ft)		OD	Wt	Gr	Conn	MIY	Col	Jt Str	Safety Factors Calculated per ConocoPhillips Corporate Criteria		
		From	To								Burst DF	Collapse DF	Jt Str DF (Tension) Dry/Buoyant
Cond	20	0	40' - 85' (30' - 75' BGL)	16	0.5" wall	B	Line Pipe	N/A	N/A	N/A	NA	NA	NA
Alt. Cond	20	0	40' - 85' (30' - 75' BGL)	13-3/8	48#	H-40	PE	1730	740	N/A	NA	NA	NA
Surf	12-1/4	0	<del>785' - 830'</del> <i>822'</i>	8-5/8	24#	J-55	STC	2950	1370	244	1.58	3.71	3.62
Prod	7-7/8	0	7121' - 7166'	5-1/2	17#	L-80	LTC	7740	6290	338	2.08	2.48	1.96

The casing will be suitable for H<sub>2</sub>S Service. All casing will be new.

The surface and production casing will be set approximately 10' off bottom and we will drill the hole with a 45' range uncertainty for casing set depth to fit the casing string so that the cementing head is positioned at the floor for the cement job.

The production casing will be set 155' to 200' below the deepest estimated perforation to provide rathole for the pumping completion and for the logs to get deep enough to log the interval of interest.

### Casing Safety Factors - BLM Criteria:

Type	Depth	Wt	MIY	Col	Jt Str	Drill Fluid	Burst	Collapse	Tensile-Dry	Tens-Bouy
Surface Casing	830	24	2950	1370	244000	8.5	8.04	3.73	12.2	14.1
Production Casing	7166	17	7740	6290	338000	10	2.08	1.69	2.77	3.27

### Casing Safety Factors - Additional ConocoPhillips Criteria:

ConocoPhillips casing design policy establishes Corporate Minimum Design Factors (see table below) and requires that service life load cases be considered and provided for in the casing design.

ConocoPhillips Corporate Criteria for Minimum Design Factors

	Burst	Collapse	Axial
Casing Design Factors	1.15	1.05	1.4

Type	Depth	Wt	MIY	Col	Jt Str	Pipe Yield MW	Burst	Col	Ten
Conductor	85	65	35000	-	-	432966	-	-	-
Surface Casing (8-5/8" 24# J-55 STC)	830	24	2950	1370	244000	381000	8.5	1.58	3.71
Production Casing (5-1/2" 17# L-80 LTC)	7166	17	7740	6290	338000	397000	10	2.08	2.48

#### Burst - ConocoPhillips Required Load Cases

The maximum internal (burst) load on the Surface Casing occurs when the surface casing is tested to 1500 psi (as per BLM Onshore Order 2 - II Requirements).

The maximum internal (burst) load on the Production Casing occurs during the fracture stimulation where the maximum allowable working pressure

(MAWP) is the pressure that would fit ConocoPhillips Corporate Criteria for Minimum Factors.

Surface Casing Test Pressure =	1500 psi	Predicted Pore Pressure at TD (PPTD) =	8.55 ppg
Surface Rated Working Pressure (ROPE) =	3000 psi	Predicted Frac Gradient at Shoe (CSFG) =	19.23 ppg
Field SW =	10 ppg		

Surface Casing Burst Safety Factor = API Burst Rating / Maximum Predicted Surface Pressure (MPSP) OR Maximum Allowable Surface Pressure (MASP)

Production Casing MAWP for the Fracture Stimulation = API Burst Rating / Corporate Minimum Burst Design Factor

#### Surface Casing Burst Safety Factor:

Case #1. MPSP (MWYd next section) =	830	x	0.052	x	10	=	432		
Case #2. MPSP (Field SW @ Bullhead casing + 200 psi) =	830	x	0.052	x	19.23	=	432	+	200
Case #3. MPSP (Kick Vol @ next section TD) =	7166	x	0.052	x	8.55	=	633.6	-	367
Case #4. MPSP (PPTD - GG) =	7166	x	0.052	x	8.55	=	716.6	=	2469
Case #3 & #4 Limited to MPSP (CSFG + 0.2 ppg) =	830	x	0.052	x	( 19.23 + 0.2 )	=	839		
MASP (MWYd + Test Pressure) =	830	x	0.052	x	8.5	+	1500	=	1867
Burst Safety Factor (Max. MPSP or MASP) =	2950	/	1867	=	1.58				

#### Production Casing Burst Safety Factor:

Case #1. MPSP (MWYd TD) =	7166	x	0.052	x	10	=	3726.32		
Case #4. MPSP (PPTD - GG) =	7166	x	0.052	x	8.55	=	716.6	=	2469
Burst Safety Factor (Max. MPSP) =	7740	/	3726	=	2.08				
MAWP for the Fracture Stimulation (Corporate Criteria) =	7740	/	1.15	=	6730				

#### Collapse - ConocoPhillips Required Load Cases

The maximum collapse load on the Surface Casing occurs when cementing to surface, 1/3 evacuation to the next casing setting depth, or deepest depth of exposure (full evacuation).

The maximum collapse load on the Production Casing occurs when cementing to surface, or 1/3 evacuation to the deepest depth of exposure; and

therefore, the external pressure profile for the evacuation cases should be equal to the pore pressure of the horizon on the outside of the casing which we assumed to be PPTD.

Surface Casing Collapse Safety Factor = API Collapse Rating / Full Evacuation OR Cement Displacement during Cementing to Surface

Production Casing Collapse Safety Factor = API Collapse Rating / Maximum Predicted Surface Pressure OR Cement Displacement during Cementing to Surface

Cement Displacement Fluid (FW) =	8.34 ppg	Top of Cement =	Cement to Surface
Surface Cement Lead =	13.6 ppg	Prod Cement Lead =	11.8 ppg
Surface Cement Tail =	14.8 ppg	Prod Cement Tail =	16.4 ppg
Top of Surface Tail Cement =	300 ft	Top of Prod Tail Cement =	5200 ft

#### Surface Casing Collapse Safety Factor:

Full Evacuation Diff Pressure =	830	x	0.052	x	8.55	=	369		
Cementing Diff Lit Pressure =	( ( 530 x 0.052 x 13.6 ) + ( 300 x 0.052 x 14.8 ) - 360 )	=	246						
Collapse Safety Factor =	1370	/	369	=	3.71				

#### Production Casing Collapse Safety Factor:

1/3 Evacuation Diff Pressure =	( ( 7166 x 0.052 x 8.55 ) - ( 7166 / 3 x 0.052 x 8.34 ) )	=	2150						
Cementing Diff Lit Pressure =	( ( 1966 x 0.052 x 11.8 ) + ( 5200 x 0.052 x 16.4 ) - 3108 )	=	2533						
Collapse Safety Factor =	6290	/	2533	=	2.48				

#### Tensile Strength - ConocoPhillips Required Load Cases

The maximum axial (tension) load occurs if casing were to get stuck and pulled on to try to get it unstuck.

Maximum Allowable Axial Load for Pipe Yield = API Pipe Yield Strength Rating / Corporate Minimum Axial Design Factor

Maximum Allowable Axial Load for Joint = API Joint Strength Rating / Corporate Minimum Axial Design Factor

Maximum Allowable Hook Load (Limited to 75% of Rig Max Load) = Maximum Allowable Axial Load

Maximum Allowable Overpull Margin = Maximum Allowable Hook Load - Buoyant Wt of the String

Tensile Safety Factor = API Pipe Yield OR API Joint Strength OR Rig Max Load Rating / ( Buoyant Wt of String + Maximum Overpull Required )

Rig Max Load (300,000 lbs) x 75% =	225000 lbs
Minimum Overpull Required =	50000 lbs

#### Surface Casing Tensile Strength Safety Factor:

Air Wt =	19920								
Buoyant Wt =	19920	x	0.870	=	17335				
Max. Allowable Axial Load (Pipe Yield) =	381000	/	1.40	=	272143				
Max. Allowable Axial Load (Joint) =	244000	/	1.40	=	174286				
Max. Allowable Hook Load (Limited to 75% of Rig Max Load) =	174286								
Max. Allowable Overpull Margin =	174286 - ( 19920 x 0.870 )	=	156951						
Tensile Safety Factor =	244000	/	( 17335 + 50000 )	=	3.62				

#### Production Casing Tensile Strength Safety Factor:

Air Wt =	121822								
Buoyant Wt =	121822	x	0.847	=	103223				
Max. Allowable Axial Load (Pipe Yield) =	397000	/	1.40	=	283571				
Max. Allowable Axial Load (Joint) =	338000	/	1.40	=	241429				
Max. Allowable Hook Load (Limited to 75% of Rig Max Load) =	225000								
Max. Allowable Overpull Margin =	225000 - ( 121822 x 0.847 )	=	121777						
Tensile Safety Factor =	300000	/	( 103223 + 50000 )	=	1.96				

#### Compression Strength - ConocoPhillips Required Load Cases

The maximum axial (compression) load for the well is where the surface casing is landed on the conductor

with a support of a plate or landing ring. The surface casing is also calculated to bear 60% of the load

but not exceed. Any other axial loads such as a snubbing unit or other would need to be added to the load.

Compression Safety Factor = API Axial Joint Strength Rating OR API Axial Pipe Yield Rating / Maximum Predicted Load

Wellhead Load = 3000 lbs

#### Conductor & Surface Compression Safety Factor

Surf Casing Wt (Buoyant) =	( 19920 x 0.870 )	=	17335						
Prod Casing Wt (Buoyant) =	( 121822 x 0.847 )	=	103223						
Tubing Wt (Air Wt) =	7166 x 6.5	=	46579						
Tubing Fluid Wt =	7166 x 0.052 x 6.55	x	0.7854 x 2.441	*2 =	11422				
Load on Conductor =	3000 + 17335 + 46579 + 11422	=	181559						
Conductor Compression Safety Factor =	432966	/	181559	=	2.38				
Load on Surface Casing =	181559 x 60%	=	108936						
Surface Casing Compression Safety Factor =	244000	/	108936	=	2.24				

### 3. Proposed cementing program:

#### 16" or 13-3/8" Conductor:

Cement to surface with rathole mix, ready mix or Class C Neat cement.  
(Note: The gravel used in the cement is not to exceed 3/8" diameter)  
TOC at surface.

#### 8-5/8" Surface Casing Cementing Program:

The intention for the cementing program for the Surface Casing is to:

- Place the Tail Slurry from the casing shoe to 300' above the casing shoe,
- Bring the Lead Slurry to surface.

Spacer: 20 bbls Fresh Water

Slurry		Intervals Ft MD		Weight ppg	Sx	Vol Cuft	Additives	Yield ft <sup>3</sup> /sx
Lead	Class C	Surface	485' – 530'	13.6	300	510	2% Extender 2% CaCl <sub>2</sub> 0.125 lb/sx LCM if needed 0.2% Defoamer  Excess = 75% based on gauge hole volume	1.70
Tail	Class C	485' – 530'	785' – 830'	14.8	200	268	1% CaCl <sub>2</sub>  Excess = 100% based on gauge hole volume	1.34

Displacement: Fresh Water.

**Note: In accordance with the Pecos District Conditions of Approval, we will Wait on Cement (WOC) for a period of not less than 18 hrs after placement or until at least 500 psi compressive strength has been reached in both the Lead Slurry and Tail Slurry cements on the Surface Casing, whichever is greater.**

#### 5-1/2" Production Casing & Cementing Program:

The intention for the cementing program for the Production Casing is to:

- Place the Tail Slurry from the casing shoe to a point approximately 200' above the top of the Paddock,
- Bring the Lead Slurry to surface.

Spacer: 20 bbls Fresh Water

Slurry		Intervals Ft MD		Weight ppg	Sx	Vol Cuft	Additives	Yield ft <sup>3</sup> /sx
Lead	50:50 Poz/C	Surface	5200'	11.8	700	1820	10% Bentonite 5% Salt 0.2%-0.4% Fluid loss additive 0.125 lb/sx LCM if needed Excess = 220% or more if needed based on gauge hole volume	2.6
Tail	Class H	5200'	7121' – 7166'	16.4	400	428	0.2% Fluid loss additive 0.3% Dispersant 0.15% Retarder 0.2% Antifoam  Excess = 100% or more if needed based on gauge hole volume	1.07

Displacement: Fresh Water with approximately 250 ppm glutaraldehyde biocide.

#### Proposal for Option to Adjust Production Casing Cement Volumes:

The production casing cement volume presented above are estimates based on gauge 7-7/8" hole. We will adjust these volumes based on the caliper log data for each well and our trends for amount of cement returns to surface. Also, if no caliper log is available for any particular well, we would propose an option to possibly increase the production casing cement volume to account for any uncertainty in regard to the hole volume.

#### **4. Pressure Control Equipment:**

A 11" 3M system will be installed, used, maintained, and tested accordingly as described in Onshore Oil and Gas Order No. 2.

Our BOP equipment will be:

- o Rotating Head
- o Annular BOP, 11" 3M
- o Blind Ram, 11" 3M
- o Pipe Ram, 11" 3M

After nipping up, and every 30 days thereafter or whenever any seal subject to test pressure is broken followed by related repairs, blowout preventors will be pressure tested. BOP will be inspected and operated at least daily to insure good working order. All pressure and operating tests will be done by an independent service company and recorded on the daily drilling reports. BOP will be tested using a test plug to isolate BOP stack from casing. BOP test will include a low pressure test from 250 to 300 psi for a minimum of 10 minutes or until requirements of test are met, whichever is longer. Ram type preventers and associated equipment will be tested to the approved stack working pressure of 3000 psi isolated by test plug. Annular type preventers will be tested to 50 percent of rated working pressure, and therefore will be tested to 1500 psi. Pressure will be held for at least 10 minutes or until provisions of test are met, whichever is longer. Valve on casing head below test plug will be open during testing of BOP stack. BOP will comply with all provisions of Onshore Oil and Gas Order No. 2 as specified. **See Attached BOPE Schematic.** A variance is respectfully requested to allow for the use of flexible hose. The variance request is included as a separate enclosure with attachments.

#### **5. Proposed Mud System:**

The mud systems that are proposed for use are as follows:

DEPTH	TYPE	Density ppg	FV sec/qt	API Fluid Loss cc/30 min	pH	Vol bbl
0 – Surface Casing Point	Fresh Water or Fresh Water Native Mud in Steel Pits	8.5 – 9.0	28 – 40	N.C.	N.C.	120 – 160
Surface Casing Point to TD	Brine (Saturated NaCl <sub>2</sub> ) in Steel Pits	10	29	N.C.	10 – 11	500 – 1000
Conversion to Mud at TD	Brine Based Mud (NaCl <sub>2</sub> ) in Steel Pits	10	33 – 40	5 – 10	10 – 11	0 – 750

Gas detection equipment and pit level flow monitoring equipment will be on location. A flow paddle will be installed in the flow line to monitor relative amount of mud flowing in the non-pressurized return line. Mud probes will be installed in the individual tanks to monitor pit volumes of the drilling fluid with a pit volume totalizer. Gas detecting equipment and H<sub>2</sub>S monitor alarm will be installed in the mud return system and will be monitored. A mud gas separator will be installed and operable before drilling out from the Surface Casing. The gases shall be piped into the flare system. Drilling mud containing H<sub>2</sub>S shall be degassed in accordance with API RP-49, item 5.14.

In the event that the well is flowing from a waterflow, then we would discharge excess drilling fluids from the steel mud pits through a fas-line into steel frac tanks at an offset location for containment. Depending on the rate of waterflow, excess fluids will be hauled to an approved disposal facility, or if in suitable condition, may be reused on the next well.

No reserve pit will be built.

**Proposal for Option to Not Mud Up at TD:**

FW, Brine, and Mud volume presented above are estimates based on gauge 12-1/4" or 7-7/8" holes. We will adjust these volume based on hole conditions. We do not plan to keep any weighting material at the wellsite. Also, we propose an option to not mud up leaving only brine in the hole if we have good hole stability.

**6. Logging, Coring, and Testing Program:**

- a. No drill stem tests will be done
- b. Remote gas monitoring planned for the production hole section (optional).
- c. No whole cores are planned
- d. The open hole electrical logging program is planned to be as follows:
  - Total Depth to 2500': Resistivity, Density, and Gamma Ray
  - Total Depth to surface Casing Shoe: Caliper
  - Total Depth to surface, Gamma Ray and Neutron
  - Formation pressure data (XPT) on electric line if needed (optional)
  - Rotary Sidewall Cores on electric line if needed (optional)
  - BHC or Dipole Sonic if needed (optional)
  - Spectral Gamma Ray if needed (optional)

**7. Abnormal Pressures and Temperatures:**

- No abnormal pressures are expected to be encountered.
  - Loss of circulation is a possibility in the horizons below the Top of Grayburg. We expect that normal Loss of Circulation Material will be successful in healing any such loss of circulation events.
    - The bottom hole pressure is expected to be 8.55 ppg gradient.
    - The expected Bottom Hole Temperature is 115 degrees F.
- Self  
ESA* • The estimated H<sub>2</sub>S concentrations and ROE calculations for the gas in the zones to be penetrated are presented in the table below for the various producing horizons in this area:

FORMATION / ZONE	H2S (PPM)	Gas Rate (MCFD)	ROE 100 PPM	ROE 500 PPM
Grayburg / San Andres (from MCA)	14000	38	59	27
Yeso Group	400	433	34	15

ConocoPhillips will comply with the provisions of Oil and Gas Order # 6, Hydrogen Sulfide Operations. Also, ConocoPhillips will provide an H<sub>2</sub>S Contingency Plan (please see copy attached) and will keep this plan updated and posted at the wellsite during the drilling operation.

**8. Anticipated starting date and duration of operations:**

Well pad and road constructions will begin as soon as all agency approvals are obtained. Anticipated date to drill this well as early as 2014 after receiving approval of the APD.

## **Attachments:**

- Attachment # 1 ..... BOP and Choke Manifold Schematic – 3M System
- Attachment # 2 ..... Diagram of Choke Manifold Equipment

## **Contact Information:**

Proposed 28 October 2013 by:  
James Chen  
Drilling Engineer, ConocoPhillips Company  
Phone (832) 486-2184  
Cell (832) 768-1647



# **ConocoPhillips MCBU**

**Buckeye**

**Ruby Federal**

**Ruby Federal 27**

**Ruby Federal 27**

**Plan: Slant Plan**

## **Standard Planning Report - Geographic**

**30 September, 2013**

# ConocoPhillips

## Planning Report - Geographic

<b>Database:</b>	EDM Central Planning	<b>Local Co-ordinate Reference:</b>	Well Ruby Federal 27
<b>Company:</b>	ConocoPhillips MCBU	<b>TVD Reference:</b>	RKB @ 4024.0usft (PD 822)
<b>Project:</b>	Buckeye	<b>MD Reference:</b>	RKB @ 4024.0usft (PD 822)
<b>Site:</b>	Ruby Federal	<b>North Reference:</b>	Grid
<b>Well:</b>	Ruby Federal 27	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Ruby Federal 27		
<b>Design:</b>	Slant Plan		

<b>Project</b>	Buckeye, Lea County, NM		
<b>Map System:</b>	US State Plane 1927 (Exact solution)	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	NAD 1927 (NADCON CONUS)		
<b>Map Zone:</b>	New Mexico East 3001		Using geodetic scale factor

<b>Site</b>	Ruby Federal, New Mexico, Southeast		
<b>Site Position:</b>		<b>Northing:</b>	666,097.48 usft
<b>From:</b>	Lat/Long	<b>Easting:</b>	666,763.63 usft
<b>Position Uncertainty:</b>	3.5 usft	<b>Slot Radius:</b>	8 "
		<b>Latitude:</b>	32° 49' 48.040 N
		<b>Longitude:</b>	103° 47' 25.559 W
		<b>Grid Convergence:</b>	0.29 °

<b>Well</b>	Ruby Federal 27, Deviated Well		
<b>Well Position</b>	+N/-S	0.0 usft	<b>Northing:</b> 668,910.92 usft
	+E/-W	0.0 usft	<b>Easting:</b> 667,714.91 usft
<b>Position Uncertainty</b>	0.0 usft	<b>Wellhead Elevation:</b>	<b>Latitude:</b> 32° 50' 15.830 N
			<b>Longitude:</b> 103° 47' 14.240 W
			<b>Ground Level:</b> 4,011.0 usft

<b>Wellbore</b>	Ruby Federal 27				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination</b>	<b>Dip Angle</b>	<b>Field Strength</b>
			(°)	(°)	(nT)
	BGGM2012	8/6/2013	7.57	60.60	48,715

<b>Design</b>	Slant Plan			
<b>Audit Notes:</b>				
<b>Version:</b>	1	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b> 0.0
<b>Vertical Section:</b>	<b>Depth From (TVD)</b>	<b>+N/-S</b>	<b>+E/-W</b>	<b>Direction</b>
	(usft)	(usft)	(usft)	(°)
	0.0	0.0	0.0	214.82

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,960.0	0.00	0.00	1,960.0	0.0	0.0	0.00	0.00	0.00	0.00	
3,121.5	17.42	214.82	3,103.7	-143.9	-100.1	1.50	1.50	0.00	214.82	
5,049.9	17.42	214.82	4,943.6	-617.9	-429.8	0.00	0.00	0.00	0.00	
5,544.7	10.00	214.82	5,424.0	-714.1	-496.7	1.50	-1.50	0.00	180.00	Ruby Federal 27 (Plat
7,175.5	10.00	214.82	7,030.0	-946.6	-658.4	0.00	0.00	0.00	0.00	

# ConocoPhillips

## Planning Report - Geographic

**Database:** EDM Central Planning  
**Company:** ConocoPhillips MCBU  
**Project:** Buckeye  
**Site:** Ruby Federal  
**Well:** Ruby Federal 27  
**Wellbore:** Ruby Federal 27  
**Design:** Slant Plan

**Local Co-ordinate Reference:** Well Ruby Federal 27  
**TVD Reference:** RKB @ 4024.0usft (PD 822)  
**MD Reference:** RKB @ 4024.0usft (PD 822)  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature

### Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.0	0.00	0.00	0.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
85.0	0.00	0.00	85.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
<b>Conductor</b>									
100.0	0.00	0.00	100.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
200.0	0.00	0.00	200.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
300.0	0.00	0.00	300.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
400.0	0.00	0.00	400.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
500.0	0.00	0.00	500.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
600.0	0.00	0.00	600.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
700.0	0.00	0.00	700.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
760.0	0.00	0.00	760.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
<b>Rustler</b>									
800.0	0.00	0.00	800.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
830.0	0.00	0.00	830.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
<b>Surface</b>									
900.0	0.00	0.00	900.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
938.0	0.00	0.00	938.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
<b>Salado</b>									
1,000.0	0.00	0.00	1,000.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,100.0	0.00	0.00	1,100.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,200.0	0.00	0.00	1,200.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,300.0	0.00	0.00	1,300.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,400.0	0.00	0.00	1,400.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,500.0	0.00	0.00	1,500.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,600.0	0.00	0.00	1,600.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,700.0	0.00	0.00	1,700.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,800.0	0.00	0.00	1,800.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,900.0	0.00	0.00	1,900.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
1,960.0	0.00	0.00	1,960.0	0.0	0.0	668,910.92	667,714.91	32° 50' 15.830 N	103° 47' 14.240 W
<b>Tansill</b>									
2,000.0	0.60	214.82	2,000.0	-0.2	-0.1	668,910.75	667,714.79	32° 50' 15.828 N	103° 47' 14.241 W
2,100.0	2.10	214.82	2,100.0	-2.1	-1.5	668,908.82	667,713.44	32° 50' 15.809 N	103° 47' 14.257 W
2,200.0	3.60	214.82	2,199.8	-6.2	-4.3	668,904.74	667,710.61	32° 50' 15.769 N	103° 47' 14.291 W
2,300.0	5.10	214.82	2,299.6	-12.4	-8.6	668,898.51	667,706.27	32° 50' 15.708 N	103° 47' 14.342 W
2,400.0	6.60	214.82	2,399.0	-20.8	-14.5	668,890.14	667,700.46	32° 50' 15.625 N	103° 47' 14.411 W
2,500.0	8.10	214.82	2,498.2	-31.3	-21.8	668,879.64	667,693.15	32° 50' 15.522 N	103° 47' 14.497 W
2,600.0	9.60	214.82	2,597.0	-43.9	-30.5	668,867.01	667,684.37	32° 50' 15.397 N	103° 47' 14.601 W
2,700.0	11.10	214.82	2,695.4	-58.7	-40.8	668,852.26	667,674.11	32° 50' 15.252 N	103° 47' 14.722 W
2,800.0	12.60	214.82	2,793.2	-75.5	-52.5	668,835.41	667,662.38	32° 50' 15.085 N	103° 47' 14.860 W
2,900.0	14.10	214.82	2,890.5	-94.5	-65.7	668,816.45	667,649.20	32° 50' 14.899 N	103° 47' 15.016 W
3,000.0	15.60	214.82	2,987.2	-115.5	-80.3	668,795.42	667,634.57	32° 50' 14.691 N	103° 47' 15.189 W
3,100.0	17.10	214.82	3,083.2	-138.6	-96.4	668,772.31	667,618.49	32° 50' 14.463 N	103° 47' 15.378 W
3,121.5	17.42	214.82	3,103.7	-143.9	-100.1	668,767.06	667,614.85	32° 50' 14.412 N	103° 47' 15.421 W
3,200.0	17.42	214.82	3,178.6	-163.2	-113.5	668,747.78	667,601.43	32° 50' 14.221 N	103° 47' 15.580 W
3,300.0	17.42	214.82	3,274.0	-187.7	-130.6	668,723.20	667,584.33	32° 50' 13.979 N	103° 47' 15.782 W
3,400.0	17.42	214.82	3,369.4	-212.3	-147.7	668,698.62	667,567.24	32° 50' 13.737 N	103° 47' 15.984 W
3,500.0	17.42	214.82	3,464.8	-236.9	-164.8	668,674.04	667,550.14	32° 50' 13.494 N	103° 47' 16.185 W
3,523.2	17.42	214.82	3,487.0	-242.6	-168.8	668,668.32	667,546.17	32° 50' 13.438 N	103° 47' 16.232 W
<b>Grayburg</b>									
3,600.0	17.42	214.82	3,560.2	-261.5	-181.9	668,649.46	667,533.04	32° 50' 13.252 N	103° 47' 16.387 W
3,700.0	17.42	214.82	3,655.6	-286.1	-199.0	668,624.88	667,515.95	32° 50' 13.010 N	103° 47' 16.589 W
3,800.0	17.42	214.82	3,751.1	-310.6	-216.1	668,600.30	667,498.85	32° 50' 12.767 N	103° 47' 16.791 W
3,900.0	17.42	214.82	3,846.5	-335.2	-233.2	668,575.72	667,481.75	32° 50' 12.525 N	103° 47' 16.993 W

# ConocoPhillips

## Planning Report - Geographic

**Database:** EDM Central Planning  
**Company:** ConocoPhillips MCBU  
**Project:** Buckeye  
**Site:** Ruby Federal  
**Well:** Ruby Federal 27  
**Wellbore:** Ruby Federal 27  
**Design:** Slant Plan

**Local Co-ordinate Reference:** Well Ruby Federal 27  
**TVD Reference:** RKB @ 4024.0usft (PD 822)  
**MD Reference:** RKB @ 4024.0usft (PD 822)  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature

### Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
3,904.8	17.42	214.82	3,851.0	-336.4	-234.0	668,574.55	667,480.94	32° 50' 12.514 N	103° 47' 17.003 W
<b>San Andres</b>									
4,000.0	17.42	214.82	3,941.9	-359.8	-250.3	668,551.14	667,464.66	32° 50' 12.283 N	103° 47' 17.195 W
4,100.0	17.42	214.82	4,037.3	-384.4	-267.4	668,526.56	667,447.56	32° 50' 12.040 N	103° 47' 17.397 W
4,200.0	17.42	214.82	4,132.7	-409.0	-284.5	668,501.98	667,430.46	32° 50' 11.798 N	103° 47' 17.599 W
4,300.0	17.42	214.82	4,228.1	-433.5	-301.6	668,477.40	667,413.37	32° 50' 11.556 N	103° 47' 17.800 W
4,400.0	17.42	214.82	4,323.5	-458.1	-318.7	668,452.82	667,396.27	32° 50' 11.313 N	103° 47' 18.002 W
4,500.0	17.42	214.82	4,418.9	-482.7	-335.8	668,428.24	667,379.18	32° 50' 11.071 N	103° 47' 18.204 W
4,600.0	17.42	214.82	4,514.3	-507.3	-352.9	668,403.66	667,362.08	32° 50' 10.829 N	103° 47' 18.406 W
4,700.0	17.42	214.82	4,609.8	-531.9	-369.9	668,379.08	667,344.98	32° 50' 10.586 N	103° 47' 18.608 W
4,800.0	17.42	214.82	4,705.2	-556.5	-387.0	668,354.50	667,327.89	32° 50' 10.344 N	103° 47' 18.810 W
4,900.0	17.42	214.82	4,800.6	-581.0	-404.1	668,329.92	667,310.79	32° 50' 10.102 N	103° 47' 19.012 W
5,000.0	17.42	214.82	4,896.0	-605.6	-421.2	668,305.34	667,293.69	32° 50' 9.859 N	103° 47' 19.213 W
5,049.9	17.42	214.82	4,943.6	-617.9	-429.8	668,293.09	667,285.17	32° 50' 9.739 N	103° 47' 19.314 W
5,100.0	16.67	214.82	4,991.5	-629.9	-438.2	668,281.02	667,276.78	32° 50' 9.620 N	103° 47' 19.413 W
5,200.0	15.17	214.82	5,087.7	-652.5	-453.8	668,258.51	667,261.11	32° 50' 9.398 N	103° 47' 19.598 W
5,300.0	13.67	214.82	5,184.5	-672.9	-468.0	668,238.06	667,246.89	32° 50' 9.196 N	103° 47' 19.766 W
5,400.0	12.17	214.82	5,282.0	-691.3	-480.8	668,219.71	667,234.13	32° 50' 9.015 N	103° 47' 19.917 W
5,459.3	11.28	214.82	5,340.0	-701.1	-487.7	668,209.82	667,227.25	32° 50' 8.918 N	103° 47' 19.998 W
<b>Glorieta</b>									
5,500.0	10.67	214.82	5,380.0	-707.5	-492.1	668,203.45	667,222.82	32° 50' 8.855 N	103° 47' 20.050 W
5,544.7	10.00	214.82	5,424.0	-714.1	-496.7	668,196.86	667,218.24	32° 50' 8.790 N	103° 47' 20.104 W
<b>Paddock</b>									
5,600.0	10.00	214.82	5,478.4	-722.0	-502.2	668,188.99	667,212.76	32° 50' 8.712 N	103° 47' 20.169 W
5,700.0	10.00	214.82	5,576.9	-736.2	-512.1	668,174.73	667,202.84	32° 50' 8.572 N	103° 47' 20.286 W
5,800.0	10.00	214.82	5,675.4	-750.5	-522.0	668,160.48	667,192.93	32° 50' 8.431 N	103° 47' 20.403 W
5,900.0	10.00	214.82	5,773.9	-764.7	-531.9	668,146.22	667,183.01	32° 50' 8.290 N	103° 47' 20.520 W
6,000.0	10.00	214.82	5,872.4	-779.0	-541.8	668,131.97	667,173.10	32° 50' 8.150 N	103° 47' 20.637 W
6,100.0	10.00	214.82	5,970.8	-793.3	-551.8	668,117.71	667,163.18	32° 50' 8.009 N	103° 47' 20.754 W
6,200.0	10.00	214.82	6,069.3	-807.5	-561.7	668,103.46	667,153.27	32° 50' 7.869 N	103° 47' 20.871 W
6,297.2	10.00	214.82	6,165.0	-821.4	-571.3	668,089.61	667,143.63	32° 50' 7.732 N	103° 47' 20.985 W
<b>Blinberry</b>									
6,300.0	10.00	214.82	6,167.8	-821.8	-571.6	668,089.20	667,143.35	32° 50' 7.728 N	103° 47' 20.988 W
6,400.0	10.00	214.82	6,266.3	-836.0	-581.5	668,074.95	667,133.44	32° 50' 7.588 N	103° 47' 21.106 W
6,500.0	10.00	214.82	6,364.8	-850.3	-591.4	668,060.69	667,123.52	32° 50' 7.447 N	103° 47' 21.223 W
6,600.0	10.00	214.82	6,463.2	-864.5	-601.3	668,046.44	667,113.61	32° 50' 7.307 N	103° 47' 21.340 W
6,700.0	10.00	214.82	6,561.7	-878.8	-611.3	668,032.19	667,103.69	32° 50' 7.166 N	103° 47' 21.457 W
6,800.0	10.00	214.82	6,660.2	-893.0	-621.2	668,017.93	667,093.78	32° 50' 7.026 N	103° 47' 21.574 W
6,900.0	10.00	214.82	6,758.7	-907.3	-631.1	668,003.68	667,083.86	32° 50' 6.885 N	103° 47' 21.691 W
6,921.6	10.00	214.82	6,780.0	-910.4	-633.2	668,000.59	667,081.72	32° 50' 6.855 N	103° 47' 21.716 W
<b>Tubb</b>									
7,000.0	10.00	214.82	6,857.2	-921.6	-641.0	667,989.42	667,073.95	32° 50' 6.744 N	103° 47' 21.808 W
7,100.0	10.00	214.82	6,955.6	-935.8	-650.9	667,975.17	667,064.03	32° 50' 6.604 N	103° 47' 21.925 W
7,166.0	10.00	214.82	7,020.6	-945.2	-657.5	667,965.76	667,057.49	32° 50' 6.511 N	103° 47' 22.002 W
<b>Production</b>									
7,175.5	10.00	214.82	7,030.0	-946.6	-658.4	667,964.40	667,056.55	32° 50' 6.498 N	103° 47' 22.013 W

# ConocoPhillips

## Planning Report - Geographic

**Database:** EDM Central Planning  
**Company:** ConocoPhillips MCBU  
**Project:** Buckeye  
**Site:** Ruby Federal  
**Well:** Ruby Federal 27  
**Wellbore:** Ruby Federal 27  
**Design:** Slant Plan

**Local Co-ordinate Reference:** Well Ruby Federal 27  
**TVD Reference:** RKB @ 4024.0usft (PD 822)  
**MD Reference:** RKB @ 4024.0usft (PD 822)  
**North Reference:** Grid  
**Survey Calculation Method:** Minimum Curvature

### Design Targets

#### Target Name

- hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
Ruby Federal 27 (Plat BI - plan misses target center by 141.1usft at 5569.6usft MD (5448.5 TVD, -717.6 N, -499.2 E) - Circle (radius 150.0)	0.00	0.01	5,424.0	-831.7	-578.5	668,079.23	667,136.45	32° 50' 7.630 N	103° 47' 21.070 W


### Casing Points

Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (")	Hole Diameter (")
85.0	85.0	Conductor	16	20
830.0	830.0	Surface	8-5/8	12-1/4
7,166.0	7,020.6	Production	5-1/2	7-7/8

### Formations

Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
760.0	760.0	Rustler		0.00	
938.0	938.0	Salado		0.00	
1,960.0	1,960.0	Tansill		0.00	
3,523.2	3,487.0	Grayburg		0.00	
3,904.8	3,851.0	San Andres		0.00	
5,459.3	5,340.0	Glorieta		0.00	
5,544.7	5,424.0	Paddock		0.00	
6,297.2	6,165.0	Blinebry		0.00	
6,921.6	6,780.0	Tubb		0.00	


# Proposed Directional Well Plan



Project: Buckeye
Site: Ruby Federal
Well: Ruby Federal 27
Wellbore: Ruby Federal 27
Design: Slant Plan


WELL DETAILS: Ruby Federal 27					
+N/-S	+E/-W	North	Ground Level:	4011.0	
0.0	0.0	668910.92	Easting	667714.90	Latitude 32° 50' 15.830 N Longitude 47° 14.240 W

SECTION DETAILS										
Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	Vsect	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	1960.0	0.00	0.00	1960.0	0.0	0.0	0.00	0.00	0.0	
3	3103.7	17.42	214.82	3103.7	-143.9	-100.1	1.50	214.82	175.2	
4	4504.9	17.42	214.82	4943.6	-617.9	-429.8	0.00	0.00	752.6	
5	5544.7	10.00	214.82	5424.0	-714.1	-496.7	1.50	180.00	869.9	Ruby Federal 27 (Plat BHL)
6	7175.5	10.00	214.82	7030.0	-946.6	-658.4	0.00	0.00	1153.0	



CASING DETAILS			
TVD	MD	Name	Size
85.0	85.0	Conductor	16
830.0	830.0	Surface	8-5/8
7020.6	7166.0	Production	5-1/2


FORMATION TOP DETAILS		
TVDPath	MDPath	Formation
760.0	760.0	Rustler
938.0	938.0	Salado
1960.0	1960.0	Tansill
3487.0	3523.2	Grayburg
3851.0	3904.8	San Andres
5340.0	5459.3	Glorieta
5424.0	5544.7	Paddock
6165.0	6297.2	Blinberry
6780.0	6921.6	Tubb



# Attachment # 1

## BLOWOUT PREVENTER ARRANGEMENT

3M System per Onshore Oil and Gas Order No. 2 utilizing 3M and 5M Rated Equipment




Item	Description
1	Rotating Head, 11"
2A	Fill up Line and Valve
2B	Flow Line (10")
2C	Shale Shakers and Solids Settling Tank
2D	Cuttings Bins for Zero Discharge
2E	Rental Mud Gas Separator with vent line to flare and return line to mud system
3	Annular BOP (11", 3M)
4	Double Ram (11", 3M, equipped with Blind Rams and Pipe Rams)
5	Kill Line (2" flexible hose, 3000 psi WP)
6	Kill Line Valve, Inner (3-1/8", 3000 psi WP)
7	Kill Line Valve, Outer (3-1/8", 3000 psi WP)
8	Kill Line Check Valve (2-1/16", 3000 psi WP)
9	Choke Line (5M Stainless Steel Coflex Line, 3-1/8" 3M API Type 6B, 3000 psi WP)
10	Choke Line Valve, Inner (3-1/8", 3000 psi WP)
11	Choke Line Valve, Outer, (Hydraulically operated, 3-1/8", 3000 psi WP)
12	Adapter Flange (11" 5M to 11" 3M)
13	Spacer Spool (11", 5M)
14	Casing Head (11" 5M)
15	Ball Valve and Threaded Nipple on Casing Head Outlet, 2" 5M
16	Surface Casing

Submitted by: James Chen, Drilling Engineer, Mid-Continent Business Unit, ConocoPhillips Company, 25-Sep-2012

## CHOKE MANIFOLD ARRANGEMENT

3M System per Onshore Oil and Gas Order No. 2 utilizing 3M and 5M Equipment



Item	Description
1	Manual Adjustable Choke, 2-1/16", 3M
2	Remote Controlled Hydraulically Operated Adjustable Choke, 2-1/16", 3M
3	Gate Valve, 2-1/16" 5M
4	Gate Valve, 2-1/16" 5M
5	Gate Valve, 2-1/16" 5M
6	Gate Valve, 2-1/16" 5M
7	Gate Valve, 3-1/8" 3M
8	Gate Valve, 2-1/16" 5M
9	Gate Valve, 2-1/16" 5M
10	Gate Valve, 2-1/16" 5M
11	Gate Valve, 3-1/8" 3M
12	Gate Valve, 2-1/16" 5M
13	Pressure Gauge
14	2" hammer union tie-in point for BOP Tester

We will test each valve to 3000 psi from the upstream side.

Submitted by:

James Chen

Drilling Engineer, Mid-Continent Business Unit, ConocoPhillips Company

Date: 21-March-2013



## **Request for Variance**

### **ConocoPhillips Company**


Lease Number: NM LC 029405B

Well: Ruby Federal #27

Location: Sec. 17, T17S, R32E

Date: 10/29/2013

### **Request:**

 ConocoPhillips Company respectfully requests a variance to install a flexible choke line instead of a straight choke line prescribed in the Onshore Order No. 2, III.A.2.b Minimum standards and enforcement provisions for choke manifold equipment. This request is made under the provision of Onshore Order No. 2, IV Variances from Minimum Standard. The rig to be used to drill this well is equipped with a flexible choke line if the requested variance is approved and determined that the proposed alternative meets the objectives of the applicable minimum standards.

### **Justifications:**

The applicability of the flexible choke line will reduce the number of target tees required to make up from the choke valve to the choke manifold. This configuration will facilitate ease of rig up and BOPE Testing.

### **Attachments:**

- Attachment # 1 Specification from Manufacturer
- Attachment # 2 Mill & Test Certification from Manufacturer

### **Contact Information:**

Program prepared by:


James Chen

Drilling Engineer, ConocoPhillips Company

Phone (832) 486-2184

Cell (832) 768-1647

Date: 26 September 2012



## Reliance Eliminator Choke & Kill

This hose can be used as a choke hose which connects the BOP stack to the bleed-off manifold or a kill hose which connects the mud stand pipe to the BOP kill valve.

The Reliance Eliminator Choke & Kill hose contains a specially bonded compounded cover that replaces rubber covered Asbestos, Fibreglass and other fire retardant materials which are prone to damage. This high cut and gouge resistant cover overcomes costly repairs and downtime associated with older designs.

The Reliance Eliminator Choke & Kill hose has been verified by an independent engineer to meet and exceed EUB Directive 36 (700°C for 5 minutes).

Nom. ID		Nom OD		Weight		Min Bend Radius		Max WP	
in.	mm.	in.	mm	lb/ft	kg/m	in.	mm.	psi	Mpa
3	76.2	5.11	129.79	14.5	21.46	48	1219.2	5000	34.47
3-1/2	88.9	5.79	147.06	20.14	29.80	54	1371.6	5000	34.47

### Fittings

RC4X5055  
RC3X5055  
RC4X5575

### Flanges

R35 - 3-1/8 5000# API Type 6B  
R31 - 3-1/8 3000# API Type 6B

### Hammer Unions

All Union Configurations

### Other

LP Threaded Connectio  
Graylock  
Custom Ends





2030 E. 8th Street, Suite B • Greeley, CO 80631  
Ph: (970) 346-3751 • Fax: (970) 353-3168 • Toll Free: (866) 771-9739

## TEST CERTIFICATE

Customer: PRECISION DRILLING  
P.O. #: RIG 822  
Invoice #: 27792  
Material: 3 1/2" FIREGUARD  
Description: 3 1/2" X 10'  
Coupling 1: 3 1/2" FLANGE R31  
" Serial:  
" Quality:  
Coupling 2: 3 1/2" FLOATING R31  
" Serial:  
" Quality:  
Working Pressure : 3000  
Test Pressure: 7500  
Duration (mins): 10

Cert No.: 27792  
Date: 9/21/2012



Conducted By: FLORES M,  
Test Technician

☒ Acceptable  
☐ Not Acceptable

## Closed Loop System Design, Operating and Maintenance, and Closure Plan

ConocoPhillips Company  
Well: Ruby Federal #27  
Location: Sec. 17, T17S, R32E  
Date: 10/29/2013

ConocoPhillips proposes the following plan for design, operating and maintenance, and closure of our proposed closed loop system for the above named well:

1. We propose to use a closed loop system with steel pits, haul-off bins, and frac tanks for containing all cuttings, solids, mud, water, brine, and liquids. We will not dig a pit, nor will we use a drying pad, nor will we build an earth pit above ground level, nor will we dispose of or bury any waste on location.

All drilling waste and all drilling fluids (fresh water, brine, mud, cuttings, drill solids, cement returns, and any other liquid or solid that may be involved) will be contained on location in the rig's steel pits or in haul-off bins or in frac tanks as needed. The intent is as follows:

- We propose to use the rigs' steel pits for containing and maintaining the drilling fluids.
- We propose to remove cuttings and drilled solids from the mud by using solids control equipment and to contain such cuttings and drilled solids on location in haul-off bins.
- We propose that any excess water that may need to be stored on location will be stored in tanks.

**The closed loop system components will be inspected daily by each tour and any needed repairs will be made immediately. Any leak in the system will be repaired immediately, and any spilled liquids and/or solids will be cleaned immediately, and the area where any such spill occurred will be remediated immediately.**

2. Cuttings and solids will be removed from location in haul-off bins by an authorized contractor and disposed of at an authorized facility. For this well, we propose the following disposal facility:

R-360 Inc.  
4507 West Carlsbad Hwy, Hobbs, NM 88240,  
P.O. Box 388; Hobbs, New Mexico 88241  
Toll Free Phone: 877.505.4274, Local Phone Number: 432.638.4076

The physical address for the plant where the disposal facility is located is Highway 62/180 at mile marker 66 (33 miles East of Hobbs, NM and 32 miles West of Carlsbad, NM).

The Permit Number for R-360 is NM-01-0006.

A photograph showing the type of haul-off bins that will be used is attached.


3. Mud will be transported by vacuum truck and disposed of at R-360 Inc. at the facility described above.
4. Fresh Water and Brine will be hauled off by vacuum truck and disposed of at an authorized salt water disposal well. We propose the following for disposal of fresh water and brine as needed:
  - Nabors Well Services Company, 3221 NW County Rd; Hobbs, NM 88240, PO 5208 Hobbs, NM, 88241, Permit SWD 092. (Well Location: **Section 3, T19S R37E**)
  - Basic Energy Services, P.O. Box 1869; Eunice, NM 88231 Phone Number: 575.394.2545, Facility located at Hwy 18, Mile Marker 19; Eunice, NM.

James Chen  
Drilling Engineer  
Office: 281-206-5244  
Cell: 832.678.1647

# SPECIFICATIONS

## Heavy Duty Split Metal Rolling Lid

FLOOR: 3/16" PL one piece  
 CROSS MEMBER: 3 x 4-1 channel 16" on center  
 WALLS: 3/16" PL solid welded with tubing top, inside liner hooks  
 DOOR: 3/16" PL with tubing frame  
 FRONT: 3/16" PL slant formed  
 PICK UP: Standard cable with 2" x 6" x 1/4" rails, gusset at each crossmember  
 WHEELS: 10 DIA x 9" long with rease fittings  
 DOOR LATCH: 3 Independent ratchet binders with chains, vertical second latch  
 GASKETS: Extruded rubber seal with metal retainers  
 WELDS: All welds continuous except sub structure crossmembers  
 FINISH: Coated inside and out with direct to metal, rust inhibiting acrylic enamel color coat  
 HYDROTESTING: Full capacity static test  
 DIMENSIONS: 22'-11" long (21'-8" inside), 99" wide (88" inside), see drawing for height  
 OPTIONS: Steel grit blast and special paint, Ampliroil, Hell and Dino pickup  
 ROOF: 3/16" PL roof panels with tubing and channel support frame  
 LIDS: (2) 68" x 90" metal rolling lids spring loaded, self raising  
 ROLLERS: 4" V-groove rollers with delrin bearings and grease fittings  
 OPENING: (2) 60" x 82" openings with 8" divider centered on container  
 LATCH: (2) independent ratchet binders with chains per lid  
 GASKETS: Extruded rubber seal with metal retainers



CONT.	A	B
20 YD	41	53
25 YD	53	65
30 YD	65	77

