

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

HOBBS OCD

FORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FEB 19 2014

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

RECEIVED

1. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other		5. Lease Serial No. NMNM0448921A
2. Name of Operator WHITE OAK OPERATING CO LLC		6. If Indian, Allottee or Tribe Name
Contact: DAVID A EYLER E-Mail: DEYLER@MILAGRO-RES.COM		7. If Unit or CA/Agreement, Name and/or No.
3a. Address 12941 N. FREEWAY, SUITE 550 HOUSTON, TX 77060	3b. Phone No. (include area code) Ph: 432-687-3033	8. Well Name and No. MEXICO P FEDERAL 001
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 21 T26S R35E Mer NMP NENW 1980FNL 1980FWL		9. API Well No. 30-025-22405
		10. Field and Pool, or Exploratory ARENA ROJAS
		11. County or Parish, and State LEA COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
☒ Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off
☐ Subsequent Report	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	☐ Well Integrity
☐ Final Abandonment Notice	☐ Casing Repair	☐ New Construction	☐ Recomplete	☐ Other
	☐ Change Plans	☒ Plug and Abandon	☐ Temporarily Abandon	
	☐ Convert to Injection	☐ Plug Back	☐ Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomple horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recomple in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

- 1) DUMP BAIL 20' CMT. @ 15,420'-15,400'. 35' or spot 25' x 25' Class H' cmt.
2) JET CUT 2-7/8" TBG. @ +/-14,060'.
3) SET 7-5/8" CIBP @ 14,050'; DUMP BAIL 20' CMT. @ 14,050'-14,030'; CIRC. WELL 35' or spot 25' x 25' Class H' cmt.
4) PUMP 70 SXS.CMT. @ 12,598'-12,378' (7-5/8" LNR.TOP); WOC TAG
5) PUMP 120 SXS.CMT. @ 12,121'-11,901'(T/WC.); WOC X TAG CMT. PLUG.
6) PUMP 110 SXS.CMT. @ 9,540'-9,340'(T/B.S.); WOC X TAG CMT. PLUG.
7) PUMP 95 SXS.CMT. @ 7,085'-6,915'(MID-PLUG).
8) CUT X PULL 10-3/4" CSG. @ +/-5,320'.
9) PUMP 170 SXS.CMT. @ 5,395'-5,245'(10-3/4" STUB, 13-3/8" SHOE, T/DLWR.); TAG.
10) PUMP 125 SXS.CMT. @ 2,560'-2,440'(MID-PLUG); WOC X TAG CMT. PLUG.
11) PUMP 110 SXS.CMT. @ 853'-753'(20" CSG.SHOE); WOC X TAG CMT. PLUG.
12) MIX X CIRC. TO SURF. 60 SXS.CMT. @ 63'-3'.
Add: B/salt from 4915'-4765' WOC TAG.
1150'-1050' (T/salt) WOC TAG.

Ground Level Dry Hole Marker Required. Caution H₂S, circ. bottoms up (History)

14. I hereby certify that the foregoing is true and correct.	
Electronic Submission #232370 verified by the BLM Well Information System For WHITE OAK OPERATING CO LLC, sent to the Hobbs Committed to AFMSS for processing by JOHNNY DICKERSON on 01/28/2014 ()	
Name (Printed/Typed) DAVID A EYLER	Title AGENT
Signature (Electronic Submission)	Date 01/17/2014

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By <u>James G. Burns</u>	Title <u>SEAS</u>	Date <u>1-24-14</u>
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office <u>CFD</u>

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

Previous EC #231835, Same CDAs & Reclamation Objectives,
MDS/OCD 2/20/2014

FEB 20 2014

Additional data for EC transaction #232370 that would not fit on the form

32. Additional remarks, continued

13)DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD ON STEEL PLATE TO CSGS. X INSTALL DRY HOLE MARKER.

DURING THIS PROCEDURE WE PLAN TO USE THE CLOSED-LOOP SYSTEM WITH A STEEL TANK AND HAUL CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RULE 19.15.17.



White Oak Energy

Mexico P Federal #1

Well Name

Arena Rojas

Field

Lea County, New Mexico

County or Parish / State

28951

Serial Number

White Oak Operating Company, LLC

Operator

8-5-2011 CC

Date Updated

Sec 21 T26S R35E

Location

30-025-22405

API

KB: 3179

Elevation

GL: 3153 DF: 3178

30" conductor set @ 33'

36" Hole

20" set @ 803'

cmt'd w/ 1700 sxs cmt

26" Hole

13 3/8" 61# 66# 72# J55 & S80 STC Butt @ 5320'

cmt'd w/ 6700 sxs cmt

17 1/2" Hole

10 3/4" 60.7# set @ 13315'

cmt'd w/ 3400 sxs cmt

12 1/4" Hole

Strawn Perfs

14270'-14304'

14388'-14408'

15036'-15050'

Atoka Bank Perfs

15564'-15569' (47 shots) (2/25/90)

15572'-15594'

15598'-15606'

15608'-15616'

Perf & Sqz'd 15666'-15670'

7 5/8" 39# S-95 set @ 18605', cmt'd w/ 1200' sxs cmt

Silurian Perfs

19214'-19225'; 19382'-19398' (11/13/1989)

5" 23# P-110 w/ AB FL4S conn set @ 19531'

cmt'd w/ 295 sxs cmt

6 1/2" hole

Current Wellbore Status

CIRC. 60 SXS @ 63'-3"

Pump 110 SXS @ 853'-753' TAG

Pump 125 SXS @ 2520'-2440' TAG

Pump 170 SXS @ 5295'-5245'-TAG

CUT & PULL 10-3/4" CSB @ 5320'

Pump 95 SXS @ 7085'-6915'

Pump 110 SXS @ 9540'-9340'-TAG

Pump 120 SXS @ 12121'-11901'-TAG

Pump 70 SXS @ 12598'-12378'

Pump 32 1/2" 20' cmt @ 14050'-14030'

SET 7-5/8" CIBP @ 14050'

TOL @ 12488'

Pump 32 1/2" 20' cmt @ 15420'-15400'

Baker N:3 CIBP @ 15420'

TOL @ 17913'

5" 23# HOWCO EZ-SV 10' cmt on

top @ 19452'

TD: 22914'

TD: 22914' .PBD: 19452'