

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

HOBBS OCD

JAN 17 2014

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
 Santa Fe, NM 87505

RECEIVED

WELL API NO. 30-025-37995 ✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name EURO STATE ✓
8. Well Number 1 ✓
9. OGRID Number 155615
10. Pool name or Wildcat VACUUM; GRAYBURG-SAN ANDRES
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4114 GL

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
NADEL AND GUSSMAN PERMIAN, L.L.C. ✓

3. Address of Operator
601 N. MARIENFELD, SUITE 508, MIDLAND TX 79701

4. Well Location
 Unit Letter: M : 990 feet from the SOUTH line and 990 feet from the WEST line
 Section 5 Township 17S Range 34E NMPM County LEA

12. Check Appropriate Description of Nature of Notice, Report or Other Data

Approved for Plugging of well bore only.
 Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page under forms! www.emnrd.state.nm.us/oed

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 9/9/2013 RIH OPEN ENDED W/146 JTS, TAG CEMENT @ 4605'. CIRC. WELL W/60 BBLs & 15SX SALT GEL. PRESS TEST CSG TO 500 PSI FOR 15 MINS, HELD OK. POH, LD 58 JTS, 87 IN HOLE, SPOT 25SX C CEMENT FROM 2750' TO 2503'. POH STAND BACK 36 JTS. CLOSE WELL IN.
- 9/10/2013 RIH W/TBG FROM DERRICK. TAG CEMENT @ 2494', OK. PUMP 25SX CLASS C CEMENT 1580' - 1333' = 5.15. RIH W/WIRELINE TAG CEMENT @ 1318', OK. PERF RIH AND PERF @ 300', OK. CIRC. W/1 BBL OUT 8 5/8", OK. PUMP SURFACE PLUG 80SX 300-SURFACE, IN & OUT 5 1/2" CSG. CLOSE WELL IN.
- 9/11/2013 OPEN WELL, NO FLOW. CEMENT SET IN, OUT TO SURFACE. TAKE OFF VALVE, UN-FLANGE WELLHEAD. PUT ON DRY HOLE MARKER, WELD ON MARKER. COVER UP WELL & DRY HOLE MARKER, DIG OUT DEADMAN & COVER UP DEADMAN. CLEAN UP LOCATION. PUT UP EQUIPMENT.

Spud Date: 8/3/2006

Rig Release Date: 8/14/2006

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Stacey Peck TITLE: ENGINEER TECH DATE: JANUARY 14, 2014

Type or print name: STACEY PECK E-mail address: SPECK@NAGUSS.COM PHONE: (432) 682-4429

For State Use Only

APPROVED BY: Maley Brown TITLE: Compliance Officer DATE: 2/26/2014

Conditions of Approval (if any)

FEB 27 2014 JMF