

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

Revised August 1, 2011

HOBBS OCD

OIL CONSERVATION DIVISION

FEB 26 2014 1220 South St. Francis Dr.
Santa Fe, NM 87505

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-36876
1. Type of Well: Oil Well Gas Well X Other		5. Indicate Type of Lease STATE X FEE
2. Name of Operator CIMAREX ENERGY CO. OF COLORADO		6. State Oil & Gas Lease No.
3. Address of Operator 600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701		7. Lease Name or Unit Agreement Name STATE LF 30
4. Well Location Unit Letter O: 990 feet from the SOUTH line and 1490 feet from the EAST line Section 30 Township 16S Range 34E NMPM LEA County		8. Well Number 003
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4.131' - GR		9. OGRID Number 162683
		10. Pool name or Wildcat KEMNITZ; ATOKA-MORROW, S.(GAS)

12. Check Approval

Indicate Nature of Notice, Report or Other Data

NOTICE -
PERFORM REPAIRS
TEMPORARY
Approved for Plugging of well bore only.
Liability under bond is retained pending receipt of
C-103 (Specifically for Subsequent Report of Well
Plugging) which may be found at OCD web page
under forms
www.emnrd.state.nm.us/oed

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: WELL PLUGGED AND ABANDONED 02/21/14.

...ing any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02/12/14: SET CIBP @ 13,050'; PUMP 55 SXS.CMT. @ 13,050'-12,650'; CIRC. WELL; PUMP 35 SXS.CMT. @ 9,855'; WOC.

02/13/14: TAG CMT. @ 9,647'; PUMP 30 SXS.CMT. @ 8,826'-8,646'; PUMP 25 SXS.CMT. @ 8,077'-7,907'; PUMP 25 SXS.

CMT. @ 6,053'-5,903'; PUMP 25 SXS.CMT. W/ 2% CACL @ 4,605'; WOC X TAG CMT. @ 4,362'.

02/14/14: PUMP 25 SXS.CMT. @ 2,500'-2,380'; CIRC. 65 SXS.CMT. @ 475'-3'; PRES. @ SURF.; CIRC. CMT.OUT OF WELL.

02/15/14: PERF.SQZ. HOLES @ 1,000'(PER OCD); PRES. UP TO 1,250#; PUMP 30 SXS.CMT. @ 1050'.

02/16/14: TAG CMT. @ 924'; PERF. SQZ.HOLES @ 700'(PER OCD); PRES. UP TO 1,500# W/ SLIGHT BLEED OFF.

02/18/14: PUMP 30 SXS.CMT. @ 750'(PER OCD); WOC X TAG CMT. @ 525'.

02/19/14: PERF.SQZ.HOLES @ 475',250',100'(PER OCD); COULD PUMP INTO EACH SET OF PERFS. @ HIGH PRES.

02/20/14: SPOT 61 SXS.CMT.@ 500'; SQZ.FROM SURF. 100 SXS.CMT.@ 950#; CWI FOR 45 MINS. X SQZ. 190 SXS.CMT.

@ 950#; CWI W/ 250# X WOC.

02/21/14: OPEN WELL - NO PRES.; DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; TAG CMT. @ 3' IN 5-1/2" X 13-3/8", 5' IN 9-5/8"; FILL ALL ANNULI TO SURF. W/ DRY CMT. (PER OCD); WELD STEEL PLATE ON CSGS. X INSTALL DRY HOLE MARKER.

Spud Date:

MIRU: 02/09/14

Rig Release Date:

RDMO: 02/21/14

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

David A. Eyler

TITLE:

AGENT

DATE: 02/25/14

Type or print name: DAVID A. EYLER

E-mail address: DEYLER@MILAGRO-RES.COM

PHONE: 432.687.3033

For State Use Only

APPROVED BY:

Mark Whitman

TITLE

Compliance Officer

DATE

02/28/2014

Conditions of Approval (if any):

MAR 07 2014