

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OGD Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Revised July 18, 2013

MAR 14 2014

RECEIVED

WELL API NO. 30-025-08488
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No. E-5896
7. Lease Name or Unit Agreement Name Bell Lake Unit State
8. Well Number 1
9. OGRID Number 012361
10. Pool name or Wildcat Bell Lake (Bone Springs)

SUNDRY NOTICES AND REPORTS ON WELLS
1. Type of Well: Oil Well [X] Gas Well [] Other []
2. Name of Operator Kaiser-Francis Oil Company
3. Address of Operator P.O. Box 21468, Tulsa, OK 74121-1468
4. Well Location Unit Letter N Section 31 Township 23S Range 34E NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3816' GR

12. Check appropriate box to indicate Nature of Notice, Report or Other Data

Approved for Plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page under forms! www.emnrd.state.nm.us/oocd

SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A [X]
CASING/CEMENT JOB []
OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 1. 3/1/14: Began Plugging job. Ran cement bond log and found TOC @ 3460'. Tagged PBTD @ 6698'.
2. Circulated hole w/plug mud from 6698'.
3. Spotted 41 sx cmt from 6070'-5825'; tagged plug @ 5825'.
4. Perf'd squeeze holes in 7" @ 3080', RIH w/cement retainer. Stuck retainer at 75'; rec'd approval from NMOCD to cement from 75'. Circulated 673 sx cement, filling both 7" csg and 7"x 9 5/8 annulus from 3080' to surface with cement. Well P&A'd on 3/12/14.

Spud Date: [] Rig Release Date: []

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Teresa R. Mixon TITLE Regulatory Compliance Analyst DATE 3/12/2014

Type or print name Teresa Mixon E-mail address: TeresaMi@kfoc.net PHONE: 918-491-4591

APPROVED BY: Malory Brown TITLE Compliance Officer DATE 3/18/2014

MAR 19 2014

AM 02/2