Submit   Copy To Appropriate District OBBS OCD   State of New Mexico	Form C-103
Office District I – (575) 393-6161  Energy, Minerals and Natural Resources	Revised August 1, 2011
1625 N. French Dr., Hobbs, NM 88240PR 0 2 2014  District II - (575) 748-1283	WELL API NO. 30-025-41552
811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III - (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410  District IV - (505) 476-3460  1220 South St. Francis Dr.  Santa Fe, NM 87505	STATE FEE X
District IV – (505) 476-3460 1220 S. St. Francis Or., Santa Fe, NM	6. State Oil & Gas Lease No.
87505	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	B F Harrison B
PROPOSALS.)  1. Type of Well: Oil Well  Gas Well  Other	8. Well Number 29
2 Name of Operator	9. OGRID Number 4823 <b>355</b> 165
Brammer Engineering, Inc	
3. Address of Operator	10. Pool name or Wildcat
400 Texas St, Ste 600, Shreveport, LA 71101	
4. Well Location Unit Letter E : 1380 feet from the North line and	440 feet from the West line
Section 9 Township 23S Range 37E	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR,	
3316 GR	
12. Check Appropriate Box to Indicate Nature of Noti	ce, Report or Other Data
NOTICE OF INTENTION TO:	JBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK   PLUG AND ABANDON   REMEDIAL W	
	DRILLING OPNS.□ P AND A □
PULL OR ALTER CASING  MULTIPLE COMPL  CASING/CEM	ENT JOB
DOWNHOLE COMMINGLE	*
OTHER: OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.	Completions: Attach wellbore diagram of
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp	Completions: Attach wellbore diagram of eleting the well.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.	Completions: Attach wellbore diagram of eleting the well.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).	Completions: Attach wellbore diagram of eleting the well.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:	Completions: Attach wellbore diagram of eleting the well.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes: Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld)	Completions: Attach wellbore diagram of eleting the well.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:	Completions: Attach wellbore diagram of eleting the well.  As cement (details below); Production csg depth
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:  Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld)  Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld)	Completions: Attach wellbore diagram of eleting the well. es cement (details below); Production csg depth elet + 5% Salt (12.4 ppg, 2.12 yld)
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:  Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld)  Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld)  Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Sea	Completions: Attach wellbore diagram of eleting the well. es cement (details below); Production csg depth elet + 5% Salt (12.4 ppg, 2.12 yld)
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:  Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld)  Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld)  Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Sea	Completions: Attach wellbore diagram of eleting the well. es cernent (details below); Production csg depth elet + 5% Salt (12.4 ppg, 2.12 yld)
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes: Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld) Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld) Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal	Completions: Attach wellbore diagram of eleting the well. es cernent (details below); Production csg depth elet + 5% Salt (12.4 ppg, 2.12 yld)
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:  Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld)  Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld)  Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Sea	Completions: Attach wellbore diagram of eleting the well. es cement (details below); Production csg depth elet + 5% Salt (12.4 ppg, 2.12 yld)
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes: Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld) Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld) Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal	Completions: Attach wellbore diagram of eleting the well. es cement (details below); Production csg depth elet + 5% Salt (12.4 ppg, 2.12 yld)
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:  Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld)  Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld)  Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal  Tail - 330 sxs 50/50 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal	Completions: Attach wellbore diagram of eleting the well.  As cement (details below); Production csg depth  Al + 5% Salt (12.4 ppg, 2.12 yld)  + 5% Salt (14.20 ppg, 1.32 yld)
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes: Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld) Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld) Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal	Completions: Attach wellbore diagram of eleting the well.  As cement (details below); Production csg depth  Al + 5% Salt (12.4 ppg, 2.12 yld)  + 5% Salt (14.20 ppg, 1.32 yld)
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:  Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld)  Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld)  Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal  Tail - 330 sxs 50/50 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal	Completions: Attach wellbore diagram of eleting the well.  As cement (details below); Production csg depth  at + 5% Salt (12.4 ppg, 2.12 yld)  + 5% Salt (14.20 ppg, 1.32 yld)  edge and belief.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes:  Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld)  Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld)  Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal  Tail - 330 sxs 50/50 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal	Completions: Attach wellbore diagram of eleting the well.  As cement (details below); Production csg depth  al + 5% Salt (12.4 ppg, 2.12 yld)  + 5% Salt (14.20 ppg, 1.32 yld)  edge and belief.
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes: Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld) Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld) Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal Tail - 330 sxs 50/50 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal  Spud Date:  Rig Release Date:  Title Co-Admin, Regulatory	Completions: Attach wellbore diagram of eleting the well.  As cement (details below); Production csg depth  Al + 5% Salt (12.4 ppg, 2.12 yld)  + 5% Salt (14.20 ppg, 1.32 yld)  edge and belief.  Dept  DATE  4-2-14  en@brammer.com  PHONE: 318-429-2277
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes: Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld) Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld) Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal Tail - 330 sxs 50/50 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal  Spud Date:  Rig Release Date:  Title Co-Admin, Regulatory Type or print name Adonya Dryden  E-mail address: adonya.dryde	Completions: Attach wellbore diagram of eleting the well.  As cement (details below); Production csg depth  Al + 5% Salt (12.4 ppg, 2.12 yld)  + 5% Salt (14.20 ppg, 1.32 yld)  edge and belief.  Dept  DATE  4-2-14  en@brammer.com  PHONE: 318-429-2277
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple proposed completion or recompletion.  Brammer Engineering, Inc has taken over this permit from Chevron for drilling and comp Change to new APD (well not spudded yet): Surface csg depth changed to 1145', 470 st changed to 4100', 620 sxs cement (details below).  Cement Proposal Changes: Surface: Lead - 280 sxs Class C + 2% CaCl2 - Flake (Accelerator) (13.50 ppg, 1.58 yld) Tail - 190 sxs Class C + 1% CaCl2 - Flake (Accelerator) (14.80 ppg, 1.34 yld) Production: Lead - 290 sxs 35/65 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal  Tail - 330 sxs 50/50 Poz/Class C + 0.6% Halad (R)-9 + 0.125 lb/sk Kol-Seal  Spud Date:  Rig Release Date:  Title Co-Admin, Regulatory  Type or print name Adonya Dryden  E-mail address: adonya.dryde	Completions: Attach wellbore diagram of eleting the well.  As cement (details below); Production csg depth  Al + 5% Salt (12.4 ppg, 2.12 yld)  + 5% Salt (14.20 ppg, 1.32 yld)  edge and belief.  Dept  DATE  4-2-14  en@brammer.com  PHONE:  318-429-2277