

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources
HOBBS OGD
OIL CONSERVATION DIVISION
220 South St. Francis Dr.
Santa Fe, NM 87505
APR 16 2014

Form C-103
Revised July 18, 2013

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	7. Lease Name or Unit Agreement Name: Dragon 36 State
2. Name of Operator EOG Resources, Inc.	8. Well Number 6H
3. Address of Operator P.O. Box 2267 Midland, TX 79702	9. OGRID Number 7377
4. Well Location Unit Letter <u>0</u> : <u>220</u> feet from the <u>South</u> line and <u>1965</u> feet from the <u>East</u> line Section <u>36</u> Township <u>24S</u> Range <u>33E</u> NMPM County <u>Lea</u>	10. Pool name or Wildcat Red Hills; Upper Bone Spring Shale
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3471' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
TEMPORARILY ABANDON CHANGE PLANS
PULL OR ALTER CASING MULTIPLE COMPL
DOWNHOLE COMMINGLE
CLOSED-LOOP SYSTEM
OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
COMMENCE DRILLING OPNS. P AND A
CASING/CEMENT JOB
OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC.. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 4/7/14 Ran 118 jts 9-5/8", 40#, (25) FS-80 & (93) J55 casing set at 5107'.
4/8/14 Cemented lead w/ 1975 sx Class C, 12.7 ppg, 2.22 yield;
tail w/ 200 sx Class C, 14.8 ppg, 1.35 yield.
Circulated 35 sx cement to surface. WOC 25 hrs.
4/9/14 Tested casing to 2000 psi for 30 minutes. Test good.
Resumed drilling 8-3/4" hole.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stan Wagner TITLE Regulatory Analyst DATE 04/10/2014

Type or print name Stan Wagner E-mail address: _____ PHONE 432-686-3689

For State Use Only
APPROVED BY Mary Brown TITLE Dist. Supervisor DATE 4/16/2014

Conditions of Approval (if any):

APR 16 2014