

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-28610
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Endurance Resources LLC		6. State Oil & Gas Lease No. V-732
3. Address of Operator 203 West Wall Suite 1000 Midland TX		7. Lease Name or Unit Agreement Name New Mexico DL State
4. Well Location Unit Letter J : 1980 feet from the south line and 1650 feet from the east line Section 18 Township 23S Range 33E NMPM Lea County NM		8. Well Number 5
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3701' GR		9. OGRID Number 270329
		10. Pool name or Wildcat Cruz; Delaware

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Set CIBP @ 5100', cap with 100' cement. Top Perf @ 5110'.  
Top Delaware Sand 5110'.

Circulate heavy mud. Spot 25 sacks cement @ 3280'. Spot 25 sacks cement @ 1280'. Top Salt.

Spot 100' cement 641-741'. Casing shoe @ 691', 25 sacks surface plug. WOC & TAG. OR 60' - SURFACE

Cut off wellhead and install dry hole marker.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Geologist

DATE April 30, 2014

Type or print name Randall L. Harris

randall@enduranceresourcesllc.com

PHONE: 432/242-4680

For State Use Only

APPROVED BY:

TITLE

Dist. Supervisor

DATE

5/6/2014

Conditions of Approval (if any):

MAY 06 2014

ENDURANCE RESOURCES LLC

NEW MEXICO DC STATE 5

30-025-28610

