

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-025-25225
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. N/A
7. Lease Name or Unit Agreement Name SFPRR
8. Well Number 16
9. OGRID Number 288173
10. Pool name or Wildcat Sawyer San Andres West
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3967' GR

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Stanolind Operating DBA Stanolind NM LLC

3. Address of Operator
310 W. Wall, Suite 1000, Midland, Texas 79701

4. Well Location
 Unit Letter E : 1980 feet from the North line and 660 feet from the West line
 Section 34 Township 9S Range 37E NMPM Lea County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3967' GR

HOBS OCD
 MAY 09 2014

RECEIVED

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE
 CLOSED-LOOP SYSTEM
 OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8 5/8" 24# casing set @ 439', cemented w/ 300 sx Class "C", circulated to surface
 4 1/2" 10.5# casing set @ 5010', cemented w/ 320 sx Howco Lite and 200 sx Class "C" 50-50 poz, cement top 1750' (calc)
 San Andres perforations 4962-4992'.

Stanolind proposes to plug and abandon as follows:

- Set CIBP @ 4900, dump 2 sx Class "C" cement on plug **35' by w.l. / OR 25 SXS CMT BY TBG.**
- TIH and displace with mud laden fluid.
- Spot **25** 20 sx Class "C" cement from 2934' to 2834'. ~~If hole is not standing full~~, WOC and tag.
- Perforate and squeeze 35 sx Class "C" cement from 2253' to 2153'. ~~If hole is not standing full~~, WOC and tag.
- Perforate the 4 1/2" casing @ 489', circulate cement to surface, leaving the hole full of cement. Estimated volume is 140 sx.
- Cut off wellhead and install P&A marker plate (location within LPC area).
- Clean and level location.

A closed-loop system will be used. Notice will be given 24 hours before setting all plugs.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bel H. Pi TITLE Ex. VP OPERATIONS DATE 5/7/14

Type or print name _____ E-mail address: _____ PHONE: _____

For State Use Only

APPROVED BY: Maley Brown TITLE Dist. Supervisor DATE 5/13/2014

Conditions of Approval (if any)

MAY 13 2014

PRIOR TO P&A

Stanolind Operating LLC DBA Stanolind Operating NM LLC

WELL NAME:	SFPRR 16			FIELD:	West Sawyer San Andres		
LOCATION:	S34 T9S R37E			API #:	30-025-25225		
COUNTY:	Lea	ST:	NM	SPUD DATE:	02/01/76		
KB:	3978'	GL:	3967'	TD:	5057'	PBTD:	

8 5/8" @ 439' cmt'd w/ 300 sx (circ)

Formation Tops:

Top anhydrite 2253'
Base of salt 2934'
San Andres 4212'

TOC 1750' (calc)


Perfs 4962-4992'

4 1/2" @ 5010' Cmt'd w/ 320 sx Howco Lite and 200 sx Class "C" 50-50 poz

TD 5010'

AFTER P&A

WELL NAME:	SFPRR 16		FIELD:	West Sawyer San Andres	
LOCATION:	S34 T9S R37E		API #:	30-025-25225	
COUNTY:	Lea	ST:	NM	SPUD DATE:	02/01/76
KB:	3978'	GL:	3967'	TD:	5057'
PBTD:					




8 5/8" @ 439' cmt'd w/ 300 sx (circ)

Perf @ 560' and circulate cement to surface, estimated 135 sx

Formation Tops:

Top anhydrite 2253'
 Base of salt 2934'
 San Andres 4212'



TOC 1750' (calc)

35 sack cement plug @ 2253'

20 sack cement plug @ 2934'

CIBP @ 4900' plus 20' of cement

Perfs 4962-4992'

TD 5010'

4 1/2" @ 5010' Cmt'd w/ 320 sx Howco Lite and 200 sx Class "C" 50-50 poz